


Still Questioning The Accuracy Of Your Test Equipment?



Why Risk It

When it comes to the accuracy of your frequency counters, you cannot afford to look into a crystal ball for answers. The 3000A Plus w/TCXO and 8040 w/OCXO provide the accuracy you require, at prices up to four times less than other frequency counters with similar specifications. Optoelectronics frequency counters, reliable solutions for your RF testing needs.



3000APlusTCXO

- •10Hz 3GHz Handheld Frequency Counter
- Patented Digital Auto Filter and Auto Capture
- ·16 segment signal strength bargraph
- ·Multifunction counter with Period, Ratio, and Time Interval
- .1ppm TCXO
- •<600uV@ 400MHz sensitivity</p>
- ·Built-in RS232 for datalogging
- ·Built-in 800MHz high pass filter

8040

- •10Hz 3GHz Bench Frequency Counter
- •Patented Digital Auto Filter and Auto Capture
- •16 segment signal strength bargraph
- ·Multifunction counter with Period, Ratio, and Time Interval
- .02ppm OCXO ovenized timebase, <600uV sensitivity
- AC/DC Coupling, external clock input
- Built-in RS232 for datalogging
- ·Built-in NiCads for portable operation

FACTORY DIRECT ORDER LINE 800-327-5912

5821 NE 14th Avenue • Ft. Lauderdale, FL • 33334

Telephone: 954-771-2050 Fax: 954-771-2052 EMail: sales@optoelectronics.com Visa, MasterCard, C.O.D, Specifications are subject to change without notice or obligation

www.optoelectronics.com



KVG.02ppm
Ovenized timebase
used in NATO
Communication
Receivers for military operations.

Circle (1) on Fast Fact Card
MADE IN U.S.A

What Allows Our Mobile Radio To Rise Above the Competition?



The Features.

Standard Features

- Front Firing Speaker
- 25/12.5 kHz Narrowband Operation
- 6.25 kHz Frequency Stepping
- · LCD Alpha-Numeric Display
- Five Programmable Function Keys
- · Two-Levels of Priority Scanning
- Eight Character Alpha Tags
- LTR® Compatible

LTR-Net™ Features

- Unique Radio ID
- Electronic Serial Number Identification
- Direct Radio-to-Radio Calls*
- Direct Inward-Dialed Phone Calls*
- Backward Compatible with Existing LTR Systems
- Cross-Band Calling Between Subscribers on UHF, 800 and 900 MHz channels
- Over-the-Air Management
- Roaming with Auto-Registration

* DTMF microphone required.

Voice Privacy Features

- Plug-In Scrambling
- · High and Medium Security Options
- · Hop Rates Up to 1000 Times a Second
- Automatic Reception of Secure and Non-Secure Signals
- Over-the-Air Programming With Radio Disable
- Compatible With Transcrypt CVP® Scrambling (SC20-410/430/460)
- Front Panel Clear/Code Activation
- Visual Clear/Code Mode Indication on LCD Display




4800 NW 1st Street • Lincoln, NE 68521 U.S.A. 800-765-5365 • 402-474-4800 • Fax 402-474-4858 www.transcrypt.com MOBILE RADIO TECHNOLOGY ®

Technical information for paging, trunking and private wireless networks.

contents

September 1998



On the cover: As site buildouts continue, CDMA-based service providers seek ways to optimize system performance.

Graphic courtesy of Celwave; cover design by Scott Dolash, associate art director. See story on page 18.

features

18 Optimizing performance and maximizing capacity in CDMA systems

Andrew Singer

Several techniques can improve the performance and capacity of CDMA systems. RF engineers now realize that CDMA offers an opportunity to trade off capacity, coverage and call quality.

19 Some criteria for evaluating antennas

Dwight Staehler

A checklist of technical questions can help determine if an antenna qualifies as defective per a manufacturer's warranty.

24 Voice quality in PCS and cellular networks: Eliminating echo Doug Stuard

Improvements in digital communications technology can actually aggravate problems, such as echo, that are unnoticeable in analog systems. The use of echo cancelers is one way to improve voice quality.

34 PCS: A threat to SMR?

Donald E. Koehler

Will hungry, new-start, PCS companies gobble up SMR customer bases by offering multiple services? The smart SMR operator will see an immediate opportunity in many market areas—particularly in one area not usually seen as a potential for radio system owners.

38 Improving PCS reliability through cell frequency management E. Kirk Ellis

Adding additional neighbors to each sector builds in a strategy for improving system reliability with no additional cost in hardware.

42 Due process goes south in deal with north

Robert H. Schwaninger Jr.

The secret deal for Canadian SMR channels.

departments

4 Editorial

Don Bishop Making a difference

8 Calendar Editorial index

10 Editorial forum

Nikki Chandler
A failure to communicate

12 Letters

14 In the public interest

Robert H. Schwaninger Jr. Son of Sam

48 Technically speaking Harold Kinley, C.E.T.

The backup plan (Plan B?)

50 News

RFS Cablewave moves into new facility

55 Product focus

Paging system equipment

56 Products

Motorola's Customer-Owned Messaging Group is the Readers' Choice.

- 62 Media
- 63 People
- 64 Classified
- 80 Ad index

Vol. 16, Issue 9. Mobile Radio Technology (ISSN 0745-7626) is published monthly by PRIMEDIA Intertec, 9800 Metcalf Ave., Overland Park, KS 66212-2215, and is mailed for free to qualified subscribers within the United States and Canada. Periodicals postuge paid at Shawnce Mission, KS, and additional mailing offices. Canada Post International Publications Mail (Canadian Distribution) Sales Agreement No. 0956309.

POSTMASTER: Send address changes to Mobile Radio Technology, P.O. Box 12960, Overland Park, KS 66282-2960.

SUBSCRIPTIONS: Non-qualified subscribers may subscribe at the following rates: United States and Canada: one-year: \$35. Qualified and non-qualified subscribers in all other countries; one-year: \$45 (surface mail); \$105 (air mail). Subscription information: P.O. Box 12937, Overland Park, KS, 66282-2937.



Broadband Collinear Antenna

- 154 MHz Bandwidth
- 8 dBd gain
- 10° Vertical Beamwidth
- 1000 Watt Power Handling
- 225 mph Rated Wind Velocity

Visit us at PCS '98 Booth #3629

With three patents pending, this omnidirectional collinear array antenna adds a new dimension to conventional base station antenna coverage. Its true corporate-feed design improves pattern control, allowing higher gain from a shorter antenna. At only 9.5 feet, it's built to survive ice and the fiercest storms. With optional 3° or 5° downtilt, plus one model covering SMR, Paging, GSM and Cellular applications, this antenna is the first to offer "one-size-fits-all" performance for virtually any application.

Model No. 101-90-08-0-01

Operates with 1.35:1 VSWR over the entire 806-960 MHz range.

TX RX Systems Inc. 8625 Industrial Pkwy. Angola, NY 14006 Ph: 716-549-4700 Fax: 716-549-4772 Email: sales@txrx.com Web Site: www.txrx.com



TECHNOLOGIES GROUP

Circle (5) on Fast Fact Card

editorial

Making a difference



FCC Commissioner Gloria Tristani addressed the annual conference for the Associated Public-Safety Communications Officials on Aug. 10 in Albuquerque. NM. FCC commissioners. you see, traditionally take an area of focus within telecommunications, and Tristani has expressed an interest in public safety communications. Commissioner Michael Powell, for example, is known as the defense commissioner. None of the four new commissioners nor the veteran. Susan Ness, has (as far as we know) expressed a particular interest in private land mobile radio, or private wireless, as some have begun to call it.

"I know that the public safety community has identified three critical issues in the area of spectrum: insufficient frequencies overall; the need for interoperability among diverse agencies and jurisdictions: and the need for future flexibility to avail yourselves of new developments in technology." Tristani said.

Referring to the commission's Aug. 6 release of service rules for 24MHz of spectrum in the 700MHz band for public safety communications, Tristani said: "Our service and licensing rules for this new 24MHz will give you tools to meet these needs.

Let's stop for a moment and consider. The public safety lobby has stated a need for about 100MHz of spectrum to meet its needs. Portions of the 24MHz may soon be made available, but long delays may be experienced by would-be licensees in large

cities where the spectrum is tied up by TV stations.

The matter of interoperability can be a point of disagreement. For some, interoperability means second-sourcing; that is, various manufacturers' equipment will work on a given public safety radio network. That kind of interoperability allows competition to drive prices closer to cost, reducing expenses for public safety agencies.

For others—some manufacturers, in this case—interoperability means: "If you buy my radio system for countywide [or whatever jurisdiction] communications, then all of the city and county agencies can communicate with one another using our brand of radios."

From the federal government's perspective, interoperability seems to mean the ability of federal, state and local agencies to communicate with one another when their employees are responding to the same incident or who could benefit from the same information.

"We all know the stories." Tristani said.
"Like the officers who stopped a man who kidnapped, and later murdered, a little girl—who stopped him from trespassing, and who thought his behavior odd. But, who had no cause to hold him because they had no immediate access to his criminal record, and they could not hear the announcement of the kidnapping, broadcast by another department on a different channel.

"Or, like the local rescue workers who recently responded to a terrible car crash near a military base. One of the vehicles was badly crushed and the 'jaws of life' were called in to cut the frame of the car and release the driver. When the 'jaws of life' blew a hydraulic hose, a desperate call went out for a replacement. One was found 30 minutes away, but by the time it arrived, the driver had died. Only then did rescue personnel discover a spare hose, sitting the whole time in a military truck, not 100 yards away, but unused because the military units were on a different radio system and they couldn't hear the distress call."

Whether the new 24MHz of spectrum will help to reconcile these viewpoints of interoperability remains to be seen, but at least it will provide an opportunity for new system configurations that can allow various government authorities to consider the alternatives. U.S. Sen. John McCain (R-AZ) and FCC Chairman William E. Kennard have exchanged letters in the latest round of congressional efforts to oversee and direct the commission's work. McCain is chairman of the Committee on Commerce, Science and Transportation, which has responsibilty for overseeing the commission's work and for developing telecommunications legislation.

On June 24, McCain wrote to Kennard to express dissatisfaction with the commission's lack of action for several years in resolving a matter connected with license application mills that has tied up 220MHz licenses. Had the matter been resolved quickly, those frequencies might have been released to private users. Now, however the matter is resolved the frequencies are set to be auctioned.

Sometimes the FCC votes in an open meeting; sometimes a matter is "circulated" from one commissioner's office to another for a voting process that extends over days or weeks. Chairman Kennard responded on July 9 to say that an order to resolve the matter began circulating on June 26; that he voted on it on June 29; and that the rest of the commissioners were expected to vote by July 16.

On July 31, the FCC released its order, which was adopted on July 16 as scheduled. It reinstates some licenses that were canceled, upholds the cancelation of others, and schedules a time for publishing the order in the Federal Register to make it effective.

None of this probably will make any difference to the license-holders, who are unlikely to recover much, if anything, of their investment. None of this probably will make any difference to private wireless operators, who are likely to be closed out of a process to reassign the licenses. And, oddly enough, none of this probably came about because of McCain's letter. The FCC probably was motivated to "clear the title" to the frequencies so they could be auctioned. Were it not for the pending auction, the matter may have continued unresolved indefinitely. Not that it would have made any difference.


Don Bishop

A secure avenue into wireless utopia ...

Ponder for a minute ...

Information superhighways, on-ramps, speed bumps. Webs of destruction and deceit. Who has time for that?

Remember what got you here. No gimmicks, no monkey business; just solid RF design strategies coupled with selecting the best infrastructure on the market.



At DAPA we offer a most comprehensive product line of site antennas, keeping in line with RF planning, aesthetics and zoning restrictions. We concentrate on a proven metal strip-line feed technology, unlike any other. It is proven to produce continuous peak performance, repeatability and peace of mind.

Not to mention our approved vendor status in cellular and PCS networks around the globe, including the first operational PCS system in the United States.

Oh yeah, and don't forget to tangle with us on the web, http:\\www.dapacom.com, where you can get the latest in product developments, antenna data, patterns, and spec sheets.

Ponder no longer.



DAPA Communications, Inc. • Allegany, New York 14706 USA Int'l Tel +1 716 373 7228 • Int'l Fax +1 716 373 5758 • http://www.dapacom.com



REGULATORY CONSULTANT

Robert H. Schwaninger Jr., Brown and Schwaninger, Washington, DC

EDITORIAL ADVISORY BOARD

John Abbey, The Abbey Group Gene A. Buzzi, Omnicom Telecommunications Engineering Jack Daniel, The Jack Daniel Company

Gary David Gray, P.E., Orange County Communications

Frederick G. Griffin, P.E., Frederick G. Griffin P.C. Jim Hendershot, Radio Design Group Mary Kjorvestad, Nextel Communications Samuel J. Klein, Cellular Design S.R. McConoughey, P.E., Mobile Communications

Consulting
Art McDole, Salinas, CA
Tony Sabino, Regional Communications

Herb Sachs, Herb Sachs Consulting Robert C. Shapiro, P.E., Strategic Telecommunications

Leon Spencer, Exxon Computing Services Company

Gregory M. Stone, Ph.D., Quantum Radionics Raymond C. Trott, P.E., Trott Communications Group

William A. Wickline, P.E., Mentor, OH

EDITORIAL

Don Bishop, Editorial Director
David Keckler, Features Editor
Nikki Chandler, Associate Editor
Emily Reid, Editorial Assistant
Erica Thesing, Editorial Intern
Harold Kinley, C.E.T., Contributing Editor

DESIGN

Scott Dolash, Associate Art Director

BUSINESS

Cameron Bishop, President, Communications & Entertainment Division
Mercy Contreras, Group Publisher
Patricia Zahner, Director of Marketing
Scott Hanna, Advertising Production Coordinator
Nancy Hupp, Director, Corporate Advertising
Services

Patti Lee, Classified Advertising Coordinator
Tom Cook, Group Senior Managing Editor
Doug Coonrod, Corporate Creative Director
Stephanie Hanaway, Director of Marketing and Communications, Exhibitions & Conferences Division

PRIMEDIA Intertec

Raymond E. Maloney, President and CEO
Nick Cavnar, Vice President of Circulation
Barbara Kummer, Circulation Director
Julie Neely, Circulation Manager
Customer Service, 800-441-0294 or 913-341-0294
PRIMEDIA Specialty Magazines

James A. Warner, President

PRIMEDIA Inc.

William F. Reilly, Chairman and CEO Charles McCurdy, President Beverly C. Chell, Vice Chairman CORRESPONDENCE: Editorial correspondence should be addressed to P.O. Box 12901, Overland Park, KS 66282-2901. tel. 913-341-1300; fax: 913-967-7250; mrt@intertec.com

MOBILE RADIO TECHNOLOGY provides technical information to dealers, community repeater operators, specialized mobile radio operators, conventional and cellular RCC and WCC, mobile radio equipment manufacturers, manufacturers' representatives, distributors, engineering/consulting firms, national/state/local government, military agencies, public safety agencies, transportation companies, petroleum/energy products companies, public utilities and others allied to the field.

PHOTOCOPY RIGHTS: Authorization to photocopy items for internal or personal use, or the internal or personal use of specific clients, is granted by PRIMEDIA Intertec, provided that the base fee of US \$2.25 per copy, plus US \$00.00 per page is paid directly to Copyright Clearance Center, 222 Rosewood Dr., Danvers, MA 01923, USA. The fee code for users of the Transaction Reporting Service is 0745-7626/1998 \$2.25 + \$00.00. For those organizations that have been granted a photocopying license by CCC, a separate system of payment has been arranged. Prior to photocopying items for educational use, please contact CCC at 508-750-8400. Organizations or individuals with large quantity photocopy or reprint requirements should contact Cherie Wood, 913-967-7212.

BACK ISSUES: Copies of most issues printed within the past two years are available for \$10 per issue; older issues are not. Call customer service at 800-441-0294.

ARTICLE PHOTOCOPIES: Photocopies of individual articles printed since January 1987 may be ordered from UMI at 800-248-0360.

This publication is available from UMI in one or more of the following formats: online, microform, document delivery, and electronically. Call toll free 800-521-0600, Ext. 3781, for more information.

ADVERTISING SALES OFFICES

OVERLAND PARK, KANSAS

Joyce Bollegar, 913-967-1840,

East Region (including Eastern Canada)
Fax: 913-967-1901

Email: joyce_bollegar@intertec.com

Dawn Rhoden, Classifieds,
913-967-1861, Fax: 913-967-1735

Lori Christie, List Rental Services Representative,
913-967-1875, Fax: 913-967-1897
9800 Metcalf Avenue

Overland Park, KS 66212-2215



SANTA ROSA, CALIFORNIA

Dennis Hegg, West region (including Alaska, Hawaii and Western Canada) Phone: 707-541-3763, Fax: 707-541-3721 Email: dennis_hegg@intertec.com 3428 Mendocino, Avenue Santa Rosa, CA 95403

ENGLEWOOD, COLORADO

Mercy Contreras, Group Publisher, 303-220-4245 Phone: 303-793-0448 Fax: 303-793-0454 5660 Greenwood Plaza Blvd., Suite 350 Englewood, CO 80111

OXFORD, ENGLAND

Richard Woolley, International Phone: +44 1295 278 407 Fax: +44 1295 278 408 P.O. Box 250 Banbury, Oxon, OX16 8YJ United Kingdom








Audited circulation.

© 1998 by PRIMEDIA Intertec. All rights reserved.



NEXT MONTH

FEATURES:


Vocoders for portable radios Vehicular repeater technology for 800MHz Path Profiles for PCS Vehicle location technologies

ALSO:

Web Site Directory Product Focus: Batteries

And look for Robert H. Schwaninger's column, "In the Public Interest," and "Technically Speaking," written by Harold Kinley, C.E.T.

...POWER ON WITH ASTRON SWITCHING POWER SUPPLIES...



SPECIAL FEATURES:

- •HIGH EFFICIENCY SWITCHING TECHNOLOGY SPECIFICALLY FILTERED FOR USE WITH COMMUNICATIONS EQUIPMENT, FOR ALL FREQUENCIES INCLUDING HF.
 - HEAVY DUTY DESIGN
 - LOW PROFILE
 - **•LIGHT WEIGHT PACKAGE**
 - •EMI FILTER
 - MEETS FCC CLASS B

PROTECTION FEATURES:

- CURRENT LIMITING
- OVERVOLTAGE PROTECTION
- FUSE PROTECTION
- OVER TEMPERATURE SHUTDOWN

SPECIFICATIONS:

INPUT VOLTAGE:

90-132 VAC 50/60 Hz OR 180-264 VAC 50/60 Hz

SWITCH SELECTABLE

OUTPUT VOLTAGE: 13.8 VDC

MODEL	CONT. AMP	ICS	SIZE (inches)	WT.(lbs.)
SS-10	7	10	2.3 x 6 x 9	3.2
SS-12	10	12	2.3 x 6 x 9	3.4
SS-18	15	18	2.3 x 6 x 9	3.6
SS-25	20	25	27/8 x 7 x 9 3/8	4.2
SS-30	25	30	3 3/4 x 7 x 9 5/8	5
SS-25M*	20	25	27/8 x 7 x 9 3/8	4.2
SS-30M*	25	30	3 3/4 x 7 x 9 5/8	5

- · *with separate volt and amp meters
- All SS power supplies are available in a <u>RACK MOUNT VERSION</u> (3.5 x 19 x 9 3/8)
- To order Rack Mount Version change SS to SRM (example: SRM-10)



9 Autry, Irvine, California 92618 949-458-7277 Fax 949-458-0826 www. astroncorp.com

calendar

September

23–25—Personal Communications Showcase, sponsored by Personal Communications Industry Association, Orange County Convention Center, Orlando, FL. Contact: 703-739-0300.

23–25—PCS Latin America, sponsored by the Personal Communications Industry Association. Orlando. FL. Contact: Cathy Graham, 703-739-0300, ext. 3706.

October

12–14—Wireless I.T. '98, sponsored by the Cellular Telecommunications Industry Association, Bally's Las Vegas, Las Vegas, Contact: 202-785-2842.

14–16—TelecomLatina, co-sponsored by *Mobile Radio Technology*. Miami Beach Convention Center, Miami. Contact: 800-288-8606.

19–21—RF Design Conference & Expo. sponsored by RF Design magazine. San Jose Convention Center. San Jose, CA. Contact: 800-288-8606. 20–21—Wireless Interconnection, sponsored by Bellcore, Mesa Pavilion Hilton, Phoenix, AZ. Contact: 800-521-2673.

28-31—Industrial Telecommunications and USMSS joint annual conference. Grand Hyatt Hotel, Washington, DC, Contact: 703-528-5115

November

4-5—ENTELEC and UTC Joint Seminar on Emerging Wireless Communications. Adams Mark Hotel, Houston, Contact: 202-872-0030; www.utc.org

11-15—Communications Marketing Conference, sponsored by the Communications Marketing Association, San Diego Princess Resort, San Diego, Contact: Bernie Brownson, 303-371-8182. 12-13—AMTEX, sponsored by the American Mobile Telecommunications Association, Fontainebleau Hilton, Miami, Contact: 202-331-7773.

12–13—Third International Congress on Commercial Trunked Radio, sponsored by the International Mobile Telecommunications Association, Fontainebleau Hilton, Miami, Contact; 202-331-7773.

20—Radio Club of America Communications Symposium, 89th Anniversary Dinner and Awards Presentation, New York Athletic Club, New York, Contact: Gerri Hopkins, 908-842-5070.

1999

February

8–10—Wireless, sponsored by the Cellular Telecommunications Industry Association, Ernest Morial Convention Center, New Orleans, Contact: 847-940-2155.

March

8–9—Specialized Wireless Communications Management Conferece, sponsored by AMTA, San Diego Hilton Beach and Tennis Resort, San Diego, Congact: 202-331-7773 **28–31—ENTELEC**, sponsored by the Energy Telecommunications and Electrical Association, George R. Brown Convention Center, Houston. Contact: 281-357-8700.

April

28–30—International Wireless Communications Expo, co-sponsored by *Mobile Radio Technology*, Las Vegas Convention Center, Las Vegas, Contact: 800-288-8606.

June

1–3—Canadian Wireless. sponsored by the Canadian Wireless Telecommunications Association, Vancouver, Canada. Contact: 613-233-4888, ext. 102.

27-July 1—UTC Telecom '99. sponsored by UTC, Nashville, TN, Contact: 202-857-1881. 28-29—Leadership Conference & Annual Meeting, sponsored by AMTA, ANA Hotel, Washington, DC, Contact: 202-337-7773.

July

14-16—Communications Expo/Show of the Americas, Miami Beach Convention Center, Miami. Contact: Jackie Gonzales, 305-412-9000.

August

8-12—International Association of Public-Safety Communications Officials (APCO) National Conference, Minneapolis, MN. Contact: 904-322-2500

editorial index

Abner	Lenbrook Wireless Communications	54
ACS Wireless	Mac Com	63
Airtouch	MCI	36
Allgon Enterprises	Motorola 10,	53
BellSouth Mobility	NEC America	63
Celwave	Nextel Communications	54
Centurion International	Omnipoint	63
Coherent Communications Systems 52	PanaVise	63
ComTrain	Pat Connelly Repair	54
Crown Communications	RF Industries	63
Dataradio	RFS Cablewave Systems	50
Dictaphone	Sachs/Freeman Associates	10
Duke Communications Services	Sprint	36
Duke Energy 52	Tellabs	52
Ericsson	TriTech Software Systems	53
Gamber-Johnson	TruePosition	63
GN Netcom	TTC	54
LCC International	Uniden Private Radio Communications	63

One Source.



Full-line.



MS2650/60 Spectrum Analyzers

- 9 kHz to 3 GHz, 8 GHz, 21 GHz, & 30 GHz
- -130 dBm Noise Level in 30 Hz RBW
- Noise Sidebands at <-100 dBc/Hz at 10 kHz Offset
- ±1.3 dB Level Accuracy
- 1 Hz Resolution Frequency Counter
- · Color LCD Display
- 22 lb. Portable Package



MG3641A/3642A Synthesized Signal Generator

- 125 kHz to 1040 MHz/2080 MHz
- -143 to +17 dBm
- · 40ms Frequency Switching Time
- · AM, FM, and PM
- AF Synthesizer and FSK Encoder Options



MF2400 Frequency Counters

- 10 Hz to 20 GHz, 27 GHz and 40 GHz
- 10 µs Resolution
- CW/Pulse Signals (100 ns to 0.1 s Pulse Widths)
- Go/No-Go Test
- 11 lb. Portable Package



MS4630A Vector Network Analyzer

- 1 Hz to 300 MHz
- 1 Path/ 2 Port Error Correction
- 120 dB Dynamic Range
- 150 µs Sweep Speed
- · Multi-Marker Function, 10 Per Channel
- Amplitude, Phase and Group Delay Measurements

To get the kind of RF performance you want, get RF measurement equipment that's set the standard for 30 years. Anritsu.

No wonder so many manufacturers and maintenance organizations depend on Anritsu RF measurement products. Anritsu instruments meet the industry's toughest demands for accuracy, repeatability, ease-of-use and dependability.

Yet, they remain surprisingly affordable.

The value is easy to see.

So if you are involved in R&D, production test or on-site maintenance, go directly to Anritsu RF products. For complete information, call 1-800-ANRITSU today.





editorial forum

A failure to communicate



During the last two years, Kansas City, MO, firefighters have been caught in burning buildings with radios that do not work. A police officer, shot in the leg by a suspect, tried to radio for help —but got only static.

Many communications problems such as these started happening years after Kansas City awarded an \$18.5 million contract to Lynchburg, VA-based Ericsson to build a 800MHz digital trunked radio system. In 1997, before the city would accept the system and make a final payment, it went to bat against Ericsson because officers couldn't communicate in certain parts of the city. Come to find out, the signal strength was the main problem.

The city pointed fingers for two years, but the source was to blame all along. KC said it would sue Ericsson. When Ericsson maintained that it merely built the system to the city's specifications, the city then said it would sue the original consulting firm, Sachs/Freeman Associates. The catch is that Kansas City officials wrote faulty specifications because they were unhappy with the consultant's advice. Building the system for the signal level recommended by the consultant would have cost about \$26 million.

The mayor of Kansas City finally stood up and took the blame (or acknowledged that the blame should not leave city hall) in May 1998. What is worse, Motorola, Sachs/Freeman and Ericsson warned the city that the proposed signal strength was too weak to meet the city's expectations.

The original specifications called for a 33dB signal loss to account for KC's trees, tall buildings and hills. That signal level would have provided coverage in 95% of the city 95% of the time.


The city went with a 21.5dB loss factor. So the fingers point back to the city. A Kansas City Star editorial fumed, "A committee of midlevel bureaucrats, faced with a shortage of money, decided to build an insufficient system with insufficient funds, and didn't tell anyone about it."

What did these officials have in mind when they did this? Didn't they realize that building a public safety radio communications system without enough signal strength is like buying a computer without the printer? How did they expect police officers and firefighters to protect the public if they couldn't protect themselves?

When the city specified this system, it reduced the expense by \$8 million, but put 750,000 lives in jeopardy. Kansas City now needs to spend additional millions (the cost changes from day to day) to retroactively fix the system. The final cost may exceed the original \$26 million estimate.

Radio communication is essential to public safety. When it comes to installing a system, governments cannot take shortcuts. Stunts such as this threaten the safety of civilians and of the officers who protect them.

-Nikki Chandler, Associate Editor



our world-wide web site today.

Sinclair Technologies Inc. 85 Mary St., Aurora, Ont., Can. L4G 6X5 Tel: (800) 263-3275 Fax: (905) 727-0861 55 Oriskany Dr., Tonawanda, NY 14150, U.S.A Tel: (800) 288-2763 Fax: (716) 874-4007

Sinclair Technologies Ltd.,

William James House, Cowley Rd, Cambridge CB4-4WX, U.K. Tel: +44 (0) 1223 42 03 03

TRILOGY

COMMUNICATIONS

THE QUALITY ALTERNATIVE IN WIRELESS COMMUNICATIONS



AII AirCell products are available in both 50Ω and 75Ω .

buildings, subways and tunnels, etc.





Call or write for additional information:

TRILOGY COMMUNICATIONS INC., 2910 Highway 80 East, Pearl, Mississippi 39208 (800) 874-5649, (601) 932-4461 / FAX (601) 939-6637

letters

Is the technician glass half-full, or half-empty?

Thought I would respond to your question ("Editorial," July 1998) on whether your salary surveys would help to hire or retain technicians. Yes, depending on which side of the coin you are on.

When "the other guys" are trying to acquire talent (without paying their dues), they could look at the salary survey and know how much to pay if they were planning to be the high bidder. This falls into a part of your "Viewpoint One-There is no shortage."

When the little guys (yes, I consider our organization one of the little guys) wanted to know if they were staying up with the Joneses, then your survey provided a measuring stick.

In our industry, there are still lots of old systems and equipment in service while new technologies are simultaneously put into place.

This makes it very hard from a training perspective. You need prior experience to handle the legacy stuff, since there is no longer any active training available. The systems are old, and you have to be crazy to invest in learning them since they are slowly disappearing anyway. You also have to be trained on the latest technologies, or you will be left behind in the dust in our business.

Mix this up with all the different frequency bands, manufacturers and communications protocols and products in the land mobile communications world, and it makes for a really good training challenge.

At RCI we still do it the old-fashioned way, by providing fertile soil and the opportunity to grow. This method requires time and patience. With a whole lot of nurturing and occasional weeding, we experience a modicum of success. This is one of those easy to say, but hard to do, solutions to a problem. The success of the individual is frequently based upon the combination of their own personal efforts and the support efforts of their fellow technicians. Teamwork at its best.

Yes, there is a shortage. No, there is not a shortage. Is the technician glass half-full or half-empty? It's a matter of perspective.

—Tony Sabino President, Regional Communications Paramus, NJ

Quality technicians are becoming rare


I'd like to respond to your article ("Editorial," July 1998), which I find most interesting.

In "Viewpoint One-There is no shortage," it is true that those who pay well and nurture with training, equipment, reward and recognition will retain and probably not have a shortage of "good" technicians. But if not, good people are always looking for betterment somewhere else. In today's world, there is very little employee loyalty due to our (management's) loss of common sense.

In "Viewpoint Two-You better believe there is a shortage," good technicians are hard to find on the street because there are few fully trained in the way that was once the cornerstone of many large (communications) companies and even the armed forces. We have not fostered in our public schools that being a good technician can be a rewarding career. But the problem also lies within organizations that fail to train and provide tools and test equipment that are needed by their personnel and some "hands-on" experience.

Sometimes, we put the burden on those who have experience to train newcomers, who now have Associate or other degrees and are hired in at a higher rate than those who are training them. Newer technicians want everything now (higher pay, bigger profile) but don't have experience. Experience still, in my book, counts a great deal.

I agree with your analogy about being



Get out of the heat with Vega's model C-6124. with its cool touch-screen and independent line selection. The C-6124 offers up to 24-line control, instant PTT, and loads of additional features.

Any line can he configured as a dedicated 2/4 wire radiocircuit, dial-up access or full duplex conventional PSTN telephone circuit, (simply plug in the appropriate module). Any combination of lines can be set-up in a crosspatch mode. C-6124 with it's future expandability will keep you out of the inferno.



9900 East Baldwin Place El Monte, California 91731-2294

Telephone: (626) 442-0782 Toll-Free: 800-877-1771 Fax: (626) 444-1342 • FaxBack: (626) 444-2017 / 800-274-2017 email: vega_signal@earthlink.net www. vega-signaling.com

"close-mouthed" about strategies. However, when people start reading more of the "ads" in their field, or head-hunters find them, then they'll know what the demand is out there. Quality technicians, in my opinion, are becoming "rare."

—Dick Fay Manager, Wireless Group, Duke University

Companies compete for technicians

Regarding technician shortage, I believe that "Viewpoint One—There is no shortage" is correct

While our company is a manufacturer, rather than a service provider, we still use the same skill sets for our final test technicians and customer service techs as a contemporary twoway radio technician. These guys do not work on the same variety of radios that an independent shop would see, but they must be thoroughly familiar with the innards of FM and now digital radios. RF power amplifiers. duplexers, etc. and also be able to assemble these components into our point-to-point fixed radio telephone links and our trunked point-tomultipoint systems and make these systems perform to specification. Our benches have the same type of test equipment, including IFR 1200. HP 8920A and Motorola service monitors. HP and Tec scopes, as any two-way shop. We therefore compete directly with two-way shops both in our region and nationally for talent, as do several other telecom manufacturers in our area. We advertise extensively on the Internet for technicians and hire people from all over the country.

Within the last four months, our company had to move from the rural area where we were founded ... in order to attract technical and engineering talent. Others who compete for the radio segment of this talent pool include all of the cellular service providers, PCS providers and those suprisingly numerous companies that are system integrators in the international market. Our two field technicians who travel to our customer's sites (mostly international) to install our systems and train our customers in the operation and maintenance are literally the highest-paid employees in the company, when considered on an hourly compensation basis. We compete with companies such as Motorola, Bechtel and Fluor Daniel for the talents of these experienced people.

Unfortunately this means that the talent available to many two-way shops that cannot afford to pay market wages or provide highly competitive benefits (our benefits include stock options, medical, dental and life insurance, integrated vacation and sick pay amounting to four weeks after three years of employment, and more) will not get the pick of the crop. The only solution I can suggest is to raise the

price of service, and pass this on to the employees. There is an effect of diminishing returns when doing this, as more equipment becomes unrepairable because of economics.


> —Jim Longnecker Senior Applications Engineer Optaphone Systems

Taxpayer Identification Number

Robert Schwaninger may be speaking a little too lightly about the "Taxpayer Identification Number" (TIN) ("Regulating Technology," June 1998). This seems to be suddenly extremely important and, for some reason, has eclipsed the all-important callsign in the FCC. I suppose this is the result of some congressional legislation (oversight). I wonder what would happen to a license application, auction bid, etc. that you submitted, and it so happened you had made a mistake on a yearly submission or had something pending with the other organization concerned with "TIN."

May Robert be appointed someday kicking and screaming to the FCC, live long and continue writing his delightful column after his appointment!

> —Dennis R. Murphy Bismarck, ND



in the public interest

The sound of Sam

By Robert H. Schwaninger Jr.

This is Washington, where the summer heat bounces off the pavement in steamy waves. Government workers' blue-lightspecial ties hang limply from sweat-soaked necks. An endless stream of secretaries lope on retro stacked-heeled shoes toward the Metro. The human mass moves along huge squat buildings that hint at the longdead WPA, barely recognizing each other's existence until queuing for position at the

deli counter or halfsmoke vendor cart.

Among the eddies and streams of people are lawyers, consultants, lobbyand media types. These denizens demonstrate the most carnivorous nature. They feed on Congress. They dine on executive decisions. They consume their own in cannibalistic frenzy. These political predators hear and smell thingsindications that are missed by the untrained ears and antennae of other humans.

They hear rumblings of change, like tectonic plates moving a millimeter closer to the ocean, emanating basso echoes from the halls of Congress. They detect a

high-pitched squeal, like that of a small creature before it trembles for the last time, whistling from the lifeless lips of a constituent who has been told "That's the way it is." They sense the rhythmic drone of the bureaucratic machinery pounding along, one pile-driving beat at a time.

I'm one of the predators: a lawyer. I've

Schwaninger, MRT's regulatory consultant, is a partner in the law firm of Brown and Schwaninger. Washington. He is a member of the Radio Club of America.

been trained to see a catastrophe as a billable occurrence and devastation as opportunity. And, like a small child, I've been told again and again to look both ways before crossing the agency highways where truckloads of decisions, rules, regulations, licenses and fertilizer are carted to the nation's hinterlands.

"Don't get in the way, boy," is the admonition. Sometimes, I don't listen.

Sometimes, I'm listening to other sounds-sweet, sad sounds, that overpower the din from meeting and committee rooms. Like a cricket's song of unrequited love, the sound that I hear chirps

who's asking, "Why?" I hear it again and again. "Why?"

He might be a guy named Sam, who works in a plant down the street from the loading dock my old man spent 29 years patrolling. His damn radio won't work because he's getting interference from another operator again, and nobody's doing anything about it. Sam complains to the boss, who tells him, "They're working on it." But Sam knows that they've been working on it for over a year, and it's just getting worse.

Sam is the guy who had to take the cellular phone out of his wife's car. They can't afford it anymore, because his cable

bill keeps creeping up and up at the same time that his favorite team is switching to pay-per-view. Now he reads that he'll have to buy a new television set for something called HDTV. His set works fine. It's the world that's a little screwy.

Sam bought his kid a computer a few years ago. He had to scrimp to get it, and his wife had to wear the same dress two years in a row to the family Christmas dinner, but they figured they were doing right by the kid. Now the damn thing is obsolete and won't run the new software. The kid




Illustration by John Hayes

and sings to my conscience, reminding me that it wasn't always like this for me. It shouldn't always be like this. I try to ignore it, or dismiss it as an unworthy distraction. But it keeps coming and coming, until I have to pay attention. I have to stop shooing it from my mind. I have to act.

The sound I hear is the distant cry of the recipients and victims of those truckloads of regulation and decisions, made with mechanized precision on the desktops and laptops and cyberflops of the government. The sound of one guy back in Missouri

claims he's the only 15-year-old on earth with something called a "386." Sam feels rotten, but a new computer costs over a grand, and the Chevy needs an overhaul.

Sam reads in the paper that his cable company just got sold for billions, and he stares at the notice in his bill that says the rates are going up again. And while he's staring down at the stack of bills on the kitchen table, he notices that he's still being charged two bucks a month for digit dialing. Sam can't remember the last time he saw a rotary phone. It was sometime



Narda's tower top
antenna amplifiers
expand cell site
coverage and
heighten customer
satisfaction.

It's not easy being a cell site in many areas.

They can be challenged by remote locations, obstructions and low mobile phone output power. However, while there are many problems, there's one proven solution. Narda's tower top amplifier systems.

These unique systems have been designed for use on RX antennas or duplexed RX/TX antennas. Encased in rugged enclosures for extreme environments, our proprietary products utilize an ultra-low noise amplifier to boost low power and/or distant signals received by the antenna as much as 13.6 dB.

Incorporated in all Narda units are our advanced low-loss cavity filters or duplexers. They significantly improve the carrier-to-noise ratio of the signal. Our tower top amplifiers can also be provided with our CATS Monitoring Systems. If VSWR is exceeded or transmitted power falls below user-defined threshold levels, you'll be alerted.

Once our system is installed, the benefits are unbeatable. With stronger and better signals, you'll connect with customers over a wider area. Uplink co-channel interference will be reduced. An improved C/N ratio will cut back dropped calls dramatically. Even the battery life of your customers' phones will be lengthened.


The Narda tower top antenna amplifier systems. For expanded cell coverage, improved performance and enhanced customer satisfaction—you're covered.

Call Narda today at 516-231-1700. Or call our Faxback and ask for document 1120 at 1-800-4NARDANY.





It's Narda to be precise.







Circle (8) on Fast Fact Card

before the phone company told him he was now the owner of his home telephone equipment and the wiring in his house. He remembers he wasn't sure what that meant, but Sam kept that secret to himself.

Aunt Martha's birthday card ticked him

Why doesn't the

FCC care whether

Sam's radio works?

off. The wife forgot to tell her that the area code has changed, and Aunt Martha didn't know how to get the new one. She's over 80, you see, and talking to telephonic menus is simply too for-

eign, too new. Aunt Martha doesn't know from LATAs. She has never surfed the 'Net or received email or seen "The X-Files." But she makes the best strawberry-rhubarb pie in Pella, IA.

Sam rakes his calloused fingers through his thinning hair and stares out the window. A long, dejected sigh rushes from Sam's lips, with a sound like dusty air from a bellows at the bottom of a cave, that only a tear could punctuate. At the end, Sam asks in a small voice, "Why?"

That's the sound I hear-the one that keeps nagging me, berating me, making me do things, write things, say things that cause my fellow capital carnivores to look sideways and shake their heads. Like a milliwatt into a preamp and out a highgain antenna, I repeat Sam's question loud as I can. I shout it with the power of overused lungs, "WHY?!"

Why doesn't the FCC care whether Sam's radio works? Why does Congress allow the telephone companies to charge for a "new

> technology" that has been in the market for over 20 years? Why do cable rates continue to rise with impunity? Why are commanufacturers puter allowed to make twovear-old models obsolete?

Why can't you go down to the phone company and sit across the desk from someone who will discuss your bill and answer your questions? Why, with every newfangled device, does the price for service seem to go up and up for features that Sam can't use—and wouldn't buy if he had a choice?

Forget about PCS, the TDF, the OPP, the GAO, the Portals, co-locations, TNPP agreements, Y2K, TINs, the ULS, the WTB and the political/global/re-engineered/TQM crudathon that flows across the bored, sweaty pages of the business and op-ed pages of the Post and the Times. Just answer me this: With all of the technological advances that this industry has made in the last 20 years, why isn't Sam's life better and fairer?

It's a question that keeps me going.



Circle (9) on Fast Fact Card



Introducing Decibel's Omni Diversity Master™ — the first omni antenna with dual polarization.

There's no doubt what reaction you'll get with the better signal strength and improved uplink performance of Decibel's new Omni Diversity Master. With the enhanced diversity of dual polarization combined with 360 degree signal penetration, it's only natural to smile. Available in the 896-942 MHz frequency for paging and trunking, the Omni Diversity Master handles 500 watts of power, delivers a gain of 9 dBd (11.1 dBi), and provides an isolation greater than 30 dB. And it meets or exceeds the same quality standards you've come to expect from us. So proceed with caution; this antenna may spark a smile.


To learn more about the Omni Diversity Master and to order a free catalog, call 1-800-676-5342 or 214-631-0310, or visit www.decibelproducts.com to see our antenna patterns online.

Visit us at PCS, booth #3751.





The Decibel Products Division is compliant with all ISO-9001 standards.



Several techniques
can improve the
performance and
capacity of
CDMA systems. RF
engineers now
realize that
CDMA offers an
opportunity to
trade off capacity,
coverage and
call quality.

As PCS carriers operating code-division multiple-access (CDMA) systems finish deploying their phase-one "buildouts," they move to the *optimization* stage. Optimization is a critical stage that can significantly affect the performance and capacity of a CDMA system. Several techniques can be used to optimize CDMA system performance during this critical stage.

One of the easiest methods of "stealing" system capacity is to have too large of a soft hand-off zone. "Soft hand-off"

nication with multiple base stations at the same time. "Softer" hand-off is when the mobile is in communication with multiple sectors of the same cell. A link is established with a target cell before the link with the currently serving cell is broken. CDMA gains several advantages by employing soft hand-off: fewer calls are dropped, less portable transmit power is required and less interference is experienced. However, as in many cases, too much of a good thing can hurt you. If the soft hand-off zone is too large, the system will have less capacity because two base stations are carrying the same call during soft hand-off, as shown in Figure 1, below. Soft hand-off is a compromise between system performance and system capacity. Greater soft hand-off usually improves performance, but it decreases capacity. The ideal amount of soft hand-off is about 25% to 40%. The need for minimized overlap between sectors is one of the reasons that CDMA operators are deploying 65° and 90° horizontal beamwidth antennas instead of the traditional 105° and 120° horizontal beamwidth antennas used in AMPS cellular. An operator must also ensure that the T_ADD, T_DROP and T_TDROP parameters are set correctly for optimum performance.

when making this critical decision regarding the use of narrower horizontal beamwidths. Although the trend has been toward narrower beamwidth antennas, with excellent results, there are exceptions. One operator deployed 80° horizontal beamwidth antennas on a few relatively high sites with disappointing results. In that application, there were significant "notches" in the coverage area between sectors. A general rule is that as tower heights increase and site radius widens, horizontal beamwidth will need to widen. Many operators are deploying 90° horizontal beamwidths for their CDMA sites, and some operators are using 65° horizontal beam-

Singer is director of technical marketing for Celwave, Marlboro, NJ. He is a member of the Radio Club of America.




Figure 1. While the mobile unit is in the soft hand-off zone, both cells are active.

widths, particularly for dense urban areas.

Another important aspect of the horizontal pattern is the H-plane "roll-off." The more rapid the power roll-off beyond the 3dB beamwidth points, the higher the sectorization efficiency. If you overlay various antennas with the same 3dB beamwidths, you can observe that two or more antennas can have the same 3dB beamwidth, but some will roll off quicker beyond the 3dB points.

One last feature to look at in horizontal patterns for CDMA systems is high front-to-back ratios. The higher the front-to-back ratio, the less likely co-channel interference will be an issue off the back of the sector.

Another optimization method is to minimize areas suffering pilot pollution. Pilot signals act as beacons to notify potential users of the existence of a CDMA base station. Portables use the pilots for power strength comparison, which is essential for the process of a hand-off. The pilot signal is the strongest channel, containing 20% of the total radiated power in a CDMA signal. Each CDMA sector sends its own pilot signal, but they are all on the same frequency.

The portables in use today have a fourfinger "rake" receiver. One finger is used to scan for pilots and the other three can "listen" for pilots. If a portable is in a location where numerous pilots are received with relatively equal signal strength, the result is pilot pollution.

Pilot pollution can cause dropped calls and decreased capacity. Drive testing in these areas will show a noticeable problem with frame-error rate. To avoid pilot pollution, operators can use antenna downtilt¹, azimuth rotation and careful horizontal beamwidth selection. Some carriers in core urban areas have been using 33° sector antennas to minimize pilot pollution, as shown in Figure 2 at the right. Often, these antennas are used at sites located on bridges because signals propagate significantly greater distances over water.

Other methods of reducing pilot pollution used less extensively include lowering cell site heights, lowering cell site power and using repeaters. One method of battling pilot pollution is to ensure that one cell has a dominant pilot. This can be done by using a repeater to saturate a small area with one particular pilot. These are tools that the RF engineer can keep in his "tool box" for solving pilot pollution issues.

Some CDMA operators use continuously adjustable electrical downtilt antennas to minimize pilot pollution. When antennas are me-

¹Singer, Andrew, "Selecting Antennas for PCS and DCS Systems," *Mobile Radio Technology*, July 1997.




Figure 2. Use of 33° sector antennas to minimize pilot pollution.

chanically downtilted, the energy off to the sides of the antenna is not reduced on the horizon, and this energy can cause pilot pollution at nearby sites. Electrically downtilting the antennas reduces the energy on the horizon both in front of the antenna and on the sides. In situations where pilot pollution is caused from the side radiation of a nearby site, a continuously adjustable downtilt antenna can be adjusted while performing drive tests after each adjustment, to optimize the system for coverage and reduction of pilot pollution.

Continued on page 22

Some Criteria for Evaluating Antennas

By Dwight Staehler

Complaints about high reflected power, high VSWR or poor match all mean the same thing. The antenna does not appear to be absorbing as much power from the transmitter as it should. It must be determined whether the installation or the product is the cause. Answers to the following technical questions can help determine if the product qualifies as defective per the manufacturer's warranty. (This presumes all connections are clean, dry and tight and that all test equipment is in good condition and properly calibrated.)

1. What is the VSWR you measured?

Check to see if it is a higher number than the catalog value for this product. For example, many antennas have a match of 1.5:1 or 1.6:1 across a specified bandwidth. Performance at a VSWR greater than 2.0:1 may be unsatisfactory. Some technicians will refer to match as "return loss," in which case rates of 14dB or 12dB apply. Performance at a return loss of less than 9dB may be unsatisfactory.

2. What test equipment did you use?

Check to see that the equipment has been properly calibrated and that any connector adapters are of good quality. A poorly matched adapter will invalidate the results.

▶ Wattmeter/power meter — These devices are inexpensive, and therefore, more common, but they can be inaccurate, particularly if more than one RF carrier signal is present. Technicians who use wattmeters and power meters will eagerly tell you how many watts of power is reflected back to the transmitter, but often they do not know the actual mismatch. The forward power measure-

ment is required to calculate the VSWR or return loss number. This can be tricky because some transmitters have an output stage protection circuit that reduces power under highly reflective conditions

▶ Network analyzer/spectrum analyzer with tracking generator — These devices do not rely on the site's transmitter as a signal source. They can produce more accurate and meaningful results, but they do not subject the antenna to full power, when arcing or flashover would occur.

▶ Time domain reflectometer — Occasionally, a technician will use a TDR. This is not an industry-recognized instrument for antenna testing, and many manufacturers will not respond to these measurements because they do not use RF and do not measure beyond bandlimiting devices.¹

3. Did you perform the measurement directly at the antenna's connector?

The technician may have chosen not to perform this test because it requires climbing the tower. This procedure should be done to eliminate jumper cable or downlead cable factors. The cables could be defective and causing the problem. They could also be fine, but they could be absorbing the reflection that masks the problem.

4. What is your operational frequency?

Check to see if the antenna was ordered for the correct frequency. The manufacturer may have mismarked the antenna or carton. Several methods can determine an antenna's frequency. If the technician has swept the response of the antenna, he will know

Continued on page 20

Staehler is an applications engineer for Celwave, Marlboro, NJ.

¹Dong, Cynthia, "Identifying Transmission Line Faults," *Microwave & RF Communications Products*, Nov./Dec. 1996.

MOBILE SYSTEMS ENGINEERS



The Reference Source for SPREAD SPECTRUM TECHNOLOGY

This book presents:

- Modern Mobile Communication concepts
- Detailed Case Studies
- Practical Implementation Issues

Spread Spectrum in Mobile Communication presents the concepts of modern mobile communication and discusses the user requirements and operational environment which influence mobile systems design.

The book contains detailed case studies that illustrate practical issues involved in implementing spread spectrum technology.

Authors: O. Berg; T. Berg; S. Haavik; J.F. Hjelmstad; and R. Staug.

ISBN: 0-85296-935 X - Hardcover, 480 pp.

To order

1-888-438-2517

(toll free in US) or 732-417-9575

E-mail: wcbooksiee@aol.com

The Power of Information

98013

Books by the IEE



Circle (11) on Fast Fact Card

CRITERIA Continued from page 19

the frequency of the best match. That should be its *designed* frequency. The technician can also measure the physical length and compare it to a cut chart. This is a crude method. If the antenna is relatively new and the model number is known, the factory may still have the production test data sheet that will identify its frequency by serial number.

5. Did you measure the antenna erect, free and clear of metal objects?

Side mounting too close to the tower can detune an antenna. The required spacing distance between the antenna and any other metal object decreases as the operational frequency increases. Some good numbers per our factory test procedure for omnidirectional antennas are from 100 feet at 30MHz to five feet at 900MHz.

6. What is the dc continuity, as measured with an ohmmeter?

Some antennas have direct ground lightning protection. These normally measure as a dc short between the connector's inner and outer conductor but will be the proper 50Ω impedance at RF. See "lightning notes" in catalog specifications to determine if the antenna will measure as an open or a short.

7. Did you have the opportunity to substitute an identical antenna?

If the second antenna measures OK under the same mounting conditions, the technician's first antenna is probably defective. If the second one yields the same bad result, the problem is unlikely to be the antenna. Perhaps the transmitter is not operating on the expected frequency.

8. When was the antenna installed?

It could either be new and defective or one that had performed nominally for some time before failing. It is a good practice for technicians to test products on receipt before transporting them to the job site. Manufacturers' warranties cover only manufacturing defects, not damage from an improper installation. An example would be mounting a standard antenna upside-down. This would put the drain hole at the top, where it could collect water and cause the product to fail over time. Factory options given to an inverted antenna include reconfiguring both the drain hole location and any electrical beam tilt.

9. Are the antenna drain holes open?

They are placed at the bottom of the antenna for draining internal moisture. Periodic inspection of these openings is the responsibility of the owner. They must remain clear of debris to preclude corrosion from internal condensation. Such damage can drastically affect performance, and it is not covered by warranty.

10. Is the antenna intermittent?

It is a good idea to shake the antenna during the above tests to ensure there are no mechanical intermittents. Poor connections may lead to RF intermodulation products. Water entering the antenna may lead to electrical intermittents that subside when the antenna dries out.

Match is only one indicator of antenna quality. VSWR tells us how well the product's impedance matches to (absorbs) a transmitters signal, and it is easy to measure in the field. Unfortunately, VSWR does not reveal an antenna's *efficiency* (how well it radiates the signal). This measurement (an antenna's *radiation pattern*) is more difficult to perform in the field. We may presume that match bandwidth and pattern bandwidth are equal, but this is not always true. For example, operating an end-fed antenna below its design frequency will result in an electrically downtilted vertical pattern. Usually, substitution with an identical unit of known quality is the method of choice when a defective product is suspected.

The typical VSWR for a good antenna is 1.5:1. Although some site engineers may specify a minimum acceptable value of 1.3:1, there is only a miniscule improvement. For example, at a 1.5:1 ratio, 4.0% of the power is reflected back, creating a 0.18dB loss. At a 1.3:1 ratio, 1.7% is reflected, resulting in 0.07dB loss. The performance improvement is only 0.11dB.

It is a good idea to document performance upon installation. This is usually done by choosing a remote site and measuring the signal level received from the transmitter. Periodic measurements at that same location will reveal the amount of any degradation so that corrective action may be taken.

The New Celwave Integrated-Technology Combiner. Smaller Size, Lower Cost



What's light, compact, extremely versatile, and perfect for the 851-869 MHz trunking band? Celwave's new WIJD Series integrated technology combiners, in five- and six-channel models.

Based on the operating characteristics and patented temperature-compensation technology of the previous WJD Series, these remarkable WIJD units are smaller ... lighter ... and easily expanded in the field.

Rigorously tested, the WIJD combiners permit any channel arrangement and give you low insertion loss and high isolation between transmitters, even down to 150 kHz channel spacing.

Want more? The WIJD combiners excel in minimizing transmitter IM. They have higher Q than others. And they are temperature-compensated to +/- 0.45 ppm, with power dissipation up to 150 watts efficiently delivering your transmitter power to the antenna system.

In brief, Celwave's new integrated technology combiners bring you great performance in less space at lower cost.

Check them out. Call 1-800-CELWAVE to request free specification sheets.

And see how these remarkable units can boost the performance of your trunking system.

VISIT US AT BOOTH 4040 • PCS show September 23-25 in Orlando Hot New Products • Free Phone Cards • Grand Prize Drawing: Rolex Watch

CELWAVE

2 Ryan Road, Marlboro, NJ 07746-1899
Phone: 1-800-CELWAVE • Outside U.S.: (602) 252-8058 • Fax (602) 417-2124 • www.celwave.com

Circle (6) on Fast Fact Card

OPTIMIZING PERFORMANCE Continued from page 19

One often-ignored method of optimizing CDMA systems is tweaking the neighbor list. An operator needs to avoid a hand-off to a sector that may only temporarily provide good coverage, such as the high site shown in Figure 3 at the right. Tweaking the neighbor list allows the portable to be instructed as to which neighbors to search first for a good hand-off. If the portable hands off to the wrong sites, the call can be dropped, and capacity will be wasted as well. The neighbor list needs to be updated as new system sites are added.

One final method of optimization is to ensure that your antenna system is minimizing the addition of noise and interference into your CDMA system. Noise and interference can significantly limit your system's capacity. Antenna intermodulation is one form of this noise and interference. Make sure that your system's antennas are designed robustly enough that their intermodulation (IM) performance does not decrease with time. The IM performance of designs using multiple cables and solder joints are susceptible to deterioration once the antennas are placed in an outdoor environment. Many antennas do not even meet their advertised IM specifica-




Figure 3. Cell 3 should not be on the neighbor list, but Cell 2 should be.

tion before being placed on a site.

Antennas that use PC boards can also add a noticeable amount of noise to the system. For instance, if the PC board used in the antenna has a distributed loss of 2dB, this is the same (from a system noise standpoint) as adding a 2dB attenuator pad to the input of the antenna. This 2dB of loss will also improve the VSWR of the antenna, but for the wrong reasons. Remember, a 50Ω load can have a great match, but all the power is absorbed as heat. An operator needs to keep in mind that any losses in the antenna, such as

lossy PC board material, will negatively affect the receiver sensitivity.

Operators also need to understand the compromises and potential negative impact of using polarization diversity in a system.²

There are many methods for improving the performance and capacity of CDMA systems. RF engineers realize that CDMA offers us an opportunity to trade off capacity, coverage and call quality.

²Singer, Andrew, "Improving System Performance," Wireless Review, Feb. 1, 1998.

Andrew stops lightning before it stops your system



Arresting Developments

Andrew never stops developing innovative lightning protection solutions. Arrestor Plus® Surge Arrestors are offered in quarter wave stub or gas tube technologies in a wide range of configurations to satisfy your system requirements.

- 1 Integrated Series Surge Arrestors easier, cost saving attachment directly to HELIAX[®] cable with innovative RingFlare™ Connector technology.
- 2 T-Series Surge Arrestors bulkhead or stud mounting/grounding options for your specific application.
- Mini Series Surge Arrestors quick installation for small radio cabinets and tower mounted amplifiers.
- Gas Tube Series Surge Arrestors for broadband performance, simple maintenance; ideal solution for applications requiring DC feed through coax.


For superior lightning protection, call Andrew or your local Andrew Distributor today.

1-800-255-1479 ext. 362 or fax us at 1-800-349-5444 Visit our Web Site at http://www.andrew.com



In A Communicating World, Andrew Is Everywhere

Circle (23) on Fast Fact Card



ROCKIN' CLASSIC

ROLLIN' CLASSIC

RADIO CLASSIC

20 YEARS LATER, OUR CLASSICS ARE BETTER THAN EVER.

s it possible to improve on a classic? At MAXRAD, we believe it is. Sure, the '64 Corvette is one-in-a-million. And the old Les Paul guitars are valuable collectibles. But over the years both have been improved through innovation and technology. At MAXRAD we have used the same philosophy to improve our classic mobile antennas.

Since 1978, we have made countless improvements to our mobile antennas so they perform better, longer and for a wider range of radio products. Since 1978, we have become the premier supplier of mobile antenna products. We couldn't have done this without the support of our loyal dealers—folks who know classic value and quality.

And we're not stopping there. At MAXRAD we're constantly developing new products that will, one day, become classics.

MAXRAD'S CLASSIC ANTENNAS

Our classic mobile antennas have been working hard for our customers for 20 years. And every day, we're working to improve these classics and develop new ones. Join the leader whose "new classics" are ready to meet the specifications of tomorrow's radio products.

- ·Low Band
- •VHF
- •UHF
- •800 MHz



Contact us about our complete new line of 2.4 GHz ISM wireless data antennas.



CALL:(800)323-9122

www.maxrad.com



fidelity

Voice quality in PCS and cellular networks: Eliminating echo

Improvements in digital mobile communications technology can actually aggravate problems, such as echo, that are unnoticeable in analog systems.

The use of echo cancelers is one way to improve voice quality.

By Doug Stuard

Wireless customers want their phones to sound as good as their landline phones. To meet this demand for "toll-quality" sound, service providers must increase voice quality throughout their systems. Changing from analog to digital modulation dramatically improved voice quality by reducing the noise associated with analog air interfaces. Digital systems, however, introduced circuit delays that made acoustic echo seem more prominent.

Some network providers have taken steps to resolve acoustic echo. Diligence is

necessary because additional mobile network improvements that reduce noise even more will unmask lower levels of acoustic echo

Echo Sources

In a typical wireless-to-wireline phone call in a PCS or digital cellular system (that is, from a wireless phone to a PSTN phone), two types of echo exist. *Hybrid echo* on the public switched telephone network (PSTN) end of the phone call is caused by the electronic reflection resulting from the four-wire to two-wire impedance mismatch. (See Figure 1 on page 26.) For echo to be noticeable, the human ear

must detect some delay between the source signal (in this case, the spoken word) and the echo signal. In typical local-loop applications, this echo is not noticeable because the delay is so short that the human ear does not separate the original speech from the echo. Typical long-distance applications induce delay primarily through propagation, and thus they require hybrid echo cancelers for correct operation.

In a PCS network, however, propagation is a secondary issue because processing delay is always introduced into the

Stuard is the product manager at Tellabs, Ashburn, VA.





Photo 1. Voice prints reveal wireless and wireline echo without and with cancelation.

RFS CABLEWAVE SYSTEMS

LIGHT YEARS ABOVE THE REST FLEXWELL PREMIUM JUMPER ASSEMBLIES FOR PCS

PASS SWEEP TESTS THE FIRST TIME, EVERY TIME
ELIMINATING CONSTRUCTION TEST DELAYS

MAXIMUM GUARANTEED VSWR 1.08:1



RADIO FREQUENCY SYSTEMS
RFS Cablewave



200 Pondview Drive Meriden, CT 06450 Tel: (203) 630-3311 Fax: (203) 821-3852 www.cablewave.com propagation path through the network. This delay is reduced or eliminated in the mobile network, typically at the mobile switching center (MSC), according to GSM specifications that require cancelation "looking toward" the PSTN.

The International Telecommunications Union's (ITU) Recommendation ITU-T G.168 ("Digital Network Echo Cancelers") specifies the performance of echo cancelers and the test conditions for verifying performance in the PSTN. In wireless standards work, the GSM standards, as noted above, deal explicitly with hybrid echo cancelation.

Acoustic echo

The other previously mentioned echo phenomenon, *acoustic echo*, has become apparent in wireless networks.

Acoustic echo is defined as the coupling of received voice transmission between the earpiece and mouthpiece of a portable handset or the speaker and microphone of a hands-free mobile phone. When acoustic echo occurs, it is the PSTN user who is discomforted. (For simplicity, this discussion will refer to a wireless user and a PSTN user, even though the general case could include two wireless users.)

Acoustic echo is a much more complex signal than hybrid echo. The simple case of a




Figure 1. Hybrid echo in a wireless-to-wireline call.


hands-free mobile phone illustrates the example most clearly. The received signal emits from the speaker and reflects from multiple surfaces inside an automobile. The reflections return the signal, at various time delays and amplitudes, into the microphone, and over the phone connection to the PSTN user's ear. In addition, the tail circuit is non-linear because of the speech compression. Because these reflected signals are typically delayed 180ms or more, the PSTN user hears a perceptible echo.

Portable handsets couple the PSTN user's voice between the earpiece and mouth-

piece, as shown in Figure 2 on page 28. This occurs either directly, as handsets get smaller, via reflections off the user; or via reflections from the environment. This coupling is more prominent when the wireless user increases the handset volume, to compensate for high background noise and for PSTN users with soft voices.

Handset specification

GSM specifiers did not ignore acoustic echo when developing standards. As with any echo, the closer to the source it is dealt



It's a "NO BRAINER" Battery Analyzer & Conditioner

Now...
at your fingertip!

FUNCT

Easy-To-Use..."Just one Button" gives you access to the most technically advanced and affordable analyzer/conditioner on the market today!

The Analyzer I, III & VI Series has standard features not found on other systems costing over three times as much...including:

- Charges & analyzes Nickel-Cadmium, Nickel Metal Hydride, Lead Acid & certain Lithium Ion chemistries.
- Single button operation.

NCTION

- Four independent charge rates.
- Eight independent discharge rates.
- Interchangeable adapter cups.
- UL, CSA & CE approved.

Call for our comprehensive catalog describing in detail our innovative line of Analyzers/Conditioners.



FUNCTION



800 South Broadway, Hicksville, New York 11801

In U.S. & Canada 800-221-0732

In NY State 516-942-0011 • Fax 516-942-1944

E-Mail: w-wassoc@ix.netcom.com • Web Site: http://www.wwassociates.com


All specifications subject to change without notice.

Circle (27) on Fast Fact Card

The new ULTRA-COM NT

Windows NT-Based

Radio Dispatch System



Moducom's new Windowsbased ULTRA-COM NT is the only communications workstation that lets you design screens and set operating parameters with no changes to software and with no reprogramming costs, using MODUCOM's exclusive Screenmaker and Customizer programs.

Now, the new MEDIC diagnostic program analyzes the status and performance of the hardware and software in the system and recommends corrective action if required.

The ULTRA-COM NT's design, whether stand-alone or as part of a multi-position system, takes advantage of the latest advances in communications technology.

Moducom Windows NT-based dispatch consoles, are designed for today's emergency communications requirements, and for the future.

Write, phone or fax for detailed literature

MODULAR COMMUNICATION SYSTEMS, INC.

13309 Saticoy St.
No. Hollywood, CA 91605
(818) 764-1333 Fax (818) 764-1992
www.MODUCOM.COM




Figure 2. Handset acoustic echo paths can be formed by reflections off of the user.

with, the more effective the solution. For acoustic echo, the source is the handset. Two aspects of handset specifications deal with echo loss performance characteristics. One is the handset performance, and the other is testing specifications. The weighted terminal coupling loss (TCLw) value of 46dB, derived from ITU's Recommendation ITU-T G.131 ("Control of Talker Echo"), is the specified performance characteristic for handset acoustic echo return loss (AERL). This level, as evidenced by continuing discussions among the European Telecommunications Standards Institute's (ETSI) special mobile groups, is not universally accepted as being correct or indicative of operational conditions across the voice bandwidth.

GSM Phase 1 testing methods are flawed, in that sinusoidal tone testing is allowed to be run through the speech coder/decoder (codec) to verify performance. The full-rate codecs cause sinusoidal spreading, which results in lower power

when measured at discrete frequencies. Testing that bypasses the codec, as allowed by the specifications, is also flawed, because it precludes an element that degrades the GSM system. Both test approaches result in equipment that dis-

plays artificially high AERL levels that allow acoustic echo to leak through.

Phase II specifications are intended to improve this performance via an artificial voice test stimulus as specified by ITU's Recommendation ITU-T P.50 ("Artificial Voices"). In conjunction with a proposed head-and-torso simulator (HATS) that incorporates free-air transmission, these test methods would attempt to more closely represent actual user conditions. There is still

resistance to this approach, so the main improvement in testing in Phase II is expected to be the more indicative stimuli.

The effect of improved coders

Attempts to increase GSM system voice quality have resulted in extensive study and proposed alternate coding techniques. The enhanced full-rate (EFR) coder concept was put forward to improve the quality without imposing a penalty on bandwidth. The U.S.1 codec, adopted by ETSI, provides improved performance over the fullrate coder while using the full-rate codec, thus making deployment easier. The comparative quality is shown on a mean-opinion score (MOS) scale in Figure 3 on page 30. The graph shows statistically significant performance improvement in errorfree conditions (EP0) through carrier-tointerference (C/I) conditions of as much as 7dB (EP2).

So where's the problem?

Improved quality from the processing within the coding stage diminishes the masking of acoustic echo produced by the mobile handset. EFR coding, for instance, improves the channel's performance but allows acoustic echo to be detected by the user. Mobile users are prone to increase their volume levels to overcome local background noise, exacerbating the acoustic echo problem by increasing the likelihood of coupling.

Echo cancelation

Testing that bypasses

the codec ... is also

flawed, because it

precludes an element

that degrades the

GSM system.


To solve this problem, many carriers limited the level of the mobile user. This decreases the acoustic coupling, but the subscribers (who are paying the bills) cannot hear the PSTN-side user. Another solution is

to use echo suppressers in the switching equipment. Many manufacturers integrate suppressers into their systems, but the performance of these devices is limited, particularly with double-talk. (See "Echo cancel-

ing vs. echo suppression" on page 32.) The ideal solution to acoustic echo is the use of high-quality echo cancelers.

To be effective in a wireless environment, echo cancelers need critical features including effective, bidirectional, acoustic and hybrid echo cancelation. They must also be able to tune the tail circuit delay offset. Finally, they must be compact and support future audio-enhancing signal processing capabilities.

Wireless is limitless.



Some planning tools are great at cellular or PCS but useless otherwise. EDX SignalPro™ is a full-featured planning tool for Windows® 95/NT that provides comprehensive, accurate designs for any system in the 30 MHz to 100 GHz frequency range.

- Cellular
- Wireless local loop
- PCS
- Microcell
- Paging
- · Indoor wireless
- MDS
- · Land mobile
- LMDS
- Microwave link
- AM, FM, and TV broadcast (DTV)

EDX SignalPro and its modules offer 21 different propagation models, including transmitter-specific measurementderived models, and full 3D ray-tracing models for indoor and outdoor microcell studies.

EDX SignalPro includes SignalMXTM (pat.pend.) making it the world's only planning tool with multimedia simulations of system performance. EDX also offers an extensive collection of terrain, groundcover, demographic, map image, and vector map data for most areas of the world.

For 13 years EDX has been the leader in PC-based wireless planning tools. We provide features and performance that are not available from any other tool at any price—on any platform.

Contact us today for a fully operational demo CD (not just a slideshow.) You'll discover why EDX is the name to know in wireless system planning tools.



Tools for Wireless Design

Circle (12) on Fast Fact Card

Effective acoustic echo canceling in digital wireless networks requires a different approach from conventional hybrid echo canceling because of the non-linear tail circuit. The implementation must account for these non-linearities and must remain stable upon convergence to provide seamless canceling. For echo canceling to be effective in this mode requires the significant processing capacity of a network processing canceler when in the presence of low-performance handsets.

Traditional echo cancelers are limited to 128ms tail lengths, largely due to cost. Processing delays in the tail circuit (between the MSC and the handset) of a mobile system will result in tail lengths approaching 300ms. To cancel effectively, a 64ms canceler needs to anticipate the non-linearity associated with this additional delay and cancel the echo where the reflections are most prominent. Initial convergence accounting for this tail circuit property will result in a more stable system. Photo 1 on page 24 shows voice prints of echo without and with cancelation.

Architecturally, ideal use of space in the MSC for an acoustic canceler would result from the use of a canceler that looks both into the wireless end and out at the PSTN end, in a single canceler package. Photo 2 on page 32 shows one such canceler. The alternative (independent cancelers that are wired back-




Figure 3. The graph shows the relative speech performance of GSM speech coders.

to-back), requires additional money, space and power. Because of the unpredictability of the handset's AERL capabilities and the variability of the caller environment, it is impractical to place a canceler in the circuit only when conditions require it.

Conclusion

Voice quality problems, particularly those attributable to handsets, reflect poorly on overall network quality. The ideal solution, stricter governance of handsets, is impractical both from an economic and technical perspective. The handset marketplace demands small size, high fidelity and low prices. Implementation of sophisticated processing to solve acoustic echo problems at this level is not likely because it would adversely affect handset size, weight and cost. From a technical point of view, specifying and testing handsets in many and varied environmental conditions with realistic test conditions and stimuli have been resisted to date.

ALL THE COMMUNICATION EQUIPMENT YOU NEED. . . IN ONE CATALOG!

For over 20 years, Marketronics has provided quality communication equipment at very competitive prices.

Now, we bring you our NEW Product Selection Guide. It's packed with cutting edge products from many new manufacturers as well as expanded offerings of existing product lines.

When you select Marketronics as your provider, you'll receive quality equipment along with excellent service at the lowest total cost.

Contact us today to request your FREE copy of our catalog!

tel: 800 845 1230 or 954 846 1011

fax: 954 846 1672

email: sales@marketronics.com

www.marketronics.com

- More than 10,000 items
- Over 120 Manufacturers
- Lowest Total Cost



PLEASE VISIT US AT PCS '98 IN BOOTH #377 OR AT TELECOM LATINA IN BOOTH #347

World's Leading Distributor of Quality Wireless Equipment

Foresight.



Hindsight.



Site Master**
lets you see
potential quality
problems
before your
customers do.

Customers expect perfection.

Better preventive maintenance is the way to deliver it. That's why there's Site Master.

Site Master makes sure small problems don't turn into big ones. It records antenna system signature characteristics and stores them for comparison over time. Site Master even works in the presence of live site interference. And thanks to Frequency Domain Reflectometry, potential problems can be pinpointed and repaired, saving time and money. That's what preventive maintenance is all about.

But seeing is believing. For information or to set up a demonstration, call 1-800-ANRITSU today.



Inritsu
One world. One name, Anritsu.




Photo 2. A Bidirectional echo canceler board.

It falls to network providers to implement solutions that deliver better voice quality to their customers. State-of-the-art acoustic or bidirectional hybrid and acoustic echo cancelers can provide that support today to wireless networks worldwide.

References

"Analysis of Noise Sources when Measuring Echo Loss of GSM-Mobiles with the GSM-Test System," Special Mobile Group 7, European Telecommunications Standards Institute, Sophia Antipolis, France, TDoc SMG7 448/97.

"Artificial Voices," ITU-T Recommendation P.50, International Telecommunications Union, Geneva, 1993.

"Control of Talker Echo," ITU-T Recommendation G.131, International Telecommunications Union, Geneva, 1996.

Echo canceling vs. echo suppression

Have you ever been on a speakerphone conference call where you couldn't get a word in edgewise? The problem may not be long-winded associates—it's probably an echo suppresser.

Echo suppressers are commonly used in telephony for providing cheap, effective echo control. Simply put, an echo suppresser is a one-way attenuator that is activated when speech (or paper rustling or other high background noise) is detected on the transmit side. The major drawback of an echo suppresser is that it blocks transmission in one direction while the other direction is active.

Echo cancelers use a more userfriendly approach to echo control. The echo canceler characterizes the tail circuit impulse response and applies a sophisticated subtraction algorithm to the return path, which removes a significant amount of echo. Any remaining (residual) echo is then further processed by the non-linear processor, which performs complex attenuation of that residual echo.

Incorporated into many echo cancelers is the ability to inject comfort noise. In fact, many new echo cancelers have noise injection capabilities that provide background noise matching, which further enhances the aural comfort.

As for that interminable speaker? Because only very low-level residual echo is attenuated, you can make your point—and he will hear you.

"Digital Network Echo Cancelers," ITU-T Recommendation G.168, International Telecommunications Union, Geneva, 1997.

Goetz, I., "Opportunities for Improving the Speech Quality of Digital Cellular Systems," DMR VII Conference, October 1996.

"Liaison Statement—Problem with Echo Loss Testing," Special Mobile Group 7, European Telecommunications Standards Institute, Sophia Antipolis, France, TDoc SMG7 553/97. Mehrotra, A., "GSM System Engineering," Artech

House, Boston, 1997.

"Problem with Echo Loss Testing," Special Mobile Group 11, European Telecommunications Standards Institute, Sophia Antipolis, France, TDoc SMG11 30/98.

If you depend on your batteries, here are a few things we think you should know...

Our unique battery processing and reconditioning systems are widely recognized as the very best available. Even the US Military says so, and who's going to argue with them? From the ground up, our system designs are superior in many ways. Simply put, it means we offer you more capabilities, more reliability, for more battery types, with a better, simpler interface than any other system - period. For example, we offer intelligent, truly simultaneous processing of up to 252 batteries faster than others process 4!

Our technological leadership is thanks in part to our ability to provide custom-designed solutions when customer needs exceed existing industry capabilities. That's how we pioneered the only true reconditioning charger. That's also how we created the only true Smart Battery Processing System. We've been leading the industry since 1986; so don't let the other guys mislead you. As they announce their "industry firsts", we want you to know that they've never even come close to catching up.

Our customers report that after using our reconditioning systems, many of their batteries are actually in better shape after 3 years of use than they were new out of the box! This is why our systems often pay for themselves in less than a year. Most people just don't believe it until they see it, so call us today to see how you can benefit from *The BatteryPRO Advantage*.



▲ 28 pack RAMSystem



YEAR 2000 Compliant!



When the performance of your batteries can mean the difference between life and death, why would you settle for anything less than the very best?

http://www.batterypro.com



Critical Control of **A** Base Stations

You can now control up to four base stations from a single, compact, attractive desktop instrument.

Zetron's Digital Tone Remotes are the preferred radio controllers for all critical applications.

Versatility is maximized with a built-in paging encoder and a PC-programmable feature set. Ease-of-use is guaranteed by a text display that shows the formal name ("Police," "Ambulance," "Line Crew," etc.) for every frequency or pager code entered by the dispatcher.

But most importantly, the remotes are from Zetron. This means reliability that is backed up by the industry's

best warranty and technical support.

If you are in the business of supporting critical communications, call Zetron today for more information on the Model 284 Tone Remote.



↑ Emergency

EVERGREEN


Family Maternety Center




Zetron, Inc. PO Box 97004, Redmond WA 98073-9704 USA

Phone: (425) 820-6363 Fax: (425) 820-7031 Email: zetron@zetron.com Web: http://www.zetron.com European Office: Zetron, Inc. 27-29 Campbell Court, Bramley, TADLEY, Basingstoke, RG26 5EG, UK Phone: +44 1256 880663 Fax: +44 1256 880491

PCS: A threat to SMR?





Will hungry, start-up, PCS companies gobble up SMR customer bases by offering multiple services? The smart SMR operator will see an immediate opportunity in many market areas—particularly in one area not usually seen as a potential for radio system owners.

By Donald E. Koehler

Rapid changes in recent years within the communications industry have some SMR business owners looking over their shoulder at increased competition. That competition was first expected to come, at least potentially, from major telecommunication providers. However, changes in federal regulations and within the telecommunications industry may have created more *opportunities* for SMR system operators than competitors—at least in some markets. Here is a quick look at some key history and recent regulatory changes, their effects on the industry and po-

tential new opportunities for SMR system operators.

Prior to 1974, the Bell system owned or operated most of the mobile telephone service market. The LMR systems in service were owned by the user/operator/licensee. When Congress created the specialized mobile radio (SMR) service in 1974, the new service (and spectrum) was divided to keep telephony providers and more conventional radio service providers well apart in the realm of business competition. The cellular and SMR services were created to serve different groups of users, to create opportunity for new business growth and to reduce the cost of dispatch-type services for small business op-

erations. The key difference was the classification of the SMR operator as "private" and the cellular operator as "common" carriers, with different levels of federal and state regulation and oversight.

The success of SMR trunking systems led the FCC to change the rules in 1982 and again in 1983, opening the way for services such as wide-area paging and the use of new frequency bands by private carriers. The growth and success of both services indicates how well the business community was served

Koehler, a communications technician, teaches at the University of Alaska, Anchorage. His email address is afdek@uaa.alaska.edu.

If your business is up in the air...

we'll bring it down to earth.

Our pioneering success in the design and development of components for the wireless communications industry has made systems solutions from the top down a reality. Our patented planar antenna technology has led to the smallest, lightest, most aesthetically pleasing base station and microcell



by the changes. Today, almost 80% of SMR subscribers use the service for their business dispatch needs.

This change within the communications (radio) industry was, in some ways, almost invisible to the general public. At the same time, greater changes were altering the landscape for telecommunications (wireline) providers. The breakup of the Bell operating system into regional bell operating companies (RBOCs) in 1984, and the growth of companies such as MCI and Sprint, forever changed how people would communicate. What effect did these changes have on SMR operators? Little, until 1993.

By 1993, changes in technology, marketplace conditions and delivery of interconnection service had been described as a "technology convergence." This blurring of service and technology was a driving force behind the amendment of the Communications Act of 1934 and the reclassification of all land mobile services as either private mobile radio service (PMRS) or as commercial mobile radio service (CMRS). At once, all operators that provided third-party interconnection to the public switched telephone network (PSTN) were classified as "common carriers" and were regulated as such. If that wasn't enough, the personal communications service (PCS) was created. Not much occurred with PCS initially, as technology choice issues, similar to those faced by the infant SMR industry, slowed growth.

The stalemate was broken, in part, when the telecommunications industry was hit with another major change in 1996. Now local exchange carriers (LECs) were allowed to offer long distance connections, and interexchange carriers (IXCs) could enter the local access market. This change, coupled with spectrum auctions and the high prices paid for that spectrum, had observers in the SMR industry worried. Would hungry, start-up, PCS companies gobble up SMR customer bases by offering multiple services? Could SMRs compete with huge, rich, RBOC-run systems, or would the RBOCs simply purchase existing SMR systems under the new rules?

The complete fallout has yet to be determined, but the smart SMR operator will see some immediate opportunities. One lies in the wireless replacement of the traditional copper "local loop" for the new competitive local exchange carrier (C-LEC) providers in local communities, especially in areas with low population density. Not all PCS license holders want to compete head-to-head with established cellular providers and limit their use of PCS technology to a single-service delivery

As new C-LEC providers start operations, they face several choices for access to their potential customer base. First, they could lease this access from the incumbent local exchange carrier (I-LEC) in the form of the embedded, copper-based, outside plant. This is a large monthly cost to a start-up company, and most I-LECs have fought tooth-and-nail to avoid leasing. Issues over interconnection standards, methods of interconnection, maintenance costs and right-of-way concerns further cloud the issue.

Second, a new C-LEC could build its own outside plant, but regulators frown on this, unless transmission is through fiber-optic cable or a combination of fiber-optic and coaxial cable (hybrid fiber-coax) that offers large bandwidth capacity to the customer. Even if this is considered, the cost to bring service to customers demands a high-density potential customer base and a desire to offer multiple services such as telephony, Internet access, entertainment or security. Right-ofway issues can still cause problems.

Third, a new C-LEC could purchase a PCS license and build a wireless system to provide local access. In many markets, many start-up companies choose to do this. Unfortunately, the auction process forced the price of spectrum so high that many companies could not fund both the cost of new equipment and a license. Further complications in the form of competing PCS technologies (GSM, TDMA, CDMA, PACS and others) can slow the



growth of new C-LEC providers. Why? Until this technology issue settles out, many business customers are reluctant to purchase new subscriber equipment or services—especially if they travel extensively and require roaming support.

Where does this leave the SMR provider? New C-LEC providers might find SMRbased local access attractive, especially for areas with low customer density. It also offers a quick way to ramp up their cash flow with new customers, if the I-LEC has been extremely recalcitrant on local access wholesale leasing.

What is the payback to the system operator? The potential in partnering with a new C-LEC could provide significantly reduced interconnection charges, access to new customers, and the opportunity for enough new traffic revenue to support new growth or equipment in the system. Even a simple reselling agreement (wholesale) has the potential to increase business significantly while reducing the threat of additional immediate competition. The C-LEC, in turn, sees an established service with a known technology and proven performance—and less incentive to purchase their own system, at least in the near term.

The telephony business is significantly different from what SMR providers may have dealt with in the past. It has it's own set of business expectations, paradigms for customer service and maintenance philosophy. This doesn't make it impossible to deal with these companies, you just have to do your homework. In fact, many of the new C-LECs are successful because their "corporate culture" significantly differs from the old Bell system.

References

Calhoun, George C., Wireless Access and the Local Telephone Network, Artech House, Boston, 1992.

Freeman, Roger L., Telecommunication System Engineering, 3rd ed., Wiley, New York, 1996.

Reeve, Whitham D., Subscriber Loop Signaling and Transmission Handbook: Analog, IEEE Press, Piscataway, NJ, 1992.

Reeve, Whitham D., Subscriber Loop Signaling and Transmission Handbook: Digital. IEEE Press, Piscataway, NJ, 1995.

Web references

On the World Wide Web, use the keywords "local loop," "CLEC," "wireless." Applicable sites include www.clecinfo.com, www.bellcore.com and www.fcc.gov.

An exceptional site is www.nortel.com. It has excellent tutorials, particularly "Telephony 101," "Long Distance 101" and "SONET 101."



Circle (43) on Fast Fact Card



Circle (44) on Fast Fact Card

Improving PCS reliability through cell frequency management

Adding additional neighbors to each sector builds in a strategy for improving system reliability with no additional cost in hardware.

By E. Kirk Ellis

In the last few years, there has been an explosion of cell site growth in the wireless industry. Many PCS carrier's system designs do not have the redundancy of their earlier cellular counterparts necessary to meet an aggressive buildout schedule. Some of this is due to the nature of the equipment design or the inherent weaknesses of the format. For example, GSM and TDMA typically use one RF carrier and multiplex several timeslots (talk slots, or logical channels) on one RF transmitter

1-95 606 SMITHFIELD 610 NORTH 4620 FOUR OAKS ₩630 640 4 BENSON (650 KEY XXX = CHANNEL NO. 660 DUNN (XXXT=ALPHA SECTOR 670 XXX_=BETA SECTOR 680 GODWIN 1-95

Figure 1. Site location and frequency assignments are shown for a section of I-95 in North Carolina.

per sector. Failure of this single transmitter takes the sector out, opening up a coverage "hole."

Many sites have been deployed without ac generators for backup or with backup battery capacity of only an hour. To meet the aggressive buildout, providers have deployed most PCS sites using the local telco's T1 wire facilities instead of microwave. Wired T1s are much less reliable than microwave and inherently fail much more often. All of these factors can take a PCS site completely out in short order, often for hours (or even days) before it can be restored.

With its reduced coverage, as compared to 800MHz cellular, there are many more cell sites required for PCS. This inherently offers some opportunity for redundant coverage, but only if the RF frequency "neighbor list" is correctly implemented. This article discusses some ways to implement this backup coverage. GSM systems are the primary focus, but the underlying theory should apply to other technologies as well, including TDMA and some cellular systems.

Neighbor lists and implementations

A neighbor list is a group of parameters that are stored in the cellsite data base con-

Table 1. Site frequency assignment.

SITE	SECTOR	FREQUENCY
Smithfield	alpha	606
Smithfield	beta	610
Four Oaks	alpha	620
Four Oaks	beta	630
Benson	alpha	640
Benson	beta	650
Dunn	alpha	660
Dunn	beta	670
Godwin	alpha	680
Godwin	beta	685

tained in the base station controller (BSC), which is typically located in the mobile switching center (MSC). The neighbor list consists of the channels (frequencies) assigned to the site (including its adjacent sectors) and the channels assigned to the neighboring cell sites.

These neighbor lists are downloaded into the BSC and are used by the BSC to control mobile handoffs between adjacent sectors and neighboring cell sites.

An example will help to clarify this

Ellis is a senior network engineer for BellSouth Mobility, DCS, Raleigh, NC.




Figure 2. Coverage overlaps when all sites and sectors are on the air.




Figure 3. When the T1 is cut, Benson goes off the air, and the coverage changes.

datafill. Imagine a simple system based on highway coverage, using three two-sector sites. This is a typical configuration where coverage is of prime importance, and capacity is not the driving factor.

The hypothetical cell sites are part of the RF buildout designed to cover Interstate 95. Cell sites are located at the towns of Four Oaks, Benson and Dunn as shown in Figure 1 on page 38.

The distance between these sites is covered by deployment of directional antennas pointing up and down the interstate. On a typical PCS1900 GSM system, a channel consists of a control time slot and seven talk time slots. Convention has it that the alpha sector points north and the beta sector points south.

At Four Oaks, the north sector (alpha) is assigned channel 620. The south sector (beta) is assigned channel 630 (see Figure I and Table 1 on page 38).

To the south of Four Oaks lies the town of Benson. Its cell site has channel 640 loaded in the alpha sector and channel 650 loaded in the beta sector. Continuing south on I-95, we reach the town of Dunn, with its cell site loaded with channel 660 (alpha sector) and channel 670 (beta sector).

This buildout continues up and down I-95 with cell sites located about every five miles




Figure 4. Coverage changes again when the Benson beta transmitter fails.







Circle (46) on Fast Fact Card

Table 2. Original basic neighbor list (typical).

SITE	SECTOR	NEIGHBORS
Four Oaks	alpha	610, 630
Four Oaks	beta	620, 640
Benson	alpha	630, 650
Benson	beta	640, 660
Dunn	alpha	650, 670
Dunn	beta	660, 680

(Note: For illustration purposes, only the three sites used in the examples are shown)

north and south of this part of the system.

Cell site mobile handovers

Before we can look at a failure mode, it is necessary to look at the basic operation of the system and its intracell and intercell handovers. Suppose a car is traveling south on 1-95 and approaches the town of Four Oaks. At some point north of town, the mobile originates a call. The call is established on channel 620 (alpha). As the mobile passes by the site, the intracell handover occurs according to the data in the site's neighbor list. Typical implementation has channel 630 loaded, so the mo-

bile is handed off from alpha (channel 620) to beta (channel 630). The beta sector has its neighbor list loaded with channel 620 (intracell neighbor) and channel 640 (intercell neighbor), which is the alpha sector of the site at Benson. These handovers continue in the same fashion, and as the car travels south on I-95, the mobile is handed off from channel 640 to 650, from 650 to 660, 660 to 670 and so on.

One last point. Coverage from Four Oaks overlaps the Benson site, and coverage from Dunn also overlaps the Benson site. The coverage at the town of Benson from these two sites is weak, but useable, even without the Benson site on the air, as shown in Figure 2 on page 38.

Here is where the problem begins.

Failure modes and coverage

Suppose the site at Benson goes off the air due to a cut leased T1 from the local Telco, which occurred when a water line was installed between the local Central Office and the Benson site. (See Figure 3 on page 39).

The cut T1 renders the site at Benson unavailable, as call traffic cannot reach the MSC for processing. The site shuts down automatically when it loses communcations with the MSC.

Our hypothetical user passes by the Four Oaks site, which is loaded with the nowabsent Benson alpha sector. Although adequate coverage to maintain a call exists between Four Oaks and Dunn, without Benson on the air, the sites do not know about each other because they are not on each other's neighbor lists. Hence, as the mobile caller travels down I-95, Four Oaks cannot hand off to Dunn. Somewhere between the two, where Four Oaks' coverage ends, the call is dropped.


The neighbor lists, as initially implemented by the original RF engineering for these sites, are listed in Table 2 above. These are typical basic neighbor implementations found in many carriers' systems.

In the second example (see Figure 4 on page 39), the beta transmitter at the Benson site fails. This is a typical GSM failure that takes a sector down. If a call is up, it passes from the Four Oaks beta sector to the Benson alpha sector as normal.

However, as the mobile caller passes Benson, a problem begins. Because the beta sector is off the air, the alpha sector of Benson has nowhere to hand off to, even though coverage is available from the Dunn alpha sector. The site simply does not know that the other sector (Dunn channel 660) is available because it is not loaded into its neighbor list.

Table 2 shows that the only neighbors

Digital ANI: Compatible with Motorola® MDC-1200®



Micro-Miniature ID-12

Motorola and MDC-1200 are registered trademarks of Motorola Inc.

Manufactured by Control Signal? the ID-12 ANI encoder is a costeffective way to upgrade all the radios in your fleet with ANI that is compatible with Motorola MDC-1200. Works in all radios, and its tiny size (.59" x .65" x .12") allows it to fit in virtually all hand-helds. Has leading and trailing IDs. emergency, and time-out timer. Fleet price (100 qty) \$89 ea.

Call 800-521-2203

CONTROL SIGNAL

1985 S. Depew. #7, Denver, CO 80227 FAX 303-989-8003

Circle (47) on Fast Fact Card



SITE	SECTOR	NEIGHBORS
Four Oaks	alpha	606, 610, 630, 640, + beta sector of site north of the Smithfield site
Four Oaks	beta	610, 620, 640, 650, 660
Benson	alpha	610, 620, 630, 650, 660
Benson	beta	630, 640, 660, 670, 680
Dunn	alpha	630, 640, 650, 670, 680
Dunn	beta	650, 660, 680, 685, + alpha sector of site south of Godwin site

(Note: For illustration purposes, only the three sites used in the examples are shown.)

loaded into the Benson alpha sector are Four Oaks channel 630 to the north and its adiacent sector to the south on the same tower, channel 650, which currently is off the air.

The mobile "drags" the coverage from Benson alpha around the site to the south side and the call drops shortly after the mobile passes by.

Neighbor list additions

What would have happened in the previous two examples if the neighbor lists in Table 3, above, had been implemented instead of the neighbor lists in Table 2. The new neighbor list has three more entries per sector for neighbors (five instead of two).

The list has more neighbors because it is looking ahead one sector in each direction past its immediate neighbor. Compare the Table 2 typical implementation with the Table 3 implementation, looking at the Benson alpha sector as an example.

In the basic implementation in Table 2, Benson alpha only has its immediate neighbors loaded, that is, Four Oaks beta sector at the site to the north, channel 630, and Benson beta channel 650 to the south, located at the same site.

In the improved implementation, the site knows to look ahead. The system parameters are set to use the strongest available neighbor, so under normal system operation, the neighbor lists cause handovers to proceed exactly as in Table 2.

To the north, Benson alpha not only looks at Four Oaks beta, but knows that Four Oaks alpha and Smithfield beta exist as well. Likewise, to the south, in addition to its own beta sector, it also knows that Dunn alpha and beta and Godwin alpha exist.

What will happen this time when the T1 is cut to the site at Benson? The site at Benson is off the air. A southbound caller initiates a call and is on the alpha sector of Four Oaks. As he passes the site, he is handed off from Four Oaks alpha to beta (intracell handover). The mobile continues south on 1-95. The site at Benson is not on the air, but this time the neighbor list makes the call available for handover

to the alpha sector at Dunn. Although call quality is not as good as normal, the call does stay up and is not dropped as the mobile moves from Four Oaks beta to Dunn alpha. The hole in coverage with the failure of the Benson site has been reduced to a weak area, all done by neighbor list data fill.

In the second scenario, repeated from above, the Benson beta transmitter has failed. As the vehicle travels south from Four Oaks toward Benson, all is well. When the caller goes past the Benson site, instead of "dragging" the alpha sector around the south side of the site, the neighbor list indicates that Dunn alpha exists, and the call is handed off to Dunn alpha

instead of being dropped. Again, proper neighbor list loading has prevented dropped calls by filling in a coverage hole caused by equipment failure.


Summary

Clearly, in many locations, system redundancy can be built in by using existing coverage that is not normally used when all sites are on the air. When all sites are operating normally, handovers occur in the simplistic fashion shown in Table 2. However, adding additional neighbors to each sector builds in a strategy for improving system reliability with no additional cost in hardware.

In these cases, call quality will most likely be degraded, but call processing will continue, with handovers being made, and will not necessarily drop if the sites are appropriately spaced.

Not implementing additional neighbors will definitely cause dropped calls as the mobile drives into a failure-induced hole and the sector is "dragged" out.

This strategy is easily implemented with a little additional time and planning when the RF engineering of the system is done. Having fewer dropped calls and apparent holes keeps customers happier, reducing churn and increasing revenues.



Circle (49) on Fast Fact Card

Due process goes south in deal with north

> The secret deal for Canadian SMR Channels

Land Mobile Services," was signed by Ronald

By Robert H. Schwaninger Jr.

On May 14, 1998, the FCC secretly entered into an agreement with our neighbors in Canada to allow Nextel and its Canadian counterpart, Clearnet, to use 800MHz channels along the U.S.-Canadian border, for which use is precluded for all other licensees by rule.

In essence, the agreement would allow one U.S. company, McLean, VA-based Nextel Communications, and one Canadian company. Clearnet, to do what no other American company has been allowed to do for over a decade—that is, to use 800MHz channels in one country that have been exclusively allocated for use in the other country.

The document, "Special Coordination Procedures for the Use of Frequencies in the Bands 806-821MHz and 851-866MHz for

Table 1. Geographic area within 100km of the United States-Canada border between 72° and 74° 30'W

		with Canadian	red frequencies madian priority use (MHz)	
819.3875	864.3875	814.7125	859.7125	
819.6875	864.6875	816.3125	861.3125	
819.7125	864.7125	816.6125	861.6125	
819.8375	864.8375	817.3125	862.3125	
820.6875	865.6875	818.4375	863.4375	
820.7375	865.7375	818.5375	863.5375	

Note: Frequencies listed above will be used for the IDEN digital network only. (Source: FCC documents.)

Amero, director, Space and International Regulatory Activities, Industry Canada, on April 9, 1998, and was cosigned on May 14, 1998, by a representative for Regina Keeney. chief of the FCC's International Bureau (IB).

Table 2. Geographic area: within 100km of the United States-Canada border between 74° 30' and 76° W longitude.

Paired frequencies with U.S. priority use (MHz)		Paired frequencies with Canadian priority use (MHz)	
818.9625	863.9625	809.2125	854.2125
818.9875	863,9875	809.4625	854.4625
819.0125	864.0125	809.9125	854.9125
819.1125	864.1125	810.1625	855,1625
819.1375	864.1375	810.4125	855,4125
819.4125	864.4125	810.8875	855.8875
819.4375	864.4375	811.1375	856.1375
819.4625	864,4625	813.2375	858.2375
819.5625	864.5625	813,4875	858,4875
819.5875	864.5875	813.7375	858,7375
819.8625	864.8625	813.9875	858.9875
819.8875	864.8875	814.2375	859.2375
819.9125	864.9125	814.4875	859.4875
820.0125	865.0125	814.7375	859.7375
820.0375	865.0375	814.9875	859.9875
820.3125	865.3125	816.2875	861.2875
820.3375	865.3375	816.5375	861.5375
820.3625	865,3625	816.7875	861.7875
820.4625	865.4625	817.0375	862.0375
820.4875	865,4875	817.2875	862.2875
820.7625	865.7625	817.5125	862.5125
820.7875	865.7875	817.7625	862.7625
820.8125	865.8125	818.0125	863.0125
820.9125	865.9125	818.2625	863.2625
820.9375	865.9375	818.5125	863.5125

Note: Frequencies listed above will be used for the IDEN digital network only. (Source: FCC documents.) Judging by footnotes and references, the document had been in the works since at least Jan. 9, 1997.

llustration by Scott Dolash

The text of the agreement is fairly short, running only two pages (see page 43), with a seven-page annex of channel charts that identify the hundreds of frequencies Nextel can use in the United States and that Clearnet can use in Canada. The agreement and the associated channel charts (reproduced as Tables 1 through 5 throughout this article) are amazing in their effect and what they say about the state of affairs in our government.

The agreement allows one, and only one, company to avoid the channel allocation scheme that has existed between the United States and Canada since 1982 and that has limited the number of available channels above "Line A" for all applicants and licensees. Line A is an imaginary line at a fixed distance from, and approximately parallel to, the Canadian border.

Although the agreement language mentions Nextel and Clearnet, the agreement attempts to appear neutral as to other operators that might also be able to use the frequency-sharing arrangement across the border. For example, if a company in Syracuse, NY, can find a sister company in

Schwaninger, MRT's regulatory consultant, is a partner in the law firm of Brown and Schwaninger, Washington. DC. He is a member of the Radio Club of America.

Special Coordination Procedures for the Use of Frequencies in the Bands 806-821MHz and 851-866MHz for Land Mobile Services

Recognizing that the priority use of frequencies by the United States of America and Canada remains pursuant to Section 3 of the Arrangement Concerning the Use of the Band 806-890MHz Along the Canada-United States Border1, as amended2, between the Federal Communications Commission (FCC) and Industry Canada³ hereafter referred to as the Agencies:

Recognizing further that administrations must maintain the flexibility to assign frequencies from their respective frequency blocks where they enjoy priority usage, using their chosen method of authorization;

Recognizing that there may be licensees/operators other than Nextel Communications Inc. in the U.S. or Clearnet Inc. in Canada on frequencies identified in Annex A;

Recognizing that the use of frequencies identified in Annex A may be different beyond 100km of the border than that within this border zone;

Noting that business arrangements may exist between Canadian and U.S. system operators, in this case Clearnet Inc. and Nextel Communications Inc., which provide for spectrum-efficient, seamless frequency re-use plans that extend across the Canada/U.S.A. border and facilitate roaming;

It is AGREED that:

Industry Canada and the FCC may authorize these system operators to use specific frequencies, as set forth in Annex A (consisting of five parts) and incorporated herein by reference, within 100km of the United States-Canada border that exceed the Power Flux Density limits specified in the Arrangement and are in the other countries' frequency block provided that the following conditions are placed on such authorizations:

- the system operators must file with their representative Agency a copy of the business arrangement listing the frequencies they would be sharing and in which geographical areas;
- agreement will be reached between the Canadian and U.S. licensees for each proposed station within the relevant geographical service area before it is placed in operation;
- in the event that the operations provided for herein cause harmful

interference to primary operations in either country, the system operators will take immediate action to mitigate the situation. Should resolution of the interference situation not be found, the interfering station will be required to cease operation within 10 calendar days except, in the case where public safety licenses are affected, operations would cease immediately upon being advised;

- no service may be offered by the Canadian licensee within the U.S. and, no service may be offered by the U.S. licensee within Canada; and,
- any changes to the notified business arrangement will require a review by the Agencies.

The authorizing Agency shall send a notification to the other Agency for each frequency assigned under the terms of this procedure.

In the event that any of the authorized frequencies listed in Annex A are affected by subsequent licensing action by either Agency, operations on these affected frequencies in the other country will cease within three months from date of notification.

For any reason whatsoever, this procedure may be subject to unconditional withdrawal by either Agency giving three months written notice.

This procedure is accepted as a revised understanding between the FCC and Industry Canada and replaces Special Coordination Procedure previously issued to Nextel Communications Inc. and Clearnet Inc., originally signed January 9, 1997. This revised procedure will come into effect on the date of signature by representatives of both Agencies.

(signed) Regina M. Keency Chief, International Bureau Federal Communications Commission May 14, 1998


(signed) Ronald Amero Director, Space and International Regulatory Activities Industry Canada April 9, 1998

Arrangement between the Department of Communications of Canada and the Federal Communications Commission of the United States concerning the use of the band 806-890MHz along the Canada-United States border, dated April 7,

²See exchange of letters between the FCC and Industry Canada dated December 10, 1994.

³ Formerly the Department of Communications.

VSWR BRIDGES & TEST CABLES



FEATURES:


5 watt power High directivity RF reflected port Rugged construction

Using the EAGLE return loss bridge allows frequency domain reflectometry tests to be made easily and inexpensively. There is no need to spend thousands of dollars on a dedicated antenna tester. Simply use the EAGLE bridge with your present spectrum analyzer and tracking generator. This technique is described in our free application note. See offer below.

Price: \$469.00 for a 1.0 GHz bridge.

FEATURES:

Low loss Low Cost Custom labels Swept to 3.0 GHz Rugged! 60 lb. pull Excellent return loss



Are you frustrated with cable assemblies that break easily, are lossy at low microwave, or work intermittantly? Our bridge customers had the same problem. At EAGLE we now manufacture low-cost rugged test cables! Each one is tested on a vector network analyzer to 3.0 GHz. Our custom labeling makes cable ID a snap. Excellent return loss reduces disturbances to combiners and filters.

Price: \$29.00 1-4 quantity with "N" connectors.

Call for FREE application note: "Antenna and Feedline Measurements"



PO. BOX 4010 * SEDONA, AZ*86340 * VOICE: (520) 204-2597 * FAX: (520) 204-2568

Canada that will agree to share channels across the border, then, theoretically, the company in Syracuse could use some Canadian channels and vice versa. At last check, only one U.S. company, Nextel, had an affiliated Canadian company with which to use the terms of the agreement. Given the recent 800MHz auction, this number is unlikely to increase.

Motorola's involvement

If you scan the pages of the agreement and charts, you will not find the name "Motorola." The language of the agreement does not say. for example, "At the behest of the biggest, blue-bat behemoth in land mobile equipment sales on either side of Lake Erie, we, the browbeaten members of the FCC and Industry Canada, hereby declare. ..." The document is a bit more subtle than that,

However, the fact that Motorola stands to benefit by the deal is carved into the footnotes of the frequency charts that read: "Note: Frequencies listed above will be used for the IDEN digital network only." Stated another way, if you want to benefit by this agreement, buy Motorola, and buy often.

With Digital PCS... You need a HELLO...what... I can't hear...WHAT. Hirschmann signal...what... I can't hear you... HELL00000... antenna now more than ever for your wireless phone! The new PCS network is still under development...sa you can't always get a strong signal for your digital PCS phone when you're in the car. Not only that, but digital phones are 1/3 as powerful as cell phones. The best way to a clear signal inside your car for both PCS and cellular is a Hirschmann ON-2d/b Glass Mount dual band antenna on the outside. Because when you have a weak signal, you need a strong antenna. You need a Hirschmann. Call, fax or e-mail us today for more information. Rheinmetall Elektronik Hirschmann . Industrial Row . P.O. Box 229 . Riverdale, NJ 07457 800/225-0524 973/835-5002 Fax: 973/835-8354 e-mail: ant-sales@hirschmann-usa.com Circle (51) on Fast Fact Card

Table 3. Geographic area: within 100km of the United States-Canada border between 76° and 81° W longitude.

Paired fre		w	Paired fre	quencies priority use
(Mi		, A.A.	(MI	łz)
818.7625	863.7625		809.1625	854.1625
818.8375	863.8375		809.2125	854.2125
818.9625	863.9625		809.2375	854.2375
819.0125	864.0125		811.1125	856.1125
819.0375	864.0375		811.1625	856.1625
819.0625	864.0625		811.6125	856.6125
819.0875	864.0875		811.6625	856.6625
819.1125	864.1125		813.1625	858.1625
819.1375	864.1375		813.6625	858.6625
819.1625	864.1625		814.1625	859.1625
819.2125	864.2125		815.0625	860.0625
819.2375	864.2375		815.1375	860.1375
819.2875	864.2875		815.6375	860.6375
819.4125	864.4125		816.0875	861.0875
819.4625	864.4625		816.1375	861,1375
819.4875	864.4875		816.2875	861.2875
819.5125	864.5125		816.3375	861.3375
819,5375	864.5375		816.3875	861.3875
819,5625	864.5625		816.5375	861.5375
819.5875	864.5875		816.5875	861.5875
819.6875	864.6875		816.6375	861.6375
819.7125	864.7125		816.7875	861_7875
819.7875	864.7875		816.8375	861.8375
819.8625	864.8625	160	816.8875	861.8875
819.9125 819.9375	864.9125 864.9375		817.1375 817.3375	862.1375
819.9625	100 C C C C C C C C C C C C C C C C C C		817.3875	862,3375
819.9875	864,9625 864,9875		817.5125	862.3875 862.5125
820.0125	865.0125		817.5625	862.5625
820.0375	865.0375		817.5875	862.5875
820.0625	865.0625		817.6125	862.6125
820.1125	865.1125		817.6375	862.6375
820.2375	865.2375		817.7625	862.7625
820.2625	865.2625		817.8125	862.8125
820.3625	865.3625		817.8875	862.8875
820.3875	865.3875		818.0125	863.0125
820,4125	865.4125		818.0625	863,0625
820.4375	865.4375		818.0875	863.0875
820,4625	865.4625		818.1125	863.1125
820,4875	865,4875		818.1375	863.1375
820.5125	865.5125		818.2625	863.2625
820.5875	865.5875		818.3125	863.3125
820.7125	865.7125		818.3375	863.3375
820.8125	865.8125		818.3625	863,3625
820.8375	865.8375		818.3875	863,3875
820,8625	865.8625		818.5125	863.5125
820.8875	865.8875		818.5625	863.5625
820.9125	865.9125		818.5875	863.5875
820.9375	865.9375		818.6125	863.6125
820.9625	865.9625		818.6375	863.6375

Note: Frequencies listed above will be used for the IDEN digital network only. (Source: FCC documents.)

There's a real problem here. Since when does the U.S. government enter into deals with foreign countries that identifies a proprietary technology in the terms of the negotiated agreement? ("Earth' to International Bureau Chief Regina Keeney. There's a call for you from the U.S. Department of Justice Antitrust Division on line two.")

Then there's that other little element lurking in the background. As I recall, Motorola owns about 30% of the equity in Nextel (and hence Clearnet). So what we have here is the "Canadian/U.S. IDEN Relief Act of 1998." complete with enough caveats to preclude any other entity from enjoying the fruits of this clandestine compact.

To say that this deal "isn't fair" is to do a disservice to the word fair. This little cabal of U.S./Canadian chicanery is so patently

unfair that it makes a mockery out of due process and points out how far wrong the FCC can go if it fails to allow the American public to look over its shoulder.

Okay, so I'll be fair. In a meeting I had with staff members of the IB in August, it appeared that the staff never thought that the deal would be a problem.

"Nobody ever complained about other agreements we've brokered," they said.

The IB appeared to be acting under the advice of the Wireless Telecommunications Bureau, which also evidently does not have a copy of the FCC rules. Could it be the IB was lured into the swamp by the WTB?

Why the cloak and dagger?

The FCC's action, without public notice, comment, rulemaking or any mention in any official document publication, is quite curious. Why the secrecy? There are many local operators of SMR systems in Region 2 (upstate New York) and along the Canadian border all the way to Puget Sound in Washington. So why weren't these SMR operators informed about the discussions with Industry Canada (formerly the Canadian Department of Communications)?

Obviously, numerous other companies would be vitally interested in participating in any discussion that might allow any of them to achieve additional channels. Those same operators might be quite concerned to learn that Nextel is poised to increase their competitive position via additional channel depth through a sweetheart international agreement. So why the secrecy?

Maybe the whole affair was well-covered in the "Toronto City Gazette" next to the Blue Jays' box scores. But the Associated Press missed the story, and the FCC never put it on the wire. Frankly, the only way I found out about it was that one of my clients tripped across the agreement almost by accident. It was not posted on the FCC's Web site.

The agreement was inked about two months ago, but I missed the "grip-and-grin" photos of diplomats as they shook hands in cyberspace on the deal, using the FCC's new Universal Licensing System, thereby adding \$2.30 per minute to the cost of negotiations.

At the same time that the FCC is claiming increased access to its procedures via the Internet, the agency has failed to consider what happens if its actions are kept off the Web, out of public notices, outside the pages of the Federal Register and holed up in file cabinets of the International Bureau.

The only plausible reason for the agency's failure to make public this discussion with

Table 4. Geographic area: within 100km of the United States-Canada border between 81° and 85° W longitude.

with U.S.	equencles priority use Hz)	Paired fre with Canadian (Mi	priority use
809.6625	854.6625	811.2625	856,2625
809.9125	854.9125	811.4375	856.4375
817.7375	862.7375	811.5125	856.5125
818.9875	863.9875	811.6875	856.6875
819.4125	864.4125	811.7625	856.7625
819.4375	864.4375	811.9375	856.9375
819.4625	864.4625	812.0125	857.0125
819.4875	864.4875	812.1325	857,1325
819.5125	864.5125	812.1875	857.1875
819.5375	864.5375	812.2625	857.2625
819.6375	864.6375	812,3875	857.3875
819.6875	864.6875	812.4375	857.4375
819.7375	864.7375	813.1875	858.1875
819.7625	865.7625	813.2375	858.2375
819.7875	864.7875	813.4375	858.4375
819.8375	864.8375	813.4875	858.4875
819.8625	864.8625	813.6875	858.6875
819.9125	864.9125	813.7375	858.7375
819.9875	864.9875	813.9375	858.9375
820.4375	865.4375	813.9875	858.9875
820.4625	865.4625	814.1875	859.1875
820.5375	865.5375	814.2375	859.2375
820.6375	865.6375	814.4875	859.4875
820.6875	865.6875	814.7375	859.7375
820.7375	865.7375	814.9875	859.9875
820.7625	865.7625	815.0625	860.0625
820.6375	865.6375	815.3125	860.3125
820.8625	865.8625	815.5625	860.5625

Note: Frequencies listed above will be used for the IDEN digital network only. (Source: FCC documents.)

In order for a company to survive in this communications jumple, it must produce a

In order for a company to survive in this communications jungle, it must produce a product that gives reliable service, is cost effective and operates at peak performance.

TPL Communications gives you this and more with over 25 years of experience, knowledge and know-how. TPL's family of continuous duty *power amplifiers* are known around the world as the most reliable, top performing amplifiers on the market today.

Here is a list of just a few of the family's outstanding features:

HMS Series -


- Output to 500 watts VHF, 300 watts UHF & low band, 250 watts 800-900MHz.
- Digital meter & remote monitoring for system evaluation.
- Self-contained regulated switching power supply.
- · Over-temperature & VSWR protection/power reduction.

LMS Series -

- · Power levels up to 120 watts, from 35 to 960MHz.
- Digital meter & remote monitoring for system evaluation.
- Self-contained regulated switching power supply.
- Over-temperature and VSWR protection/power reduction.

RXR Series -

- Accommodates all bands from 35 to 960MHz.
- · Input as low as 25mW, output up to 120 watts.
- · Supplied with or without a DC power supply.
- · Front panel circuit breaker/switch.
- · Fan option available.



HMS Series



Call 800-HI POWER for more information

3370 San Fernando Rd., #206 • Los Angeles, CA 90065-1417 • (213) 256-3000 • FAX (213) 254-3210 • electronic@compuserve.com

Canada is that it stinks and the FCC knows that it stinks. It stinks the same way that John D. Rockefeller's secret deals with the railroad smelled, only this time the robber barons are trading in spectrum, rather than oil, and they're using the federal government as their broker.

Yeah, but is it legal?

This agreement is fine, as long as Nextel doesn't actually start using Canadian channels north of Line A. Huh? What the heck are you talking about, Schwaninger? Okay. here's the deal. The governments of Canada and the United States can get together and agree on anything they want. They can decide that in case of Martian attack, only women named Greta will be allowed to breed with planetary-challenged people. These handshake (or tentacle-shake) deals can be struck, and it means little-unless it gets approved by the U.S. Senate via a treaty procedure.

To be legally effective, however, these semi-formal agreements must comport with the laws of the local countries. In the case of this particular agreement, that may be a big problem. First, the agreement would create a change in the FCC rules. Such changes may only be made pursuant to no-

Table 5. Geographic area: within 100km of the United States-Canada border between 121° 30' and 125° W longitude.

Paired fre		Paired fre with Canadian	
(MI		(Mi	100 Teles
817.5125	862.5125	810.1375	855.1375
817.5375	862.5375	810.1875	855.1875
817.5875	862.5875	810.3875	855.3875
817.6625	862.6625	810.4375	855.4375
817.6875	862.6875	810.6375	855.6375
817.7125	862.7125	810.6875	855.6875
817.8125	862.8125	810.9375	855.9375
818.0125	863.0125	811.0875	856.0875
818.0625	863.0625	811.1125	856.1125
818.1125	863.1125	811.1375	856.1375
818.3375	863.3375	811.5875	856.5875
818.4375	863.4375	811.6375	856.6375
818.5375	863.5375	812.0875	857.0875
818.5875	863.5875	812.1125	857.1125
818.7125	863.7125	813.0375	858.0375
818.7375	863.7375	813.0875	858.0875
818.8375	863.8375	813.1125	858.1125
819.0375	864.0375	813.1375	858.1375
819.0625	864.0625	813.1875	858.1875
819.1125	864.1125	813.8375	858.8375
819.2125	864.2125	813.8875	858.8875
819.2875	864.2875	814.0375	859.0375
819.3125	864.3125	814.0875	859.0875
819.4125	864.4125	814.1125	859.1125
819.4375	864.4375	814.1375	859.1375
819.4625	864.4625	814.1875	859.1875
819.4875	864.4875	815.0375	860.0375
819,5125	864.5125	815.0625	860.0625
819.5625	864.5625	815.0875	860.0875
819.5875	864.5875	815.1125	860.1125
819.6875	864.6875	815.1375	860.1375
819.7875	864.7875	815.2875	860.2875
819.8375	864.8375	815,3125	860.3125
819.8625	864.8625	815.3875	860.3875
819.9125	864.9125	815.5375	860.5375
819.9375	864.9375	815.5625	860.5625
819.9625	864.9625	815.5875	860.5875
819.9875	864.9875	815.6375	860.6375
820.1125	865.1125	815.7875	860.7875
820.3125	865.3125	815.8125	860.8125
820.3375	865.3375	815.8375	860.8375
820.3875	865.3875	815.8875	860.8875
820.4375	865.4375	816.0375	861.0375
820.5875	865.5875	816,0625	861.0625
820.6375	865.6375	816.0875	861.0875
820.6875	865.6875	816.1125	861.1125
820.7375	865.7375	816.1375	861.1375
820.7625	865.7625	816.2125	861.2125
820.8375	865.8375	816.2375	861,2375
820.8625	865.8625	816.3875	861.3875

Note: Frequencies listed above will be used for the IDEN digital network only. (Source: FCC documents.)

ic (an

ortunately, when choosing EAGLE WIRELESS R.F. infrastructure products and services, you can choose all three: Price, Features & Quality. EAGLE has a full line of R.F. infrastructure products to fill all of your transmission needs ranging from full highpower FLEX Base Stations to small low-power "fill-in" Extend-A-Page systems. All domestic frequency bands are covered as well as most international frequencies.

Quality R.F. product at a reasonable price is Eagle's major objective. Where else can you buy a full-featured 300 Watt 900 MHz FLEX base station including cabinet, metering and all standard accessories for under \$12,000

Ask about our new 80 Watt Low Cost Compact Base Station.



Eagle's full line of R.F. infrastructure products are built with the best components available, feature packed and very competitively priced.



EAGLE WIRELESS INTERNATIONAL

Delivering Quality, Features & Value

BASE STATIONS / TRANSAUTTERS . POWER SUPPLES . CONTROL PRODUCTS . REPEATER / FILLIN PRODUCTS . PAGING TERMINALS . SPREAD SPECTRUM PRODUCTS

800-628-3910

281-280-0488

281-280-0488 www.eglw.com sales@eglw.com

FLEX is a frademark of MOTOROIA

Circle (33) on Fast Fact Card

tice-and-comment rulemaking in accord with the Administrative Procedures Act. No rulemaking-no deal.

Next, the deal would have to be shown to be in the public interest and not harmful to small business in accord with the Regulatory Flexibility Act. I humbly suggest that a deal that benefits only one entity and its major equipment supplier is unlikely to be found to be "in the public interest," and I further suggest that the effect of allowing Nextel carte blanche in avoiding the prohibitions on the use of Canadian frequencies will be deemed detrimental to competing, small businesses.

Next, the deal would have to conform with the terms of the most recent 800MHz auction of the upper 200 channels and the decisions within the orders for future action

on the lower 150 channels. If the agency *knew* this deal was in the works (which the agreement implies) and failed to inform the public, then the auction was an even bigger farce than suspected.

The courts take a dim view of agency actions that provide a special benefit to a single entity while hiding its gift within unpublished



deals squirreled away in the files. What possible comments might have been received to the auction dockets if all commenters had been informed about these pending negotiations? Who else might have joined the bidding? We don't know—and neither do the courts.

Then there's the freeze. Many of the channels that Nextel might want to license in accord with the deal are caught up in an application freeze. How does Nextel get around the freeze? Again, those pesky

U.S. laws are in the way.

There's also the problems of *ex parte* actions before and by an agency that fails to notify affected parties; figuring out frequency coordination issues; failure to provide publication of a substantive rule change, thereby causing the document to be legally ineffective; and a host of other little problems generally known as laws, statutes, due process and equity.

So, as bird cage liner, the agreement is interesting. As a legally enforceable document allowing Nextel to avoid the plain language of the FCC rules, it has a way to go.

Kill it before it mutates

If history is our best teacher, then the industry should recognize that Nextel will use this two-page agreement as justification for moving forward in its plan to leverage its Canadian channels. We should not let this occur. Fortunately, the agreement itself provides an out.

One of the terms of the agreement states, "[f]or any reason whatsoever, this procedure may be subject to unconditional withdrawal by either Agency giving three months written notice." I suggest that we, the American people, remind our government that such sweetheart deals are not to be tolerated in a free-enterprise system.

I respectfully recommend that every SMR operator, every private user of 800MHz channels north of Line A, every community repeater operator who ever had to get Canadian clearance, CTIA, AMTA, PCIA, SBT, ITA, UTC, and every other association whose members were left off the invitation list to discuss the agreement, contact the FCC and tell them to withdraw immediately. These demands should include a request that any further discussion regarding future use of 800MHz channels north of Line A should include representatives of *all* affected parties.

Government works best when it works in the open, not behind closed doors. The Sunshine Act and the Freedom of Information Act and similar legislation were created specifically to allow citizens to review and participate in the decision-making process of our elected and appointed representatives. Secret deals that provide gross favoritism to a single company must be vigorously discouraged.

The history of the FCC's regulation of Nextel is one of constantly emerging evidence of secret deals. The original Fleet Call waiver request in 1991, which was signed by a host of ex-FCC officials; the expansion of loading credit, which allowed Nextel to claim sufficient loading for any requested facility; the grant of the OneComm applications in 1994, en masse and on a Saturday, which was explained by reference to an electronic filing method that was unpublished, untried, and unknown before or since that date; the acceptance of thousands of Nextel applications without coordination, or proper fees, or engineering for which the FCC has formally published a denial, but which its records show is completely true; the forbearance by the agency to demand construction information from Nextel despite its receipt of a request to do so in 1996; the grant to Nextel of hundreds of improperly short-spaced channels in the FCC's computer run of 1995; the FCC's allowing Motorola to sell a 900MHz widearea license that was improperly granted by the FCC in violation of a U.S. Justice Department consent decree involving Nextel; the grant of assignment applications to Nextel for its purchase of hundreds of unconstructed Transit Communications channels; the FCC's progressing with the 800MHz auction without required authorization by the Small Business Administration in 1997; and on and on. The list of known shenanigans is practically endless.


It is time that the industry demand that Nextel receive equal treatment under law. It is time for Congress to seek resignations from all federal employees who have participated in brokering these deals.

It is time for the agency to admit its problems, its weaknesses and its inability to resist participation in improperly providing assistance for unfettered growth of a single, favored company.

It is time for something as basic and hokey and necessary as honest government.

D.T.M.F DECODER

For interconnect and remote control applications



VOICE SECURITY ENCRYPTION

The Model NC802 Model is a miniature NC802 inversion scrambler designed provide intermediate level security for two-way radio voice communication systems and is a perfect, cost-effective solution to entry-level voice scrambling as a defense against unauthorized or casual listeners. The NC802 provides eight user selectable carrier codes commonly used by other manufacturers and interfaces easily to most radios with near transparency to the user

For Detailed Specifications or Product Catalog call our 24-Hour NorFax retrieval system at 530-477-8403 or E-Mail norcomm@jps.net.



15385 Carrie Dr., Grass Valley, CA 95945 USA

Circle (64) on Fast Fact Card

technically speaking

The backup plan (Plan B?)

By Harold Kinley, C.E.T.

Even the best-laid plans can run amuck. No matter how many backup systems you have in place, you will never achieve 100% reliability. You might achieve 99.9999% or better, but never 100%. I am speaking of communication systems in general and dispatching systems in particular.

Why is it that the 0.0001% of downtime is what sticks in the mind of those who sign our checks? Never mind the 99.9999% of the time that the system was "up" and operating normally. Another thing—why is it that the "down" time always seems to occur at a critical time? Is it a perceived problem or a real problem? If the boss perceives it as a problem, it is a real problem to us! And believe me—when the dispatch center goes down, the boss will perceive it as a problem!

As our world of electronics has become more sophisticated (read, "computerdependent"), our capabilities have greatly expanded. The capabilities of such sophisticated equipment are limited primarily by the imaginations of those designing or buying such equipment. All of the proverbial "bells and whistles" that can be attached to the ultra-sophisticated, computerized equipment are nice to have but may not be so essential when the chips are down. This sophistication comes with a price beyond the purchase and initial installation costs. Maintenance requirements are more stringent and require greater technical expertise than they did for older technology. The problem becomes more com-

COMMERCIAL POWER SYSTEM

BACKUP GENERATOR

TRANSFER SWITCH

UPS OUTLET BREAKER BOX

Figure 1: Block diagram of the backup power system at the dispatch center.

plex when we "put all our eggs into one basket."

A perfect example is the dispatching center of my own employer, the South Carolina Forestry Commission. Just a few years ago we had a large network of lookout towers, as did most of the forestry services in this country. Our radio system was simple—literally, simplex! We had no repeaters (unless you can call one tower attendant relaying to another a "repeater"—a human repeater, if you will). Each county had several lookout towers, with one tower designated as the dispatch tower for each county. Thus, we had single-county dispatching.

The time came when the old lookout towers were phased out and replaced with air patrol—the passing of an era. There is something about a lookout tower that can't be replaced by airplanes—although our pilots do a good job of detecting and directing the suppression of wildfires.

Then came more reorganization. Districts were combined to form regions, and several forestry "areas" were carved out of the regions. A region typically has five forestry areas, typically consisting of about four counties each. Every area was set up (crudely) to dispatch for the counties within it. Thus, we had four-county dispatching in typical areas.

Ultimately, dispatching was moved to a central point within the region. The dispatching center now serves the entire region (19 counties). The region is so large that the weather might be wet in one part of the region while wildfires might rage in another part. The radio system consists of several VHF high-band repeaters, some on mountaintops, along with several simplex stations controlled via telco lines back into the dispatch center. Now, with single-point

regional dispatching, the dispatch center has become an all-important hub in our communication system. It has to remain operable even in the face of powerful storms that seem to plague the southeast.

For that reason. lightning and surge protection, along with backup power, were my foremost concerns. With single-point dispatching, downtime is an unaffordable luxury.




Photo 1. The old way. This old lookout tower is now abandoned, but it still stands to remind us of the way things used to be.

However, we could hand off dispatching to another region through the T1 lines in an emergency (assuming the T1 circuits were operable). A large backup generator was installed along with a UPS system. Only critical components were served by the UPS. The generator could service most of the building. Because the generator is fueled by natural gas, it could run indefinitely without concern for fuel.

Figure 1 below shows a simplified block diagram of the interconnection of the generator, UPS and dispatching equipment. The UPS supplies only the critical components of the dispatch system. The UPS is a "standby" unit as opposed to an "online" unit. Even with the UPS in the standby mode, the power feeding the UPS outlets passes through the UPS and is conditioned by it. In the event that the UPS doesn't "like" what it sees from the commercial power source (or generator), the UPS will switch to "inverter" operation, using the internal batteries to produce power. As long as the power feeding the UPS is within tolerance (frequency and voltage), the UPS simply passes the power through (while using it to float-charge the UPS batteries).

If the commercial power fails, the UPS will automatically go to the "inverter" mode and

Kinley, a certified electronics technician, is regional communications manager, South Carolina Forestry Commission. Spartanburg, SC. He is a member of the Radio Club of America. He is the author of Standard Radio Communications Manual: With Instrumentation and Testing Techniques, which is available for direct purchase. Write to 204 Tanglewylde Drive, Spartanburg, SC 29301. Kinley's email address is hkinley@aol.com.



Photo 2. The new way. South Carolina Forestry Commission air patrol pilot Jimmy Tobias stands beside his Cessna. Tobias flies air patrol to detect wildfires and to direct fire-fighting resources in the

suppression of those wildfires. Ground crews rely heavily on Tobias' skill in directing their movements and keeping them safe as they 'work' the fire.

generate power for the UPS outlets. At the same time, the generator will start. Once the generator comes up to full power and stabilizes, the transfer switch will switch the electrical system to the generator. If the generator power is within tolerance, the UPS will revert to the "normal" mode, and the internal batteries will resume charging from the generator power source. Thus, the UPS is only online for a short period of time (assuming that the generator is operating correctly).

Recently, we experienced a power failure late in the afternoon. No thunderstorms were in the area, but the power was out for an hour or so. The UPS took over until the generator came on line. However, once the generator came on line, the UPS would switch back and forth between "normal" and "inverter" operation. This indicated that the UPS did not like the power coming from the generator. A quick check of the generator revealed that the generator frequency was fluctuating. The UPS frequency window was set to accept a frequency variance of ±3Hz, the maximum window allowed.


We called a service company to service the generator. During the testing and "adjusting" of the generator, a voltage rise or surge set off something akin to a fireworks display in the dispatch center—complete with smoke, fire and screams as the dispatchers ran out the back door! Several of the lower-priced plastic-cased surge protectors literally smoked and tripped circuit breakers on the breaker panel. These are basically MOV shunt devices that ultimately fail in the shorted mode—often in an impressive dis-

play that will scare off even the most daring dispatcher. After we finally got everything stabilized and back "up." we were able to coax the dispatchers back into the building.

At that point, I promised that I would get

those plastic-cased cheap surge protectors replaced with better units that would not threaten to catch fire.

I will continue this saga next month. Until next time—stay tuned!



Circle (22) on Fast Fact Card

news

RFS Cablewave builds state-of-the-art facility

RFS Cablewave Systems has moved into its new manufacturing plant, headquarters facility and eastern regional service center in Meriden, CT.

The new facility occupies about 10 acres on a 52-acre parcel of land. The structure itself is ¼-mile long and contains a 310,000-square-foot manufacturing plant for cables, antennas, warehousing and shipping, and 40,000 square feet for the executive and administrative offices, sales, marketing and engineering departments. The facility's project cost exceeded \$20 million.

The grand opening is set for October. The open house for employees and their families was on June 20.

"The building was a massive effort of so many people," said George Gigas, president of RFS Cablewave Systems. He explained that one of the critical components of the new expansion effort had been the development of a partnership between RFS Cablewave, the state of Connecticut and the city of Meriden. RFS Cablewave chose the Meriden site after extensive economic and demographic analysis of various locations within and outside the state of Connecticut.

"It took nine months to design, and 13 months to relocate." Gigas said.

The main office has a tall, open entryway with floor-to-ceiling windows that allow a view of the surronding forest. The actual manufacturing plant is clean, with clearly marked walkways and blue machines. "We painted all the machines, and we have acquired some new machines," Gigas said.

"The facility is outstanding as far as energy conservation is concerned." Gigas said. The building has a sophisticated climate control system that maintains comfortable temperature in all seasons. All roof surfaces are pitched to avoid standing water and ice build-up in the winter. To conserve energy, the lights in individual offices also shut off automatically when there hasn't been any movement in a certain period of time.

For employees, two lunchrooms hold new vending machines, bulletin boards, and tables and chairs. There are patios for outside dining as well. The facility contains expandable meeting rooms.

"Everything is useable space," Gigas said. "We can easily expand to twice our present capacity.

"With this new plant, we expect to satisfy any level of future demand in a very timely manner," he continued, "The employees are

> crosstrained on different products and processes to enhance manufacturing flexibility."

> RFS Cablewave Systems employs more than 300 people in the facility, an increase of 100 employees from a year ago. The company also predicts the creation of 285 additional jobs over a three-to-five-year period.

"We have people who have been with the company more than 10 years, some 20 or 30 years. We have very little fluctuation. People like it here." Gigas said.

RFS Cablewave Systems, founded in 1973, is the North American partner of the globally operating RFS group with manufacturing locations in Australia, Brazil, France, Germany and the United States. The six flags flying in front of the new facility

represent these countries, and the state of Connecticut.

The company serves its customers in North America. Latin America and the Caribbean from the new facility as well as two other regional sales and customer service centers in Illinois and California, and a network of authorized stocking distributors.



California, and a network of authorized stocking distributors

George Gigas has served as RFS Cablewave president for 13 years.

The address for the main office is: 200 Pondview Drive, Meriden, CT 06450.



RFS Cablewave's facility contains a 310,000-square-foot manufacturing plant.



Offices make up 40,000 square feet of the RFS Cablewave's headquarters.



Circle (63) on Fast Fact Card

FCC Notes

New rules promote commercial use of 47GHz military band

The FCC recently adopted a Memorandum Opinion and Order and Notice of Proposed Rulemaking representing the next step in the commercial utilization of the 47.2GHz-48.2GHz frequency band. This band was initially developed for military use and now holds the potential for commercial use. The Commission concluded that it should take a flexible approach to regulating the "frontier" band, allowing licensees to offer any service consistent with the United States Table of Allocations and the Commission's rules. The Commission is finding that the dominant use probably will be fixed and point-tomultipoint satellite services.

WTB announces new management team

The Auctions and Industry Analysis Division of the Wireless Telecommunications Bureau (WTB) has a new management team. Amy Zoslov has been named chief of the division. She has served in the Mass Media Bureau, the Cable Services Bureau, the office of Commissioner Duggan and the WTB. Zoslov was most recently deputy chief of the division. Mark Bollinger has been named deputy chief (legal) and will oversee the legal and finance branches of the division. He was previously the division legal advisor. Louis Sigalos has been named deputy chief (operations) and will oversee the auction operations and expenditures management branches of the division. He previously was the chief of the auction operations branch.

AMTA requests rulemaking

The American Mobile Telecommunications Association (AMTA) has requested that the FCC adopt rules changing licensees' status from primary to secondary if those licensees have not started using "spectrally-efficient" equipment by a certain date. AMTA proposes that the conversion date be determined by the licensees' market. The licensees in markets 1-50 would have until Dec. 31. 2002 to change their equipment; markets 51-100 would have until Dec. 31, 2008, and the remaining markets would have to convert by Dec. 31, 2020. The FCC has not acted or commented on the proposal, nor has it begun a rulemaking proceeding, which would be required for AMTA's request to be adopted.

GN Netcom completes acquisition of ACS Wireless


GN Netcom, based in Copenhagen, Denmark, has completed the previously reported acquisition of ACS Wireless, a headset manufacturer. ACS Wireless stockholders approved the terms of the agreement. A new company, GN Netcom, Inc., has been formed by the merger of GN Netcom's North American organization, GN Netcom/ Unex and ACS Wireless.

P. Michael Fairweather will be president of GN Netcom, a position he held previously with GN Netcom/Unex. The company plans to continue operations in both Nashua. NH,

and Scotts Valley, CA.

The new company will continue to design, manufacture and market telephone and computer headsets under the brand names GN Netcom UNEX and ACS. Products are sold to the mobile, call center, commercial and consumer markets through the organization's worldwide distribution.

"Our customers, distributors and employees will all benefit from this merger," Fairweather said. "We have spent the last few months planning a smooth transition, and are ready to move ahead quickly."



Tellabs, Coherent to complete merger

The antitrust division of the U.S. Department of Justice has reviewed the merger of Tellabs and Coherent Communications Systems and will not oppose the merger. The two companies anticipate that the merger will be completed in September.

The company will design, manufacture and market echo cancellation and conferencing products for international telecommunications companies, cellular and PCS providers, and network operators.

Duke Energy markets towers, property holdings

Duke Energy announced that it has created a subsidiary, Duke Communication Services, to market more than 34,000 existing tower and property holdings in 33 states to help meet the growing need for antenna sites.

Since 1996, Duke has been working with wireless providers and local city and county planners in North Carolina and South Carolina to install antennas on top of electric transmission towers. This has enabled wireless providers to market their services faster, less expensively and with less difficulty than if they had to construct their own free-standing

towers and antenna structures. The existing tower sites have been received by planners and local communities as alternatives to freestanding towers with single attachments.

Jim Miller, general manager of Duke Communication Services, said: "The creation of Duke Communication Services will take this effort a step further by leveraging Duke's existing communications tower network across the eastern United States to offer the wireless industry thousands of desirable co-location tower sites. These additional sites will help the wireless industry develop their systems, so they can offer customers the reliability they demand."

Duke Communication Services is an unregulated division of Duke Energy Transmission and offers the following services to the wireless industry:

a co-location sites on more than 320 existing communications towers ranging in height

from 50 feet to 600 feet along Duke Energy's 31-state natural gas transmission system and Duke Power's 20,000 square-mile service territory in North and South Carolina.

complete turn-key services to design, construct, install, own and manage co-location antenna sites throughout the eastern United States.

ern United States.

I thousands of potential co-location antenna sites within or near the rights of way on Duke Energy's 12,700-mile electric transmission system and 22,000-mile natural gas transmission system.

more than 30,000 antenna sites on existing electric transmission towers, rang-


ing from 75 to 200 feet, in North and South

A Duke Energy

tower.

☐ a user-friendly computer application to identify existing antenna sites available on the World Wide Web at www.dukecomsvcs.com.

The new subsidiary will work closely with Duke Engineering & Services, another Duke subsidiary, in the areas of land acquisition, design engineering, project management and construction. It also will work closely with Duke Power and Duke Energy's natural gas pipeline telecommunications groups.



If you love the convenience of a belt clip on your portable, but hate the way plastic always seems to break... BEE' has a solution for you!

Introducing the first belt clip available on a

top quality leather or nylon case. Our clip is

STATE OF THE REAL PROPERTY.

Durus

formed from heavy gauge, heat treated, powder coated spring steel and is securely riveted to the back of the case. You'll never have to worry about radio damage again.

GIVE US A BUZZ 1-800-336-3115

Now your choice of three convenient tways to carry your radio case:

Our new spring steel belt clip mounted on the back of either leather or Durus' cases.

Or

Our famous quick disconnect swivel option.

Or

Regular snap down belt flap.





BELL and Duries are registered trademarks of BLE Floritonias Inc.

Circle (36) on Fast Fact Card

E-Mail: beecasemaol.com

News Notes

Dictaphone, Stratford, CT, has formed a commercial markets sales division within



its Communications Recording Systems (CRS) group to serve call center customers. "The call center business is growing by more than 20% per year, and managers are being overwhelmed by new technologies," said

Ron Elwell, senior vice president and general manager of Dictaphone's CRS group. "Voice recording is no exception. Our team of specialists thoroughly understands the needs of call centers, so they're better equipped to help customers sort through the technology choices."

The American National Standards Institute (ANSI) approved another standard in Project 25 suite of standards, according to Project 25 Steering Committee Co-chair Art McDole, who also noted that the Telecommunications Industry Association (TIA) is publishing "Project 25 Vocoder Description" ANSI/TIA/EIA-102-BABA-1998. John DiSalvo, chairman of the Project 25 User Needs Sub-committee, said the formal adoption of the standard would ensure its industry-wide acceptance.

Dataradio, Atlanta, has installed IBM's middleware network technology on the existing Dataradio Wireless Network at Arizona Public Service (APS), Phoenix, "Reliability and stability were our main concerns in implementing a new system," said senior communications engineer Claes Laestander. "We wanted to use our existing Dataradio network, and nothing else would fit. CAD was not considered a good solution."

Motorola's Land Mobile Products Sector (LMPS), Schaumburg, IL, will manage wireless communications equipment facilities on Houston-based Waste Manage-

ment North America's sites across the country. Under the agreement, Motorola's Antenna Site Division will manage future facilities at Waste Management's transfer stations, buildings and recycling facilities. "Motorola can help



Glockner

property owners, such as Waste Management, maximize their potential revenue from these communications facilities," said Joni Glockner, director of operations for the antenna site division.

Dataradio, Atlanta, will supply Sedgwick County, KS, with a countywide mobile computing system. The plans include a multisite 800MHz data network from Dataradio to support the Sheriff's Office's mobile


computing needs. The network will enable other public safety entities within the county to utilize mobile computing. The mobile computing system will consist of four base sites for countywide coverage, as well as the networking of 200 Sheriff vehicles through a Dataradio Multi Site Controller.

Crown Communications, Pittsburgh, PA. has acquired all of the common stock in a Dallas-based partnership called Abner, including Abner's principle assets, which are five communication towers that serve the Dallas metropolitan area. Abner was founded about six years ago to take ownership of towers that its partners had owned individually as part of other communications businesses in which they were involved, including SMR, paging and community

TriTech Software Systems, San Diego, CA, has installed its VisiCAD for Fire/EMS at the San Diego Fire Department. The Windows NT-based computer-aided dispatch (CAD) system incorporates vehicle routing. high-resolution integrated mapping, comprehensive graphical reports, and a fire



Circle (52) on Fast Fact Card



Circle (53) on Fast Fact Card

and emergency medical triage system. "VisiCAD for Fire/EMS"

advanced feature set enables fire departments to reduce response times, streamline resource deployment and enhance dispatcher productivity," said Christopher D. Maloney, president of TriTech.

Nextel Communications, McLean, VA, has purchased a centralized test and monitor-

ing system from TTC. Germantown, MD. The \$3.1 million sale included



TTC's Centest 650 remote test units, TTC's

Mayerick

NetAnalyst client/server-based test management software, Clear Communication's EarlyWarning intelligent surveillance software and TTC's professional services support. "Our agreement with Nextel further establishes the need for TTC's proactive, systems-based approach to network monitoring and testing," said Gary Mayerick.

president, systems and software, TTC. "TTC's centralized test system will enhance Nextel's ability to assure network availability and will play a critical role in verifying and maintaining Nextel's network performance for its nationwide customers."

Lenbrook Wireless Communications, Pickering, Ontario, has appointed Pat Connelly Repair (PCR), Indianapolis, as the service center for warranty repairs of Powerwave Technologies' (formerly Milcom International) land mobile amplifiers sold by Lenbrook. PCR will also handle all non-warranty repairs of Powerwave land mobile amplifiers.

Here's a Family that Keeps its Secrets

Introducing Selectone's Full Line of Voice Encryption Products

Today more than ever, the world of two-way communications needs the advantage of secure voice. The Selectone family of voice encryption products offers you a clear choice at affordable prices.

From the low-end inversion scramblers, the ST-22 and ST-20B; to our mid-range scramblers, the ST-25B with digital rolling code security; to the state-of-the-art Advantage-Plus encryption series with time domain scrambling and digital signal processing, Selectone will provide the right product match for your specific security requirements. No hassles. No overselling. No kidding!


We're confident that our product line is exactly what you're looking for, and we'll provide you with a personalized quote to prove it. Simply give us a call, send us a fax or write to us with your requirements, and we'll provide you with a customized quote at no cost. It's simple. It's free. And best of all, it introduces you to the finest family of encryption products in the world. You have our name on it.



inversion scramblers. ST-22, ST-20B

Mid-range scramblers. ST-25B





State-of-the-Art Advantage-Plus series. ST-50, ST-51,

electone

1-800-227-0376

Selectone, Inc. • 3501 Breakwater Ave. • Hayward, CA 94545 USA Phone: 510-781-0376 • Fax: 510-781-5454 • Internet: www.selectone.com

product focus

Paging Equipment

Decoder intended for maintenance, monitoring



Hark Systems has developed the new Verifier II, a Flex and POCSAG off-theair paging decoder. This product does not require a separate computer for decoding paging information. It is a portable decoding device intended for maintenance and monitoring of paging channels and is

suitable for field use by system technicians. The device tracks and holds, internally, basic statistical information as well as decoded pages for unattended operation. It is packaged with a frequency-agile receiver. It decodes 512-, 1200-, and 2400-baud POCSAG. Flex format decoding includes 1,600 and 3,200 bi-phase and 3,200 quad-phase formats. It can also be used with optional software, connected to a computer via an RS-232 interface, to produce extended statistics and to gather information from multiple channels.

Circle (351) on Fast Fact Card



Notification system accommodates 500 pagers

The VS3200 from Visiplex is an advanced security desktop notification system. It is equipped with a fullsize keyboard for operations and programming, and it accommodates as many as 500 pagers. Pages can be initiated through the keyboard, a telephone, an RS-232 serial port or contact closures. The system includes

an interface with wireless pendants and other wireless devices. The system allows customers to connect to any security, alarm or access control system, and it provides fail-safe alarm reporting. Options include telephone interface, wide-area paging, expandable contact points, multiple RS-232 ports, text-sniffing interface, cellular link backup and printed reports package.

Circle (352) on Fast Fact Card

Paging system developed for fire, rescue squads




The Paging and Wireless Service Center has developed a product designed for fire departments and rescue squads. It has its own private voice paging system, called a Monitor Adapter, designed for the Motorola Keynote pager. The adapter will monitor the channel and automatically squelch the pager to eliminate background noise between transmissions. The adapter is a small, printed circuit board that mounts inside the pager housing. It is available as a separate add-on to retrofit existing pagers or available installed in a reconditioned pager. The price of the modified Keynote pagers can be less than half of the price of purchasing new traditional monitoring pagers.

Circle (353) on Fast Fact Card

Pager acts as wireless personal digital assistant

NEC America has developed the Beacon Data Pager, a wireless personal digital assistant (PDA) with full alphanumeric messaging capabilities. Data can be transferred from desktop or laptop devices to a Beacon Data Pager by using infrared technology and special Microsoft software. Users may take important personal information management (PIM) data with them, such as appointments, reminders, addresses, phone numbers, contact lists and other specialized lists of data. The pager uses Flex messaging protocol and has one of the largest display screens available in a pager, eight lines by 21 characters. The pager also features 128Kb memory.

Circle (354) on Fast Fact Card



Circle (40) on Fast Fact Card



Circle (41) on Fast Fact Card

products

READERS' CHOICE

Of the new products in the February 1998 issue, this one generated the biggest reader response. For more information on this product, circle the corresponding Fast Fact Card number on the card found in the back of this issue, and mail the card to us.

Monitor receiver performs in severe conditions

The Minitor III alert monitor receiver from Motorola's Customer-Owned Messaging Group has more capabilities including scanning, vibrating alert and expanded calls. With features such as corrosion-



resistant packaging and more than 35 hours of battery life, the Minitor III alert monitor receiver performs under severe conditions. The receiver's compact design also includes field programming capabilities for frequency and codes, and can handle six calls per channel. The Minitor III receiver's channel scan capabilities allow customers to listen to channel traffic on two separate channels, so important calls are received. The Vibra-page feature alerts customers to incoming pages, keeping them informed in loud and tough conditions.

Circle (500) on Fast Fact Card

Pager's antenna ups reception range

The Sceptar tone and voice pager from

Shinwa Communications of America is a completely synthesized VHF pager with PC programming capability. The small pager tolerates rough handling. Its cellular-like telescopic antenna is



designed to improve reception in areas that are beyond most pagers' ranges. It has up and down volume control buttons instead of rotating volume controls.

Circle (401) on Fast Fact Card

42,45 Cooperstown Four Station Coverage Study

RadioSoft

Announces the release of the NEW Version 2.0 of ComStudy for Windows

You asked for lots of expanded features:

- 256 Colors for Contours and Coverage
- TIA Frequency Coordination Compliance
- Simple Runtime Overlay Management
- Transmitter Database Import/Export
- Individual Station Editing in Systems
- Individual System Matrix Recalculation
- Area Reliability Analysis and Mapping
- True 32 bit Operation (Win 95, 98, NT)
- Increased Accuracy (Land Uses added)
- More Interference Algorithms

And RadioSoft Delivers!

ComStudy 2.0 is available as a 15 day evaluation: call 888.RADIO95 (USA) or 904.426.2521 or check our website: www.RadioSoft.com for details.

Aggressively Priced!

Special pricing for all current users of propagation software and overlays! RADIOSOFT IS A CUSTOMER FRIENDLY COMPANY 109 W. KNAPP AVENUE, EDGEWATER FL 32132

Circle (65) on Fast Fact Card

Receiver displays LTR-coded fields

Optoelectronics has added two features to the Xplorer test receiver. The receiver

will now display five fields of LTR information: area code. go to repeater, home repeater, user ID and free repeater. The portable, hand-held test receiver locks onto a transmitter from 30MHz-2GHz in less than one second. Once the signal is captured, the frequency of the transmitter is displayed along with the LTR information. In addi-



tion to LTR, the Xplorer will also decode CTCSS, DCS and DTMF, as well as display the relative signal strength and signal deviation. The second feature added to the receiver is frequency blocks. Frequency blocks allow the user to input a specific frequency range as a lock in or lock out. With 10 frequency block memories, the user may now program frequency ranges to be locked in and tested exclusively, without interference from other signals.

Circle (402) on Fast Fact Card

Wireless data terminal works on tabletop


Eagle Wireless International has upgraded its industry-standard Microbeep wireless data terminal to a tabletop unit. This product is designed for in-house paging, or as a low-cost extension to existing systems. It works for specialized applications such as remote control, remote monitoring, security systems or temporary data systems. The Microbeep-sx can connect directly to all types of personal computers, modems, or to a paging network interface using standard formats. It also works autonomously as a stand-alone unit. The terminal works with Windows 95 and can handle all paging frequencies-VHF through 900MHz. It can transmit POCSAG data at 512bps, 1,200bps or 2,400bps to numeric, tone-only or alphanumeric receivers. Power outputs of IW to 5W have provisions for connection to external transmitters for higher power requirements. The terminal can monitor as many as 16 switch type inputs and transmit messages when one of these inputs changes state. A freestanding unit can monitor processes or alarms and send pre-programmed pages as needed.

Circle (403) on Fast Fact Card


Power supply provides N+1 redundancy

Liebert's UPStation GXT multimodule is an uninterruptible power supply that is scaleable from 3kVA to 9kVA, with N+1 redundancy. The multimodule is designed for distributed processing applications that are critical enough to warrant a redundant approach, such as high-end servers, critical nodes, clustered servers or hosts. The multimodule, a build-asyou-go system, features hot-swappable batteries, SNMP software communications and UPS backup. The multimodule uses Liebert's Intellipod (power output distribution) technology.

Circle (404) on Fast Fact Card



Why monitor your PCS antenna signal?



How did your investment perform today?


Zetron, Inc.

ZETRON

PO Box 97004, Redmond WA 98073-9704 USA Phone: (425)820-6363 Fax: (425)820-7031 Email: zetron@zetron.com Web: http://www.zetron.com

See us at PCS Booth #3217

Circle (56) on Fast Fact Card



Circle (57) on Fast Fact Card



Circle (58) on Fast Fact Card

Indoor, outdoor RF extension antennas deliver entire PCS band


Maxrad's series of PCS site antennas, the MFB-19000 series, is compact, economically priced and suited for indoor and outdoor RF extensions. The omnidirectional antennas are factory-tuned to 1,900MHz and cover the entire PCS band (1,850MHz-1,990MHz) with VSWR under 1.5:1. Three models are available, offering either 4dBi, 6dBi or 8dBi gain with corresponding vertical beamwidths of 32°, 20° and 12°. The antennas' broad vertical beamwidth provides coverage at the close ranges typically involved in RF extension. A slim, low-profile (height ranges from only 9"–24", depending on gain) and weather-resistant U,V, stabilized pultruded fiberglass radome allows fast, inconspicuous mounting. The antenna can also be painted to blend with its background.

Circle (405) on Fast Fact Card

Radios offer multimode operation

The Titan FM two-way portable and mobile radio series from Midland USA features alphanumeric control heads and programmable channel scanning. The unit offers multimode operation, programmable channel bandwidth, and 12.5/15kHz or 25/30kHz channels. It is available with as many as 150 channels, programmed in 15 groups. The mobile control heads offer an LCD with a 12-character display, which identifies the channel in use. Users can monitor frequencies while reverting back to two assigned channels if a transmission comes in on those channels, by employing dual-priority channelscanning capability. The scan expander lets users add programmed groups and delete add-back channels within groups.

Circle (406) on Fast Fact Card



Commercially
Available
Military
Anti-Jamming
Technology



Automatically
Suppress
Co-channel,
Adjacent Channel
& Broadband
Interference

CMA-2032 Antenna Signal Processor

CANADIAN MARCONI COMPANY

Tel: (613) 592-7440 Email: asp@kan.marconi.ca Fax: (613) 592-7434 Web Site: www.marconi.ca 1-888-262-2032 (1-888-CMA-2032)

"Providing innovative solutions to Interference Problems"



Low-VSWR jumpers support PCS uses

The low-VSWR Flexwell jumper assemblies from RFS Cablewave Systems are for PCS applications. Because of the higher operating frequency band 2GHz, PCS systems demand low VSWR characteristics. With these jumpers, PCS operators can pass transmission line sweep tests every time, preventing construction testing delays. Each jumper assembly is 100% tested for input VSWR, which is guaranteed to be better than 1.08:1 (28.3dB minimum return loss) across 1,850MHz-1,990MHz. These jumpers are waterproof and are available in special lengths to meet installation needs. Available in both 1/2" foam and 1/2" superflexible cables, premium jumpers have been introduced in the following connector configurations: 7/16 DIN male/7/16 DIN male; 7/16 DIN male/7/ 16 DIN male right angle and 7/16 DIN male/ N male. An N male/N male version is available for 1/2" standard foam cable.

Circle (407) on Fast Fact Card

Low-loss filters block VHF. UHF harmonics


Microlab/FXR has expanded its range of lowpass filters, which are designed for VHF and UHF base stations and similar applications. The LB-CO1 and LB-CO3 feature low passband loss, low intermodulation and 500W average power capability at an economic price. With only a few solder joints and an air dielectric, the loss has been minimized and reliability enhanced. Model LB-COI is designed for passband up to 174MHz and model LB-CO3 up to 329MHz. With a stopband defined as the band from the second harmonics to 2,5000MHz, each achieves a minimum of 55dB harmonic suppression, a rejection that typically extends to beyond 12GHz. When compared to lumped element filters often used at these frequencies, the filters will run cooler, reflect less power back to the transmitter, and, with only two solder joints per assembly, will be considerably more reliable.

Circle (408) on Fast Fact Card

Repeater works with any trunking radio

Loudoun Communications' Comm-link 800 (MHz) is a lightweight, multi-

featured, portable repeater. The repeater works with any conventional-mode trunking radio, from any distant location, and is suited for use in emergency operations. The repeater can be used by electric utilities, Secret Service, FBI and SWAT teams. It can operate on 100 channels with a 25W power output and 10- to 40-mile range (depending on terrain). Weighing 35 pounds, the repeater requires only one person for both installation and operation. The repeater is fully programmable in frequency and CTCSS, and is multi-CTCSS tone capable.



Circle (409) on Fast Fact Card

GRAPHICAL ANTENNA & CABLE ANALYZERS

The complete line of AEA antenna and cable anlyzers are now available FACTORY DIRECT at the lowest possible cost. Each antenna analyzer gives a graphical display of SWR curves with variable sweep width and center frequency. The 30-150, 150-525, and 806-960 MHz antenna analyzers are each \$499.95 plus \$7.50 shipping and handling. The SWR-121 HF analyzer covers 1-32 MHz and is priced at \$299.95 plus \$7.50 shipping and handling.

We are pleased to announce the NEW AEA CIA-HF Complex Impedance Analyzer that features all the features of the above SWR Analyst products. In addition, the CIA-HF gives graphical displays of impedance, reactance, resistance and relative phase

angle with a vector display mode. Automatically display the 2:1 SWR points or any two other user selectable bandwidths. Display reactance and the conjugate match value of inductance or capacitance necessary to resonate a mis-tuned antenna. The CIA-HF covers a frequency range of 400kHz to 54 MHz and has a low introductory factory direct price of \$359.95 plus \$7.50 shipping & handling in CONUS.

The AEA CableMate[™] graphical Time Domain Reflectometer (TDR) is packaged in the same style package as the SWR analyzers. The CableMate shows multiple faults in a cable on the graphical display. Virtually any multi-conductor cable may be tested for shorts, opens or impedance lumps. Designed specifically for RF service techs, the CableMate has a special RF filter mode to kill any interference. The CableMate is an excellent device for measuring the length of most any cable for inventory purposes. It will also directly show the 25 MHz return loss. The CableMate is priced at \$359.95 plus \$7.50 shipping and handling in CONUS.

All AEA analyzer products come standard with a serial computer interface. Optional DOS applications software (except CIA-HF) with interface cable is \$29.95 each. With this software you can store the graphical data for your antennas or cables for future reference.


For more information on this exciting new product or for our catalog, contact AEA at the numbers listed below.



Circle (60) on Fast Fact Card

Buildings feature post-tensioned design

The Easi-set buildings from Easi-Set Industries create enclosures for communications, sensitive electrical controls, maintenance equipment storage, Hazmat-spill containment and mechanical housing. The buildings meet UL752 level four bullet resistance. The designs also withstand Zone 4 seismic and up to 150mph wind loads. The post-tensioned building, which will withstand a 100-pound block of ice dropped from 200 feet without any damage, is available in clear roof spans of 12', 20', 24', 30' and 40'. The buildings protect materials from weather, fire and theft. The maintenance-free building is transportable, and in most cases, installation takes less than one day because there is no need for foundations or footings. The buildings are modifiable to customer's requirements.



Circle (410) on Fast Fact Card

Headset speaker imitates human ear shape

GN Netcom/Unex's Optima-G is available in monaural and singlewire binaural and is made with quick disconnect (QD), making it compatible with all GN Netcom amplifiers, including the MPA-II multipurpose amplifier and the wireless MPA satellite. The Optima-G is a light professional grade headset featuring an ergodynamically contoured speaker that imitates the shape of a human ear, a noise-canceling microphone, a strong Duraflex boom, Pure Sound Accubass speakers, and a Stay Put ratcheting headband for all-day comfort.

Circle (411) on Fast Fact Card

Clamps aid in lightning protection

Harger Lightning Protection's family of pipe clamps provide 11/2" of contact area to ensure sufficient electrical contact for both ground fault and lightning current. These clamps can be connected to ground conductors via exothermic

connections and standard compression lugs. The UPC.75/1.25 provides bidirectional grounding capabilities, making it a suitable connection for grounding fence rail to fence post applications. Sizes range from 3¾" up through 6" nominal pipe diameters. All clamps are manufactured from



ED 15 14 1 E1

highly conductive tinned copper and feature stainless-steel hardware.

Circle (412) on Fast Fact Card

NTENN


Yagi Antennas



- Thick Wall Aluminum Boom
- · Ferrite Balun
- Balanced Center Feed Design
- · Cable Pigtail
- Moisture Proof Feed System

Omnidirectional Antennas

- · Wide Bandwidth Performance
- Heavywall Fiberglass Radome
- · Weather Resistant Design
- · Cable Pigtail



For a Catalog or to Order call: 703,450,5517

Astron Antenna Co. 22560 Glenn Dr, Ste 114, Sterling, VA 20164

> www.astronantennas.com Circle (62) on Fast Fact Card

ROTECTED Record Your Telephone and Radio Calls AVOID LEGAL ACTION DOCUMENT AND VERIFY CRITICAL RADIO & PHONE CONVERSATIONS AUTOMATIC TIME & DATE IMPRINT 2 to 20 Record Channels *J.e.i.*, COMMUNICATIO RECORDING SYSTEM DESK TOP OR RACK MOUNT

Circle (61) on Fast Fact Card

3087 Alhambra Drive Cameron Park, CA 95682

Phone (530) 677-3210

Fax (530) 677-4714

www.jei-inc.com

Protocol provides data, voice over one channel

AMP Wireless Systems' suite of flexible wireless communication products and protocols are engineered to meet the needs of specialized mobile radio (SMR) users. Opensky operates in the 800MHz SMR band and provides simultaneous data and voice communications over a single RF channel in either trunked frequency-division multiple-access (FDMA) or time-division multiple-access (TDMA). This provides users with a significant advantage over existing systems that allow either voice or data, but not both, to be transmitted at any given time. Consisting of software-based digital mobile radios, portables and base station equipment. Opensky provides users' compatibility with legacy systems and expandability. It is suitable for service in the public safety, utility, transit, taxi and field service arenas. Opensky communications protocols are extensions of the Advanced Mobile Phone System (AMPS) cellular digital packet data (CDPD) stack and are TCP/IP based. This allows users to access applications such as email and FTP (file transfer protocol). It also facilitates voice communication over Internet protocol (IP). Its trunked FDMA and TDMA protocols support both circuit-switched and packet-switched data.

Circle (413) on Fast Fact Card

Mobile radio serves VHF/UHF market

Ericsson's mobile radio, the KMC, serves the mid-tier, conventional VHF/UHF market. providing a variety of options from channel guard to PC programmability. The KMC operates in both narrowband and wideband modes and is flash-programmable to handle future software upgrades. Other features of the mobile include radio interrogate, radio disable, radio enable, group call and status message transmission.

Circle (414) on Fast Fact Card

Vocoder delivers better speech quality

The low-data rate AMBE+ vocoder from Digital Voice Systems provides speech quality and performance under bit errors and background noise conditions. Operating at 4.8kbps and 4kbps, the vocoder achieved mean opinion scores (MOS) of 3.849 and 3.646 respectively in an independent evaluation. The vocoder is suited for specialized mobile radio, satellite communications, computer telephony and other voice and storage applications where low data rate and toll quality are prerequisites.

Circle (415) on Fast Fact Card

Receive **Weather Alerts Automatically**

on your 2-way radio system, PA system, voice-mail, numeric pager or telephone!

- Rack-mount and mobile systems
- Warnings digitally recorded for DTMF access and playback
- Designed specially for demanding Public Safety use

Call toll free 1-888-877-8022 or visit our Web site at: http://www.thuneagle.com





U.S. Patents 5,444,433 - 5,574,999 - D,377,795

Circle (38) on Fast Fact Card







Circle (39) on Fast Fact Card

media

Disk features surface-mount tech

Pace's CD-ROM features surface-mount technology with more than 50 step-by-step procedures to help with the installation and non-destructive removal of surface-mount components applicable to assembly and rework operations. Procedures for removal and replacement of misaligned, poorly soldered, damaged or faulty components are illustrated. The disk includes more than 25 video clips to show the procedures and to provide greater visual assistance when needed. The CD-ROM includes component, tip and handpiece identification information as well as the Pace catalog.

Circle (451) on Fast Fact Card

Guide offers power products



Hewlett-Packard has published the 1998/1999 editions of its System Power Products Selection Guide and Power Products Catalog. The 16-page guide (literature no. 5966-1707) contains an overview of HP's power product line, highlighting key features and specifications. The 65-page catalog (literature no. 5966-1706) provides R&D and production engineers with technical information on more than 125 models of dynamic measurement

de sources, ac power source/analyzers and harmonic/flicker test systems.

Circle (452) on Fast Fact Card

Catalog includes line of probes

AEMC Instruments' Current
Measurements Catalog includes information about the AEMC line of
clamp-on current probes covering the
entire spectrum of applications, from
electrical panels to substations.
AEMC current probes measure current without interrupting the circuit
and extend the assuring capabilities of
DMMs. recorders. power meters and
loggers. The numerous jaw sizes are
designed to accommodate a wide variety of conductor diameters and ranges.




Circle (453) on Fast Fact Card

Directory contains 2,100+ listings

The Electronic Industries Alliance has released the 1998 edition of its annual Trade Directory & Membership List. The directory contains more than 2.100 listings representing the full spectrum of the \$500 billion U.S. electronics manufacturing industry. The publication lists EIA members' corporate and division locations, telephone numbers, executive level personnel, trade names and number of employees, as well as specific company products and services. It includes a section on company facilities by geographical location and a cross-reference of companies by product category as well as company logos and advertising.

Circle (454) on Fast Fact Card

Factory automated process ensures superior electrical performance



For Sure

New SureFlex™ factory made cable assemblies from Andrew combine maximum electrical performance with ready-made convenience.

Featuring a patent-pending, factory automated process that solders both inner and outer conductors to the connector, every SureFlex cable assembly promises 360° of electrical contact and a reliable weatherproof seal. No cable attachment O-rings. No sealants, Just consistent, robust attachment every time.

Other features include:

- Stable intermodulation distortion
- Consistent VSWR
- Accurate pin depth
- High pull off strength

For more details, call Andrew customer service today at:

Call 1-800-255-1479 ext. 376 or Fax us at 1-800-349-5444

Visit our Web Site at http://www.andrew.com



In A Communicating World, Andrew Is Everywhere

Circle (66) on Fast Fact Card

people









Hansen

Farina

Mance

Stewart

Mark Hansen, lead engineer, Special Antenna Division at Centurion International, Lincoln, NE, advances to engineering manager, Power Products Division.

Sal Farina, national sales manager for Uniden Private Radio Communications, Fort Worth, TX, moves up to vice president of sales.

Robert D. Mance leaves PDS Worldwide in Pompano Beach, FL, to become vice president of Mac Com, Fort Lauderdale, FL.

Michael Stewart exits Ernst and Young, Chicago, as sales and marketing manager to join LCC International, McLean, VA, as senior vice president for North America.

Bruce Richter, manufacturing unit leader for Joslyn Electronic Systems, Santa Barbara, CA, becomes director of engineering and manufacturing for Panavise, Reno, NV.

Jeff Greene departs Larsen Electronics, Vancouver, WA, as production services leader to become general manager for Gamber-Johnson, Stevens Point, WI.

Joseph A. Banos rejoins RF Industries, San Diego, as president of its Neulink Telemetry Division, replacing Arthur Ekroos, who becomes an independent sales reperesentative for Neulink Products.

Changes at TruePosition, Vienna, VA:

Dan Principe exits Ericsson Radio Systems, Reston, VA, as director of business control and operations, to join TruePosition as vice president, operations. **Paul Czarnecki**, TruePosition's director of engineering and implementation, moves up to assistant vice president, engineering and implementation.

Gareth Davies exits Motorola as director of multimedia services for Europe, the Middle East and Africa and becomes international sales and marketing director for Airtouch, Aylesburg, Bucks, UK.


Charles Johnston, general manager, PCS, for Omnipoint, Cedar Knolls, NJ, advances to chief operating officer.

Jill Prince leaves her position as public relations director for Uniden America in Fort Worth, TX, to become marketing communications manager for the wireless division of NEC America in Irving, TX.

Anders Ericsson departs Ericsson Data AB in Malaysia as regional director to become president of Allgon Enterprises, Fort Worth, TX.

Marisa Ollins, a 1998 graduate of George Washington University. Washington, DC, joins the Electronics Industry Alliance, Arlington, VA, as public affairs coordinator.

Steve M. Wilcox, tower technician and field instructor, becomes the manager of Monroe, WI-based ComTrain's new office in Sacramento, CA.



Circle (42) on Fast Fact Card





Dawn Rhoden Classified Advertising Manager

Reserve your spot in the next issue!

Phone: 913-967-1861 800-347-9375

Fax: 913-967-1735

Mail: 9800 Metcalf Ave., Overland Park, KS 66212

Category Index

Accessories
Business Opportunity 66
Computer Software 76-77
Employment 64-66
Equipment For Sale 66-74
Paging 74-76
Professional Consulting Services 75
Professional Services 64
Rentals 76
Repair Services78
Tower Services 79
Tower Space

services

★ FCC LICENSING SERVICES ★

§80, §87, §90 and §101

-Years of Experience -

Lettye G. Froboese

109 Wallingsford Circle Youngsville, LA 70592

Voice (318) 856-8141 • FAX (318) 856-1091 E-Mail: froboese@bellsouth.net

STUDY LAND MOBILE COMMUNICATIONS

AT HOME!

38 Lessons written exclusively for Mobile Communications Servicing, \$375.00

Call or write Mobile Training Institute

for free information:

P.O. Box 8278

(409) 755-7838

Lumberton, TX 77657-0278

professional services

FREDERICK G. GRIFFIN, P.C.



3229 Waterlick Road Lynchburg, VA 24502 (804) 237-2044

LIGHTNING

SYSTEMS

204B Cross Keys Rd.

PREVENTION

NATIONWIDE COMMUNICATIONS CONSULTING

Mobile Radio, Microwave, E9-1-1, CAD, Paging, LAN,

Dispatch Communications Centers Multi Site Propagation Analysis



FACTORY FRAINED TECHNICIANS

PROJECTS UNLIMITED INTERNATIONAL

SERVICE, INC.

- International and Domestic Consulting Services
 - Voice/Data HF/VHF/UHF/Spread Spectrum . Fax & Internet email by HF radio

PORTA-TECH PORTABLE TECHNICAL

FOR QUALITY SERVICE Public Service Trunking

(804) 239-3049

121 Crowell Lane . Lynchburg, VA 24502

GE Portable Radio Service Depot Factory Approved Nationwide

Current Product Lines
 Voice Guard Certified

· Surface Mount Technology

- · Manufacturer Support
- Installation/Training

PO Box 146, Twin Pears, California 92391 USA 909-336-5216 999-336-5217 Fax email: projunit@@compuserve.com http://ourworld.compuserve.com/homepages/projunitd/

STATIC DISSIPATION SYSTEMS FOR LIGHTNING STRIKE PREVENTION

Berlin, NJ 08009 Dealers/inquiries invited.

(888) 667-8745 (609) 767-7209 FAX (609)767-7547

MCCON

WWW.LPSNET.COM

Mobile Communications Consulting S.R. McConoughey, P.E.

Principal

13017 Chestnut Oak Drive

(301) 916-2837

HERB SACHS, CONSULTING

Specialist in Public Safety Communications

P.O. Box 729 Bowie, MD 20715 301-464-4268

Gaithersburg, MD 20878

OMNICOM, Inc. COMMUNICATIONS ENGINEERING

gene A. Buzzi PRESIDENT

930 THOMASVILLE ROAD, SUITE 200 TALLAHASSEE, FLORIDA 32303 PHONE: (850) 224-4451 • FAX: (850) 224-3059 E-mail: omnicom@polaris.net

- · FAST TURN
- WARRANTY
- \$48,00 hr./2 hr. MAX
- · PARTS GE LIST
- RETURN UPS PAID

Smith Communications Service 2121 W. Parrish Ave., Owensboro, KY 42301



502-683-0936

THE PORTABLE DEPOT

- FACTORY TRAINED TECHNICIANS SURFACE MOUNT TECHNOLOGY
 - . FACTORY APPROVED NATIONWIDE . · EDACS & AEGIS ·
- . VOICE GUARD CERTIFIED . • MPD, MPA, TPX, PCS AND ALL CURRENT PRODUCTS • Route 2, Box 338C • Lynchburg VA 24501 ERICSSON **■** 804-237-3427





RAYMOND C. TROTT, P.E.

Chairman

1425 Greenway Drive, Suite 350 Irving, Texas 75038 972/580-1911 • Fax: 972/580-0641

employment

ELECTRONIC MAINTAINER

Port Authority, located in Pittsburgh, Pennsylvania, is currently seeking candidates for the position of Electronic Maintainer. This position is responsible for troubleshooting, dismantling, repairing, aligning and testing a variety of communication/electronics equipment consisting of solid state and state-of-the-art microcompressor controlled equipment.

Job requirements include: Minimum of 48 college credits in Electronics, Electronic Engineering Technology or Electrical Engineering; minimum of two years experience in the troubleshooting, repair and maintenance of communication/electronic equipment and systems; valid FCC license or NABER certificate; and a valid PA driver's license. AS or BS in Electronics, Electronic Engineering Technology or Electrical Engineering preferred.

Port Authority offers a competitive compensation and benefits package. Interested candidates should forward cover letters, resumes and educational transcripts to:

Port Authority Employment & Compensation Services ATTN: H.A. Hall 2235 Beaver Avenue Pittsburgh, PA 15233-1080 EOE

employment

PageNet, the world's largest provider of wireless messaging services, is currently seeking the following positions in our Farmington Hills, Michigan office:

SYSTEMS TECHNICIANS

Responsibilities for this position include: installing and maintaining base stations and paging terminal equipment. At least one year experience with paging or wireless communications is required. FCC or NABER certification is preferred.

PageNet offers a competitive salary and a full range of benefits. Qualified applicants should send résumé/salary history to:

PageNet

ATTN: HR-ST 33533 W. 12 Mile Rd. #300 Farmington Hills, MI 48331 Fax: 248-488-3615 EOE/M/F/V

RF & Microwave Engineering Job-Site"

Wireless industry employment listings

www.job-sites.com

Free for job-seekers

\$100 flat fee for employers

TECHNICIAN WANTED MOTOROLA/RELM DEALER

For installation & repair of mobile radio. Maintenance & component level repair of same. May be other duties. Required education or experience in RF technology. Will train in satellite and telephone communications. \$18train in satellite and telephone communications. \$15-\$30K, depends on qualifications. Benefits include vacation & holidays. Call Paul at 701-251-6183, or email to pheer@fm-net.com. Can lax resume to 701-763-6385.

Positions Available in Southern California

Rapidly expanding MSS/Motorola Full Line, Nextel dealer is searching for experienced professionals for the following positions:

- Installation—Tower Climbing
- Shop Service Technicians
- Radio/CCTV Sales
- Nextel Sales
- Maintenance Contract Sales

Excellent opportunity for self-motivated professionals to progress within the company. We offer continued education, competitive wages, full benefits, factory training and possible re-location assistance. Two locations: Tri-county LA area and Ventura/Santa Barbara area.

Contact us via:

Telephone: Fax:

310-532-3211 310-532-8411

E-mail: Web site:

104437.3074@compuserv.com www.advancedelectronics.com



Advanced Electronics

"Our employees are our most valued asset"

Use COLOR to make your ad STAND OUT!

TWO WAY RADIO TECH/SALES

40-year-old GROWING Multi-line Dealer with multiple facilities in Indiana, Kentucky and Arkansas has immediate need for Mobile & Portable Two-Way Technicians and Sales Staff with 2 or more years of experience on Motorola, G.E., Kenwood, Standard, LTR or similar equipment, FCC or NABER Certified, Full benefits, competitive wages, incentive bonus package, excellent working conditions and advancement opportunities.

Send resume to:

1-800-288-2430 or FAX: 1-317-248-0118

COMMUNICATIONS MAINTENANCE INC.

5601 Progress Road Indianapolis, IN 46241 Attn: Personnel Dept.

WIRELESS SYSTEMS

SCI provides integrated solutions & on-going support to the wireless and cellular marketplace. We currently have Domestic and International projects in the following areas:

- Microwave Optimization/Tuning
- · PCS
- · GSM
- RF Systems Autoplex
- Propagation
 Networking
- - Domestic & Int'l Field/Customer Support
- Switch/Software/Protocol Development

For immediate consideration, email or fax your resume to:



4736 Main St., Suite 7 MRT Lisle, IL 60532 Fax: 630/960-2993 E-mail: sci@interaccess.com

TELECOMMUNICATIONS **ENGINEER I**

\$40,886 - \$61,330 (DOQ)

Provides telecommunications engineering & design support for one or more technology areas. Requires BS in engineering, electronics or computer science and 1 yr communications engineering design OR successful completion of vendor specific engineering or installation & design courses & associated vendor tests, FCC General Radio Telephone license or FCC equivalent & 6 vrs telecommunications installation & maintenance experience, including 4 yrs at a senior level.

Complete benefits plan & WA State Retirement program. Send cover letter & resume by 5pm, September 18, 1998 to: Snohomish County PUD, Attn: Employee Resources, PO Box 1107. Everett, WA 98206 or fax to (425) 258-8675; email resumes@snopud.com. We are an EEO employer...committed to a diverse workforce.

COMMUNICATIONS TECHNICIAN

Continuous Testing / Several Openings

County of Santa Clara (San Jose, CA) seeks individuals to service two-way radio, microwave and computer equipment used in public safety communications. Experience required, salary \$3784-4582 per month, includes County contribution to the Public Employees Retirement System for the 2% at 55 Plan; and includes payment by the County of the employee's regular contribution of approximately 7%. Excellent benefits.

For an application, please contact Communications Administration (408) 299-2711 Equal Opportunity Employer.

employment

TWO WAY RADIO TECHNICIAN

Total Radio, Inc., a Motorola MSS, has an immediate opening for a bench or field technican at our Tulsa location. Candidates should be highly motivated with a minimum of 2 years field/system experience in LMR or a Military Radio Field. An FCC License or NABER Cert. is desirable but not required. We are a growing company with good benefits, competitive salaries, and a company 401k. This is an excellent opportunity for the right person in a medium-sized Metro area with a low cost of living and small town atmosphere.

Fax resume to: 918-664-6229 or email: info@totalradioinc.com

TWO-WAY RADIO TECHNICIANS

Motorola MSS/Full Line Dealer in Central Florida has openings for bench and field techs. Motorola experience preferred. FCC and/or Naber required. Send resumé with salary requirements to:

Tri-Co Communications Inc. Attn: Brad Barber 4651-B NW 6th St. Gainesville, FL 32609 Ph: 800-228-8501 fax: 352-377-9549

Communications & Electronics Technician

A major security contractor is seeking a Communications & Electronics Technician. An applicant must have formal training in DC and AC circuits, semi-conductor and digital theory, communications circuits, and antenna and transmission line theory. Must possess PCIA/NABER two-way radio technician certification or a current FCC General Radiotelephone Operators License (GROL). Three years of experience in repairing electronics/twoway land mobile radio equipment is required. Experience with trunked radio systems is desired. Must be able to obtain/maintain a Department of Energy security clearance. Excellent salary and benefits. Send a current resume to the Employee Relations Department; PO Drawer W; Aiken, SC 29802 by October 1, 1998. EEO M/F/D/V.

business opportunity

BUSINESS OPPORTUNITY

Largest Motorola two-way sales, service and install business in Western Colorado. Four bay install shop and 7 bench tech shop. For more information, call Jon or Don at (970) 245-2766.

equipment for sale

PRYME Radio Products

Your Source For Portable Accessories




NICad and NIMH BATTERY PACKS!

We offer a variety of both NiCad and NiMH battery packs using high quality cells from both Panasonic and GP. Batteries are available for the Kenwood TK-250/350, TK-260/360, Motorola GP300, P110, SP50, Vertex VX-10, VX-200, FTH-2009, Icom H16, F10, and many more!

Check out our full line of Mini-boom microphones. Survelliance microphones, Remote speaker microphones, NiCad and NiMH battery packs, and more! Models are available for all major brands of portable radio!

Visit us on the web at http://www.pryme.com/!

Patented. over-the-ear design!



- · Comfortable, patented earhook design
- Remote PTT
- · Adjusts to fit either ear!
- · Economically priced!
- · Models available for Icom. Kenwood, Vertex, Motorola, Uniden, and more!

SPM-400

Light-duty headset

Dealer Inquiries Welcome

1-800-666-2654

Circle (75) on Fast Fact Card

FOR SALE USED

- 30 8600 EFJ Complete \$150.00 40 8604 EFJ Complete \$150.00 15 LMX 1101BK \$100.00 15 SMS 815TS \$100.00
 - 1-800-968-7820

STATION IDENTIFIERS

- ☐ Morse code and Voice ID
- ☐ 3 monitors and 3 timers
- ☐ Several models available
- ☐ Special prices for a limited time

RACOM

800-722-6664 216-351-1755

FOR SALE

Marconi 2955R & 2957R, Best offer HP8920A-all options-\$8500

718-783-6000

BUY • SELL • TRADE • CLEAN WORKING EQUIPMENT

Bases, Repeaters, Paging TX 1-MSF 5000 C24CLB7106 Repeater 450 MH	everesonoum — misses
6-SyntorX 800 MHz Base Consolet	
20-GE 900 MHz-PRC-8/9 45W Reposiers &	
10-900 MHz Paging Tx Mot, GE, Granger	
20-Mastr II-E 75W UHF Mobile Repealers w	
10-MICOR 800 MHz Repeaters 125W	
50-Micor Base/Repeaters 100-375 Watt Low	and the Co
1-MSF-5000 UHF Repeater 100 Watt, NEW	402-420 MHz Ca
4-MSR 2000 Base/Paging TX C74GR8 & C7	3VSD D-4- C-
20-Mastr II Base/Repeaters 60-250 Watt All I	Sands Co
20-Mitrek Base 100 Watt All Bands	Ca.
25-Aerotron Pioneer 1000 VHF Repeaters At	
Mobiles 2550 MHz	
200-Mitrok 30-39 MHz 100 Wetl	From \$20
10-Mitrek 39-50 MHz 110 Watt 4 Ch	
20-Mitrek 30-39 MHz 60 Watt	
300-Mitrek 39-50 MHz 60 Watt	From \$5
300-Mitrek 39-50 MHz 60 Watt 10-Syntor X 30-50 MHz 100 Watt	Cu
10-Syntor X 30-50 MHz 100 Wett 1-Marstrac 42-50 MHz, 8 Ch, 110 Watt	From \$39
20-Deta 36-42/42-50 MHz 100 Watt	From \$10
20-Delta 36-42/42-50 MHz 100 Watt 200 Masi II 30-50 MHz 60-100 Watt	. From \$5
10-Midland 70-0568 100 Walt R/M. 36-42 MH	łz \$19
Mabiles 150-175 MHz	
30-Mitrek 45-80 Watt 4 Ch.	From \$5
5-Midland 70-490 B R/M	\$20
50-Syntor X 110 Watt 32 Ch	
50-Syntor X 110 Watt 32 Ch 30-Micor 45-100 Watt 4 Ch 30-Mastr II 60-100 Watt 8 Ch 30-MVP 35 Watt Michiel Repeater 20-Debt S 100 Watt	From \$5
20-Mastr II 60-100 Watt 8 Ch	From \$5
30-MVP 35 Watt Mobile/Repeater	From. \$5
20-Deta S 100 Wat:	From \$10
50-PAC-RT 1.5 Watt Mobile Repeater	From. \$10
200-Aerolion Pioneer 2000 ACSB	
UHF MODILES 450-470 MHZ	
4-Ranger 50Watt	From \$20
4-Ranger 50Watt 8-Delta SX 100 Watt 20-Syntor X T34VBJ 32 Ch 40W 20-System 9000 PAC-RT 4KEA300GA	From , \$30
20-Syntor X T34VBJ 32 Ch 40W	From \$10
20-System 9000 PAC-RT 4KEA300GA	From \$49
50-Mastr II 45-100 Watt Repeater Busiders	From\$10
15-Mot PAC-RT Mobile Repeaters	
3D-Mitrek T44JJA 50 Watt	From \$10
900 MHz Mobiles	
20-Syntor X 9000, 35 Watt	
10-Spectra T45KGA55JC9AK 1&2 SmartNet	
B-Spectra D45KMA7JA5AK	
50-Maxirac 800T 15-35 Watt B-1-B-7	
4-GE MDX 500 PM 825N	
30-Syntor X T45VBJ 35 Watt Dual/Mode	
3-Ranger 800 144-AZ	
20-Spectra 900/B7 F.K.	
20-EX II 35 Watt W/M II PA	
100-Mosters, Micors, Traxers, Midland, TAC,	1 EC, GE From \$2
Misc Items	60
1-R 2001 B Serv. Mon. Good Condition	Grander Gr
30-SpectraTac Voter Rec Comparators	
40-Centracom II Control Eq. Consoles BIM, C	EB, Panels, Cabineta Ca Ca
2-Centracom I Consoles & Lots of Parts	HISTS C
20-GE Voter Receiver & Voter Panels 500-MOT & GE Tone & DC Remotes All Type	Ca


anded List, updated weekly, look at ou Website: www.barnettelec.com



Info: 501-676-5506 VISA & MC Accepted, NO COD's



Circle (76) on Fast Fact Card



MOTOROLA • GE • EF JOHNSON etc. PORTABLES / PAGERS / MOBILES / BASES / REPEATERS

Contact us when you are looking for economical used equipment. We are a reliable source for all major brands of used 2 way gear



(708) 681-0300 Buy . Sell . Trade




Visit our web site: WWW.MDMRADIO.COM or E-Mail us at mdmradio@earthlink.net

MDM Radio Ltd.

1629 N. 31st Ave. Melrose Park, II. 60160 Tel. (708) 681-0300 Fax (708) 681-9800

equipment for sale



Circle (77) on Fast Fact Card

BUY & SELL:

LTR-800MHz & 900MHz EF Johnson • Kenwood • Uniden MOTOROLA

UHF • VHF • 800MHz • 900MHz • Mobiles • Portables • Repeaters • Amplifiers • Paging Transmitters

1-800-786-2199

SOCIATES, INC

Fax: 972-562-7957 Mike Malone www.usedtwoway.com



equipment for sale



Check out our Web specials! www.radiocomm.com

- •We have a Flat Rate Repair service.
- •We do Installations of MX-COM boards.
- ·Wholesale Prices to Dealers Only.
- •We carry a wide selection of both radios and accessories for your convenience. Shop at just one place rather than ten for all your communications needs.

800-726-9015 • 612-808-0069 fax: 612-808-0087

email: sales@radiocomm.com

Circle (78) on Fast Fact Card



Circle (79) on Fast Fact Card

MOTOROLA RADIOS

RADIUS — RADIUS — RADIUS

Tons in stock at USA's lowest prices SP50—P110—GP300—SM50—SM120—M120—GM300 will absolutely be SHIPPED TODAY!

Full line of previously owned trunked & conventional radios HT600/VISAR/HT1000/MT2000/MARATRACS/ TRUNKED 800 & 900 SPECTRAS/MAXTRACS/ PP1000X/MTX/MTX8000/VISAR/STX/EXPO

RADIO EXPRESS INC.

OFC: 800-545-7748 FAX: 703-830-8710 e-mail: radios4sale@juno.com All major credit cards accepted

Circle (80) on Fast Fact Card

TEST EQUIPMENT - BUY & SELL!! HP8902A Measurement Receiver-\$14,900, HP89018 Modulation, A \$2500, HP8903B Audio Analyzers-\$1850, HP4905A TIMS-\$800 S2900 HP1903B Audio An IFR COM 1208 (NEW) IFR COM 1208 TO INEW) IFR COM 120ATG HP3920A Marcon 2955A Marcon 29570 Moreota R2600C CBS Motorata R2600C CBS Motorata R2600C CBS \$9800 IFR 1500 (mint) \$10,500 IFR 11005 \$7900 IFR 12005 \$9900 Wavelet 35000/TOMA \$2800 Marconi 2957A \$7900 Marconi 29578 \$7900 Marconi 29575 \$15.900 Motorica A2001D Synth, 1000 Mhz Sig. Generators Pacal 9087: 1300Mnz Signal Gonerators, low phase noise, high stability, AMF Vi Pulsin/Phase Modulation, NEW units with warranty - 51800, HP8657A-52001

Amtronix Ph: 716-763-9104, 716-661-9964 Fax: 716-763-0371

CALL US FIRST at AIR COMM WHY PAY MORE!

Used/Reconditioned Motorola, E/GE, EFJ, Kenwood. Uniden 2-way radios and accessories -ALL FREQUENCY BANDS-PLUS

> "PL" and paging reeds/filters, TCXOS Call us last to sell any of the above. WE PAY CASH

COMM 4614 E. McDowell Rd.Ph.: 602-275-4505 4614 E. MCDOWEII NU.FII. 602 275-4555 Phoenix, AZ 85008 Fax: 602-275-4555

Description Process Process	CMC ENTERP	RISES
0.3 Motordo Gomparators signal to roses type		A COLUMN TO A COLU
5 0 MC-400 term cards \$50 ea.	0.3 Microto RUM- Muco Teuriking Repea 0.3 Microto Comparators signal to nois 4.0 Kernwood 601-5 Totch 42-50 mobil 0.4 Kernwood 601-5 Totch 42-50 mobil 0.4 Kernwood 801-5 Totch 42-50 mobil 0.4 Microto Maartac US 800 mbt LTR y 0.300mm flower beacons 0.4 12-50 amp battery chargers 2-4 0.5 Microto AMR-600 Non-standity loop ra 0.4 Microto AMR-600 hot-standity loop ra 0.5 Tarmon FAS-6000 terstandity loop ra 0.6 Tarmon FAS-6000 terstandity loop ra 0.6 Tarmon FAS-6000 terstandity loop ra 1.4 Farmon FAS-6000 terstandity loop ra 1.4 Microba Startara 453 as BFRTS tran 1.5 Scentific-Atlanta 45548 BFRTS tran 1.5 Scentific-A	ters who pwr amps \$300 ac o at type \$100 ac o \$100 ac o \$100 ac o \$200 ac o

CHANNEL ELEMENTS YOUR FREQ. - \$20.00

with trade-in/3 working days

MAXON, TEKK, UNIDEN/7working days

Channel Element HQ/Kirby Ent. 4120 Kirby Rd. Cincinnati, OH 45223

1-800-237-9654 FAX: 513/542-8870

GP-68 GP-88 **GP-300**

SPECIAL PRICES and in STOCK!

VHF 136-174 MHz UHF 430-470 MHz 20ch or 16ch

DTMF Keypad (CP-50/GP-68)

Features:

PL/DPL built-in 9 DTMF memories Auto or Programmable Repeater Offset 2 or 5W Power level

All (CP-50/GP-68) radios include: 3 hour rapid charger 1200mAh battery

E-mail: info@nsiradio.com



NSI Communications Tel: (253) 946-2426 Fax: (253) 946-8311

SAME DAY

SHIPPING

some items export only

equipment for sale





Circle (82) on Fast Fact Card



Because it works.

MRT Classifieds get results.
Call (800) 347-9375
to advertise next month.



IMPROVE AMPLIFIER RELIABILITY WITH THE MATCHMAKER



Load pull may be stealing years of life from your amplifiers. Glentech's

MATCHMAKER, an impedance optimizing device, significantly improves operating efficiency of any transmitter or amplifier. The MATCHMAKER improves operation into antennas and duplexers by allowing adjustment of efficiency and stability. The low-pass matching network reduces harmonics, often eliminating the need for a low pass filter. VHF, UHF and 800/900 Mhz models, rated to 500 watts, are available. All models include reflectometer output. Please call us or visit our web site for information on the MATCHMAKER.



Tele: 847-891-2584 Fax: 847-891-2587 www.glentech-r<u>f.com</u>

Circle (83) on Fast Fact Card

SABERS

- MOT SABER IE, H44SAG7139CN, UHF, 5 WATTS, 24 FREQ., EXCELLENT COND'N, DEC. 1993 S/NS......\$250 ea.
- MOT SABER II, H44SAJ7139CN, UHF 5 WATTS, 72 FREQ.\$340 ea.
- MOT MX300S, UHF, 5 WATTS, 24 FREQ., WITH BATT, PROM, ANT, MULTI PL . \$50ea.

Personalized Service. Best Prices Guaranteed!

Call 901-755-1514

Box 38881

Germantown, TN 38183

EQUIPMENT FOR SALE

Radius

Surplus sale of 2-position Motorola CentraCom II radio console with Central Electronics Bank. Sale is of electronics only, no furniture except CEB enclosure. Sealed Bids received until 10/19/98, publicly opened at Milford Area Comm Ctr, 1 Union Sq., Town Hall, Milford, NH 03055. Further information and appointment for equipment inspection may be obtained by contacting Director Joan Wetherall at 603-674-1414. M.A.C.C. reserves the right to reject any/ and or all bids and to waive all formalities.

equipment for sale

All CCII Labels

WHITE, ORANGE, GREEN AND RED **BUTTONS AVAILABLE**

\$12.50 ea

CCII PROGRAMING AVAILABLE ORDERS SHIPPED IN 14 DAYS

NORTHEASTERN

Communications, Inc.

Waterbury, CT (203) 575-9008

EQUIPMENT FOR SALE MOT Mental 800ms MOT Manufac Now board mobilies 100w 42-50mc whace MOT Manufac Now board mobilies 100w 42-50mc whace MOT Manufac UHF mobilies 110w, whose MOT Manufac UHF mobilies whate MOT Manufac 100w board shadows 30 42mc MOT Manufac 100w board shadows 30 42mc MOT Manufac 100w board shadows 30 42mc MOT Manufac UHF 50w board shadows MOT Manufac UHF 50w board MOT Manufac Manufac 10w force of duty shaw semble unlabed chalasts 41 cabends MOT Manufac Manufac 10w force 2 receivers yellod chalasts 41 cabends MOT Manufac mobiles UHF 10w, whace MOT Manufac mobiles UHF 10w, whace MOT Manufac 45-50ms (UMF whitelies whace MOT Manufac 45-50ms (UMF whitelies whace MOT Manufac 45-50ms (UMF whitelies whace MOT Manufac UHF flow mobiles whace MOT Manufac UHF flow mobiles whace MOT Manufac WHF post, 110w Model C73MHY3101AT 61 cab. MOT Mater Row mobiles 2 freq **EQUIPMENT FOR SALE** \$395 ea \$435 ea \$195 ea \$160 ea \$175 ea \$1090 ea \$500 \$600 \$1500 ea \$1400 \$210 ea \$200 ea 5390 ca \$395 ea \$165 ea \$136 ea \$190 éa \$145 ea \$146 ea \$100 ea \$750 ea \$500 ea \$155 ea \$295 \$525 ea in some locating GE Execution 0.75% URF mobile GE Matt # 60% mobiles, 42-50mc, wisco, GE PCS VIF portables, 2-freq 5100 ea GE PICS VIFF profibilities, 2 freq. \$20 GE VHF wearete importants \$20 GE PHOCHAIX SX VIFF mightins. \$16 GE PHOCHAIX SX VIFF mightins. value. GE PHOCHAIX SX VIFF tool mightins, value. GE PLIS VIFF fellow, profibilities, learned now, in bowes wichings. GE Delta VIFF mobiles, 10 fellow watch. GE Delta VIFF mobiles, 10 fellow value. GE Delta VIFF mobiles, 10 fellow value. GE Delta VIFF mobiles, 10 fellow value. GE Custom MVP mobiles. VMF or 1917 - water GE Mastri 1100e continuous diliy amelikies 136-42mc GE Mastri 1100e continuous diliy amelikies 136-42mc GE Mastri 1100e continuous diliy amelikies GE FMastri 1100e mobiles w PPL escolore, no acci GE Custom MVP 47-50mc mobile GG GE Executive II 1916 bits estation GE Executive II 1916 bits estation GE Executive II 1910 il hing mobile, 42-50mc ii oc occ Executive II 1910 il hing mobile, 42-50mc ii oc occ Executive II 1910 il hing mobile, 42-50mc ii occ occ Executive II 1910 il hing mobile, 42-50mc ii occ occ Executive II 1910 il hing mobile executive II 1910 il notatione II 1910 il notation II 1910 Tentionic Disclinations (Motel 475 with cigital findamenter very discin 174, 195 power motel engellens, 185 (56m; cgust 14 etc. august 251-100). S100 sea Astron 183, 155 power supply. S12 DB Products VMP Displaces. GE PN 190402955 PS. Kerewas PRES (SV lov burdfasse status toaxidisms in box, 29 7 to 37 mc. General Riscl. 1951 C Signated Level Motel. Leerward Hadio 1531 C. Soured Level Nelper 532 ea. 104 califfred 1531 C. Soured Level Nelper 532 ea. 104 califfred 1531 C. Soured Level Nelper 532 ea. 104 califfred 154 califfred 15 Pre-Paid Orders Only . No Credit Cards, No C.O.D.s N.H. COMMUNICATIONS CO. P.O. Box 5342 • Manchester, NH 03108-5342

Tel: 603-668-3004 Circle (86) on Fast Fact Card

Voice Pager with Monitor

Available options:

- *Vibrator add \$5
- *Voice Storage add \$10
- *New NiCad Batteries \$6
- *Used chargers \$19
- *Extended Warranty 1 year \$19 2 Years \$18 per year 3 Years \$17 per year



☑ Durable Motorola KeyNote® pager

- □ Reconditioned to factory specifications
- We add our unique Monitor Adaptor Pager functions the same as a Minitor II® in Monitor mode
- 90 Day Warranty with optional extended warranty
- Price below is on Your Frequency and programmed to Your Paging Tones
- 51 100 units \$132 each 1 - 20 units \$135 each 21 - 50 units \$128 each over 100 units \$115 each Dealer prices only, end user prices slightly more
- *Minitor II pager repair just \$29.50 includes all Parts and Labor
- Minitor I & II tone reeds \$25 each
- *Minitor II Scan Adaptor (scan 2 channels) \$55 installed, or do it yourself kit \$45
- *Minitor II freq conversions (board swaps)

Wanted: Pagers - Minitor I

Paging and Wireless Service Center

International: 561-683-0022 Fax: 561-683-0059

e-mail:pwserctr@aol.com http://members.aol.com/pwserctr/home.htm



Circle (85) on Fast Fact Card

COMPLETE CHANNEL ELEMENTS YOUR FREQUENCY LIFETIME GUARANTEE \$25.00 - \$35.00

Crystals We Buy Used Elements

NKX


FAX 504-361-5526

1814 Hancock St. Gretna, LA 70053 504-361-5525 (in LA) * 800-237-6519 C.W. WOLFE COMMUNICATIONS 1113 Central, Billings, MT 59102

INVENTORY REDUCTION **NOW IN PROGRESS.**

BIG SAVINGS ON ALL OVERSTOCKED ITEMS.

Call 406-252-9220 or visit us at http://members.aol.com/cwwolfecom



Want to stand out in a crowd?

Try color!

Call Dawn at 800-347-9375 for more information.

equipment for sale

Professional Audio Accessories

GENUINE WHOLESALE

K-111



- The perfect Customer Service occessory, this 2-piece microphone is lightweight and offers superior audio clarity
- Mic. has clathing clip and PTT button on it's side
- Earland comes complete with an extra foain epicover.
- Mode for Motorola, Kenwood, Standard, Vertex, etc...



- Manufactured to work on the Motorcka Radius" line, this heavy-duty remote speaker mic, has excellent audio quality.
- Full warranty and wholesale pricing make this remote mic. a must have



- This microphone kit is complete with a very good quality, lightweight boom microphone and the most comfortable earloop available.
- Forbud has replaceable form ear cover
- In-line PTT button is complete with clothing (lip
- Made for Motorola, Kenwacd, Standard, Vertex, etc...

K.200



- Super-high quality single or dual muff headset for high-naise environments. Voted "Best in Class".
- Noise cancelling electret microphone.
- PTT button on earshell.
- Comfortable earcushions.
- Adjustable headband.



- High Audio Earbud.
- 2.5mm or 3.5mm connectors available
- Works on radio or with other accessories.
- Extra foam ear cover included free.

"WE are in business to increase YOUR business"

CALL NOW! (800) 959-2899

Web Site: www.kleinelectronics.com

e-mail: info@kleinelectronics.com

Circle (87) on Fast Fact Card

USED EQUIP

www.mosscom.com

Handheld Repeater Controller

Convert any handheld or mobile radio into a simplex or duplex repeater system. Ideal for setting up short-term emergency service repeaters at remote locations or disas-ter sites. SPECTRUM Phone: 800-566-2788



USED RADIOS at Low Prices!

- · MICOR
- · MITREK . BCA
- · PORTABLES
- MOCOM 70

- · MAXAR

- · GE · ACCESSORIES
- TONE ELEMENTS
 - · CHRYSTAL ELEM. BASE STATIONS

Large Quantities • (940) 433-5452

SERVICE MONITORS FOR SALE

MOTOROLA R-2038/D/HS \$5,900	IFR 1200-S \$6,200
MOTOROLA R-2008/D/HS \$5,900	IFR 1500 \$6,200
MOTOROLA R-2410-A \$4,800	HP-8920-B \$12,900
MOTOROLA R-200 L/C/HS . \$4,200	HP-8920-A \$10,900
MOTOROLA BLOGODICHIS SS 500	IEB-1600 \$10 900

FOR SALE 19 R-2038/D/HS SERVICE MONITORS FREQ. RANGE-1 MHZ TO 1 GHZ, SPECTRUM ANALYZER/ SWEEP, DUPLEX GENERATOR, MULTIMODE CODE SYNTHESIZER, CELLULAR/TDR TEST ASKING PRICE \$5,900 EACH

USED TEST EQUIPMENT WANTED RF IMAGING & COMMUNICATIONS 925-229-2034 FAX: 925-229-2035

http://www.best.com/~rfimage e-mail: rfimage@best.com

FOR SALE

Mobile Data Computers with docking stations. ITRONIX X-C 6250 Pentium 90 computers with 16 MB RAM, 340 MB hard drive, and vehicle mounting bracket. Purchased two years ago, 60 of the 68 units are still in original boxes. To view, contact Rob Henry, Director of Information Technology, at (319) 286-5390. To obtain specifics call Duffy Keller at (319) 398-7421. Submit bids to Purchasing Services Department, 50 2nd Avenue Bridge, City Hall, Cedar Rapids, IA 52401-1256. Mark bid envelope as "Bid for Mobile Data Computers." Opening date: September 15, 3 pm. The city reserves the right to reject any bid or withdraw equipment from sale.

www.usedradio.net

(Equipment list, prices & order capability all on the Web)

Motorola-Maxon-Kenwood

Portables ★ Base Stations ★ Mobiles SP10/P110/GP300/M120/GM300 SP2550/SL500/CPO510

Close-out Pricing!


American Radio Exchange Ofc: 888.260.7368 Fax: 310.312.5437

CRYSTALS

7 day delivery/\$6.00 888-678-9825 ph. 915-633-6209 fax

CUEMEKS ELECTRONICS

equipment for sale



Put the crisp, clean sound of Motorola quality to work for you with the clearly affordable TS10 portable radio. This tough talking two-way packs a lot of power in a compact, easy-to-use package, yet starts at just \$118.00.

Get your message through loud and clear with up to 2 watts (UHF, 1W-VHF) in a palm sized package. Your range could be up to 2 miles depending on the terrain.

- Synthesized models, VHF or UHF
- · Weighs just 11 ounces
- Select "dot" or "star" frequencies
- Rechargeable NiCad battery

The Motorola TS10 portable two-way radio will help you improve your bottom line by helping you stay in touch with one person or many. To learn how the TS10 can make a difference in your business, call us today.

ESFLIERS (**Exclusive territories available**

(M) and Motorola are trademarks of Motorola, Inc. FCC License Required. 'See dealer for details.

PROCOMM HDOTRS

1372 Harmony Ct.

Thousand Oaks, CA 91362 Ph: 800-497-2394 • 805-494-5078

Fax: 805-494-3115

e-mail: procommusa@aol.com www.procommusa.com

Circle (88) on Fast Fact Card

(540) 891-0569 We accept VISA and MasterCard Fax: (540) 891-0538

MECHEM ELECTRONICS

Massaponax Business Park 3605 Loren Whitney Drive Fredericksburg, VA 22408 Mailing Address: P.O. Box 7846 Fredericksburg, VA 22404

- Two-Way Radio Communications
- ► New and Reconditioned Radios
- ► Custom-Designed Radio Systems
- ► Repair and Programming
- **▶** Consulting

UHF 250W Repealers (Clear and Secure) Dual Syntor-X Secure VHF/UHF Dual Code

VHF DES Micor Bases and Repeaters MSF 5000 UHF Repeaters

MSR 2000 UHF Repeaters Master II VHF & UHF Bases & Repeaters

R1033 Test Sets

R1034 Line Test Sets

RTX 4005 Portable Test Sets RTK 4007 Auto Test Interface

URL Address: http://www.mechemelectronics.com

Circle (89) on Fast Fact Card

E-Mail: mechem@fls.infi.net

Guaranteed Best Price on

Radius KENWOOD

& Fire Department Pagers

SALES & SERVICE

It's in stock; we'll ship tonight!

800-53-RADIO

BUY & SELL QUALITY USED EQUIPMENT

Motorola • Uniden • Kenwood Johnson • VHF • UHF • 800MHz 900MHz • Mobile • Portables Repeaters

PLANO COMMUNICATIONS INC. 1-888-906-9006

EQUIPMENT FOR SALE

10 Motorola Purc 5000 VHF 350 Watt 9 Motorola Micor Purcs 375 Watt B93J2B1101 with Advanced Control Mods 10 Mot Nucleus Purc Hipower Simo Histab w/Batt Revert

2 ASC Controllers 10 GE MASTR II 800 Conv. 35 Watt Repeaters 22 900 MHz Purc 5000 DRC/ACB/Tone

6 Mot Micro 40-50 MHz Purc 375 watt 6 Mot 900 MHz Trunked MSF-5000 150 Watt Cont. 4 Mot T5272A 800 14 CH Controller 45 Mot Desktrac 800 T Repeaters

Mot Quantar 800

WE BUY USED RADIO EQUIPMENT
WE PAY THE HIGHEST PRICES
SCOTT COMMUNICATIONS
KEN SCOTT 406-745-3218
email: scott@montana.com

PROGRAMMING CABLES FOR MOTOROLA PRODUCTS

HT1000, MT2000-\$70 GP300, P110-\$50 • VISAR-\$110 HT600-\$48 • MOBILES-\$25 • SABER-\$55 HT50-\$50 • STX-\$35 • SPECTRA-\$ PROGRAMMING INTERFACE-\$95

ROADRUNNER COMMUNICATIONS

PO Box 654 · South River, NJ 08882

Phone: 732-254-3232 Fax: 732-257-4622

equipment for sale

Now you can be a dealer in a new line of

MOTOROLA 2-WAY RADIOS

WETEC ELECTRONICS

AUTHORIZED MOTOROLA TS-10 DISTRIBUTOR

Call Now 1-888-GO-WETEC, ext. 10

Visit our website at: www.wetec.com

Circle (90) on Fast Fact Card

Wireless... Remote... Control... Anything...

the wireless application solid ground. You have Technically, we are on nave the solutions.

We now have Flex capabilities in all of our

ONTROL SOURCE. WIRELESS

ITEMS

pagetap.com 303-337-4811 303-337-3084 PageTap, Inc. tele. fax

http://www.

CELLULAR & PAGER LABELS

KHCK with your company's logo. Warranty labels for batteries. Call us for free samples.

ADVANCE LABEL & TAG

1725 N. McDonald St. McKinney, TX 75069-8230

FAX: 972-548-2518 972-542-5345 www.altag.com

World Class Service for Worldwide Customers!

RIN AND SELL LISED MOTOROLA, GE AND ERICSSON FM

12 ea PURC 5003 Bases, 900MHz, C85JLB1101A 8 ea MICOR PURC Bases, 900 MHz, C75JZB1101A 11 ea MTX8000, 800MHz, H01UCH6D87AN 7 ea MTX6000, 800MHz, HOTUCHGD83AN TWO-WAY RADIOS **SCHAEFER**

RADIO CO. 130 West Fayette St. .O. Box 395 Denver, IA 50622 PHONE (319)

984-6115

FAX

(319)984-6220 7 ea MTX8000, 800MHz, 1010UCHGBISIAN
20 ea, MTX918, 800MHz H281GB5170
6 ea, MASTR II Rpr., 460MHz, 5C69VAUB88
1 ea, MICOR Comm. Rpr., 460MHz, 5C69VAUB88
2 ea, MICOR Bases, 460MHz, C64RCB1165AT
7 ea, SYNTOR X 900, 460DHz, 134RCJAUAK
5 ea, MICOR, 460DHz, 134RTJAUAK
33 ea, MTREK, 460MHz, 144JA6000
6 ea, 1014SSD, 460MHz, 144JA6000
6 ea, 1014SSD, 460MHz, 144JA6000 6 ea. JOHNSON 460MHz 7171A046A

14 ea PURC 5000 Bases, 900MHz, 02934A

6 es. JOHNSON 490MH; 7171A0464.
80 es. RADIUS 91010. 450MH; 7171A0464.
10 as. HT600, 450MH; H445VU/7120
2 es. HT50, 460MH; H245VU/7120
2 es. MT00R Base; 155MH; C73H1B1145
10 cs. MARATRAC, 155MH; T83XIA7DA2
7 cs. SYNTOR, 155MH; T83XIA7DA0
30 es. MT500, 155MH; Mised Models
0 es. SYNTOR, 95 MH; Mised Models
0 es. SYNTOR, 95 MH; Mised Models
0 es. SYNTOR, 97 M646MH; Mised Models
0 es. SYNTOR, 97 M646MH; Mised Models 19 ea SYNTOR X 30-50MHz, TYIVBJ/2044K 30 ea MARATRAC, 48MHz, T81XTA7DA3AK 33 ea MITREK, 48MHz, 1813JA4000 15 ea RAOIUS, 47MHz, D\$1LRA9DA5

10 ea MICOR Bases, 37MHz, C71RTB1406 2 es MICOR, 31MFz, 1718TN3400A 50 es Tone and DC Remote Desk Sets, Mixed Models 29 es, Local Central Desk Sets, 11903 28 ea Motorola SYSTEMS 90 Sirens

40 ea. Desktop Centracom I Tone Rémote Modules 3 ea. MARTI Phone Patches, L1159A WANTED: RADIUS, Bases, Mobiles, Portables & Repeaters • ALL HANGES & UHF Syntors

(2) Motorola Intrac 2000 F6235A and (1) Desktop central F2490. Never used. . All 3 for \$1500 (12) Motorola Desk Mics HMN1038A, like new .. \$35 ea. Cellwave Antenna 806-866mhz . . \$250 Motorola Spectra 800mhz L35KXM7174AM \$250 100 watt VHF Mitreks ... \$125 ea. GE CMX 8630 .. \$50 ea. 918-335-0885-Please leave message Will consider all offers.

NEW & USED EQUIPMENT MOTOROLA Radius ACCESSORI

Lowest Prices!

1-800-466-5345

PARTS

SYSTE

GP 300 VHF/UHF GP 88 VHF/UHF GP 68 VHF/UHF

Most popular models in stock! Complete Radius Line!

KENWOOD

New and Used

Special State & Local Gov. Discounts

1-800-264-9516 FAX 303-415-1557

COMMUNICATIONS WEST, LTD.

E-Mail: commwest@aol.com **DOMESTIC & EXPORT SALES**

LOWEST PRICES!

GE MASTR II Comb. EX76KKP66C, 100 watt. PLL excitiers, double cases, w/o accs. \$100 ea \$130 ea. \$50 GE MASTR II Comb. MX76KFP66A, w/o accs \$80 w/accs GE MASTR II Comb. EX76KKS66A, w/o accs... GOOD CONDITION BUT AS-IS, PLUS SHIPPING David Mathews • Ph: (205) 553-3059

BUYING ERICSSON-GE EQUIPMENT

BUYING ERICSSON-GE EQUIPM
CALL OR FAX FOR QUOTE
TO2310 Suitcase less printer, new
PD 638-6 VHF Duplexers
TO3380 IPE/DPE 200 Program kit
Factory net \$4000 new on sale
S825 Systems Control head
S990 128ch head wiwarranty
MVS MPH20 VHF 16ch scan w/acc
PHOENIX-SX 18ch non-scan
PHOENIX-SX 18ch non-scan
PHOENIX-SX UHF BRAND NEW w/acc
MLSL160 30-42 w/acc., new
MLSL261 42-50 8ch w/acc.
MTL UHF 4w Portable w/charger . 65 200 275 165 225 275 MTL UHF 4w Portable w/charger 225 5/100 .. 40 325 250 165 275 135 MVS Control panel 16ch scan MLS-I Control panel 8ch scan MLS-I Control panel sch scan ... MLS-I Control panel 16ch no scan ... MPA/MPD/PCS/MRK Speaker mic. MASTR II 42-50 110w less acc. MASTR II 150-174 110w no acc. MPS/MPR/MPX/MPI/MPE Chargers 40 115

NEW LONDON TECHNOLOGY 752 Alum Springs Road • Forest, VA 24551 Tel: 804-525-0068 • Fax: 804-525-0078

Nationwide Radio

HT1000 PORTABLES BELOW DEALER COST

equipment for sale

Compatible Motorola® Programming Equip



Circle (91) on Fast Fact Card

FOR SALE **MOTOROLA R-2038/D/HS SERVICE MONITORS**

FREQ. RANGE 1MHz TO 1GHz, SPECTRUM ANALYZER, DUPLEX GENERATOR, SWEEP MULTIMODE CODE SYNTHESIZER, CELLULAR

ASKING PRICE \$5900 EA. **5 UNITS AVAILABLE**

RF IMAGING & COMMUNICATIONS 925-229-2034 FAX: 925-229-2035 http://www.best.com/~rfimage e-mail: rfimage@best.com

READY

to post a job opening and promote your company in the Employment section of

Call Dawn Rhoden at 1-800-347-9375 or Fax 913-967-1735

MRT Classifieds!



closeout special

ip370 case with swivel

DEALERS

\$2.50 ea.

718-783-6000

EQUIPMENT FOR SALE Low Band Pagers 19 Mot Mentor I (HOHMMC1272AB) 5 Mot Minitor I (HohmMc1272AB) 4 Mot Minitor I Amphther/Chargers 19 Mot Mentor II Amphther/Charger Mot Mentor I Amphther/Charger Mot Mentor I Amphther/Charger LOT 2 Mont Montor Lamparetraments 3 Mont M*500 dect #143188U1164AN; 33 77 33 94 33 78 33 50 3 Mont M*500 Standard Rate Decktop Chargers Mont M*500 Speaker Mess 2 SE 4cc 164845BAX; 33 77, 33 78 33 94 2 iff Mohale Charger convertes less in the RU simplifies 18 Miss. Mont 6f & Standard leather cases

Low Band Mobile Radios

1 RCA 4ch 100w mobile (MCA1904116) 33.72 compi

3 Mot Mittek-Micro handsets

Tow Sand Base Stations

RSA 2ch 100w base (80A199A32C), wilocal remote
RSA 2ch desetop have station LOT 5

1013

UHF Portable Radios

Stan Utif Portables (HX340UtAS)
Stan Utif Portables (HX340UtAS)
Stan Ragio Chargers
Stan Speaker Mich
Figi Ten 18ch 14w portables
Figi Ten Fapid desk chargers
Figi Ten Speaker Mich
Figi Ten Speaker Mich

UHF Mobile Radios
Fun Ten 16ch 30w mobile ramp (F1M40-30929) LOT 7 Motorola INTRAC Station Alerting System (173,3625 MHz)
1 Mot INTRAC Desktop Confroher (12490A)
3 Mot INTRAC 2000 Stating Francoisers (16253A)

ent is being sold in lots and is not being bloken open in inchases. All equipment was taken out of service in operation of is being sold in "as-is" condition.

cognined to safe is available for imprehen during the day shift Meeda its Friday, 7:30a to 3:30p at Fire Headquarters 1021 Blue Hills Ave learnfield CT 96002, phone (860) 243-8949 by appointment only Resided parties are asked to contact James R. Nanh. Jr.

Get results with MRT Classifieds!

paging

PAGING SERVICE PROVIDERS!

Add system capacity to your network easily and inexpensively with the new Kantronics Paging Controller 2000, priced under \$1,300.

This rack mountable, multi-mode controller can be configured as a:

- TNPP receive-only paging controller;
- Satellite-based simulcasting controller;
- First-in-line POCSAG repeater; or
- Down-stream POCSAG repeater.

The Paging Controller 2000 supports 512, 1200, and 2400 numeric and alphanumeric POCSAG, multiple transmitters, and channel sharing.

Kantronics Co., Inc.

Phone: 785-842-7745 Fax: 785-842-2031

Website: http://www.kantronics.com E-Mail: sales@kantronics.com

Circle (92) on Fast Fact Card

professional consulting services



After 1 month.

Don't let it happen.
Make sure the memory of your ad stays with your target audience.

CALL
Dawn at
800347-9375
today!


Engineering For The Wireless World Wireless Communications Systems and Facilities Define Acquire Build Manaae Design Zone Test Operate RCC Consultants, Inc. 100 Woodbridge Center Drive, Suite 201 Woodbridge, NJ 07095 800-247-4796 email - info@rcc.com Offices Nationwide & International

accessories

Circle (93) on Fast Fact Card



paging



Circle (94) on Fast Fact Card

Trust Your Radiofrequency Compliance To The Company With The Track Record

Managing site safety means more than just knowing about RF. RSI's programs are what your company needs to be prepared for all safety related issues!

OSHA Chemical/Battery
Storage Procedures
Fall Hazard Protection Procedures
Hazard Recognition · Record Keeping
OSHA Confined Space Procedure
(OSHA says most tower sites have confined spaces)

FCC/OSHA EME Safety



Radiofrequency Safety International Corporation

1-888-830-5648

1310 Main · Kiowa KS 67070 fax 316-825-4324 Learn more about Telecommunications Safety issues at our website:

www.rfcomply.com

Custom In-House Safety Programs
RFR Train the Trainer
Superior Survey Techniques® Seminars
RF Supervisor Training Courses
RF Emissions Inventory Database®
General OSHA Safety Training
Computer MPE Analysis
Custom In-House Safety Videos
'Get on Board" Programs for Major Companies

Circle (95) on Fast Fact Card

Invest your advertising dollars where your prospects invest their time...



paging

rentals



Call now to reserve space in next month's issue of MRT!

MOTOROLA RADIO RENTALS

- HT1000, GP300, P200
- Intrinsically Safe
- Full Line of Radio Accessories
- Mobiles & Repeaters
- 24-Hour Service
- Dealer Inquiries Invited

1-800-283-COMM

EVENT RENTAL COMM., INC. e-mail: eventcomm@aol.com



computer software

HERALD Radio Link **Design Software**

Network Topology, Profile Analysis, Link Budget, Rain, Multipath, Space Diversity, Reflections, Repeaters...

HERALD is the answer

- ITU-R / Bell Labs propag, models
- Highly productive & user-friendly
- Customized Equipment Libraries
- Help with Background Theory

Reliable, Quick, and Easy

For a Demo Disk please call: Radio Engineering Services, Torino, Italy Fax: +39-011-8192120 Email: herald@alpcom.it

Circle (97) on Fast Fact Card

Classifieds are a smart, inexpensive way to reach your target audience!

Call (800) 347-9375 for details, or fax to: (913) 967-1735

Form 600 Made Painless

- * Print your FCC Form 600 on plain paper
- * Prepares Form 600 for all Radio Services
- * Convenient menu selection of answers
- * Metric & NAD conversions included

By express \$350 By mail \$325

Brown and Schwaninger

Call for demo disk

202/223-6041

Circle (98) on Fast Fact Card



The worst mistakes are the ones you can't see.

Global Trunkina Management & Billing Solutions for ...

SmartNet • SmartWorks • SmartZone LTR • MPT 1327

For more information, call (903) 561-6673 or www.GenesisWorld.com



Circle (99) on Fast Fact Card

computer software



e V e | 2.0

- Seamless rasterized topographic maps
- International enhancements
- Import of multiple terrain data formats
- Biby-D advanced propagation model

 MapInfo file import
 CDS matrix calculation method

RFCAD provides high-resolution propagation results overlaid on seamless rasterized topographic maps. RFCAD has designed to the control of the been designed to enable the most efficient and accurate planning, and analysis of RF sites, and systems.



Communications Data Services. Inc

Circle (100) on Fast Fact Card



To Your RF Coverage and Site Management Problems... On your own PC!

For either microwave links or area coverage, our Terrain Analysis Package (TAP)™ software helps you find system design solutions in-house.

See details and download demo from our web site!



SOFTWRIGHT, LLC

1010 So. Jouet St. Suite 204 AURORA, CO 80012-3150 USA Tel. (303) 344-5486 • Fax: (303) 344-2811 www.softwright.com

e-mail: sales@softwright.com

Circle (101) on Fast Fact Card

Use COLOR to make vour ad STAND OUT!

** WIRELESS SOFTWARE

Save time designing, optimizing and managing wireless Radio communication sites:

- Intermodulation Interference Analysis
- Transmitter Noise Analysis - Receiver Desense Analysis
- Signal Level Analysis
- Communications Site Design
- Site Management Database
- Equipment Maintenance and Inventory
- Desktop Mapping and Data Products

CALL 800-845-0408 or 850-906-0748 http://www.polaris.net/~douglas

Service - Sales - SMR Billing Pager Billing - Accounting

NOW AVAILABLE CRI - PRO YEAR 2000 COMPLIANT

DOS · NOVELL · LANTASTIC · UNIX

We can provide complete solutions including software, hardware, and training.

205-987-1523/205-987-1709 FAX

Circle (102) on Fast Fact Card

Radio Propagation Software for PC's / WINDOWS

- LMR Predicted Area Coverage Multi-Site Composite Coverage Maps
- No Radial Generation Required Real Time Propagation Study / Profiles
- DXF / BMP File Formats Interface with AutoCAD, MapInfo
- Multiple Propagation Models Longley-Rice, Okumura, Field Strength
- VHF UHF / Microwave Point-to-Point Path Profiles and Link Analysis
- 30 Meter and 3 Second Terrain Data Entire USA On Single CD-ROM




95/NT*

Micropath® Corporation

2023 Montane Drive East • Golden, Colorado 80401-8099 Tel: (303) 526-5454 • Fax: (303) 333-4386

e-mail: microinfo@micropath.com • www.micropath.com



Shop from the comfort of your own keyboard at

www.internettelephony.com



PRIMEDIA Intertec



repair services

Programming - Same-Day Turnaround on Most Makes and Models We Service Most Makes & Models • Fast Turnaround • 15% Discount on Service Parts



GENERAL

DISTRIBUTORS OF MOBILE COMMUNICATIONS EQUIPMENT 800-356-3200 · www.gencomm.com

5157 Anton Drive • Madison, WI 53719 • 608 271-4848 • FAX 608 274-2080

Circle (103) on Fast Fact Card

\$25.00 FLAT RATE On the following models: RH-250 WH-2516 XLH-250 RH-256 WH-2510 UC-102 UC-202 4 TRH-202 REGENCY/WILSON

OTHER MODELS-\$30/HR Plus Parts & Shipping

MULTICOM . FAST TURNAROUND

5 Broadway ore, OK 73160 -799-7356 FACTORY TRAINED 800-880-7356 • VISA - MASTERCARD - COD

Advertise in MRT!

Two Way/Paging Test Instruments

Sales of New and Used

Get Your Test Equipment Needs From Service Professionals

We Take Trade-ins and Buy Used Monitors

Repair and Calibration of Communication

Service Monitors

www.nselectronics.com

NS Electronics Service, Inc. 3610 Dekalb Technology Pkwy. Suite 110/111

Atlanta, GA 30340 Telephone: 770-451-3264 Fax: 770-458-8785



Dawn Rhoden

1-800-347-9375 Classified Advertising Manager



Loudoun Communications Inc.

Communications Systems

REPAIR DEPOT

QUALITY SERVICE ON MICROPROCESSOR-BASED MOBILES. PORTABLES AND CONTROL HEADS. SURFACE MOUNT REPAIR. MOST REPAIRS \$70 PLUS PARTS.

FREE ESTIMATES. Warranty Service Available On:

Ericsson/G.E. · Kenwood

585 Factory Shoals Rd. Austell, Ga. 30168

770-948-9566





- Quick Turn Around Free Return Shipping
- Factory Trained & FCC Licensed Techs

4RCOM 800•567•5636

11420 NW 45th Place - Sunrise, FL 33323

Regency, Relm, Maxon

Professional Two-Way Radio Repair UHF, VHF, 800 mobiles & portables, PAs Reasonable rates, quick turn-around

TA RADIO COMMUNICATIONS

00 S. John Rhodes Blvd. #C1, W. Melbourne, Ft. 32904 Ph; 407-725-4824 Fax: 407-984-9484

\$40.00 FLAT RATE

PLUS PARTS & SHIPPING/HANDLING PLECTRON & INSTALERT MONITORS

TWO-WAY REPAIRS ALL MAKES & MODELS MOTOROLA MINITOR II PAGERS \$40,00/HR, PLUS PARTS & SHIPPING/HANDLING

FAST TURNAROUND, FCC LICENSED TECHNICIAN CENTURION COMMUNICATIONS, INC.

892 N. DELSEA DR. VINELAND, NJ 08360 PH: (609) 794-8000 FAX: (609) 794-8989

WORLDWIDE ELECTRONIC

22 Years In Business
Two Way Portable & Mobile
Factory Trained & FCC Licensed
Technicians
2 Way \$45 Flat Hate plus Parts
(718) 448-1717
1208 Bay Street, S.I. NY 10305

IT IS POSSIBLE!!!
to receive quick, quality, service at affordable rates

We repair:

Transmitter Amplifiers

Tower top Amplifiers. (most makes & models)

Filters, duplexers & combiners re-tuning.

Special custom projects & equipment modifications.

ADVANCED COMMUNICATIONS
& ELECTRONICS INC.

1036 Woodhaven Drive [804) 610-5475
Lynchburg, VA 24502-3757 Fax:Phone; (804) 237-4762
E-Mail: advoomm@worldnet.atl.net

Small cost **BIG** results MRT Classifieds

tower space

We've made your highest expectations our goal for over 30 years!



CHALLENGE US

WELL PUT YOU ON SITE, ON TIME 3

- **Turn-Key Solutions**
- Specialized Assignments
- Owners/Operators

If you need Florida or Metro New York , You're in our backyard!

Phone (813) 854-1518 Fax (813) 855-1969

World Wide Web: http://highpoint-inc.com E-Mail HIGHPOINT@IBM.NET

Circle (104) on Fast Fact Card



Resco Tower

Sites available **GA and SC**

We build to suit.

Call Miles McSweeney 912-233-9354

NEED TENANTS??

Advertise your sites in the

NATIONAL COMMUNICATIONS SITE DIRECTORY

Dedicated to advertising antenna sites for lease

NEED SITES?

The NCSD contains thousands of prime antenna sites, all with space for lease Just \$25 per year. For information call: Tel: (732) 462-5964 Fax: (732) 308-4633

ARIZONA'S PREMIER TOWER FACILITIES Contact Rick or Charlie Bonifasi ANTENNA SITES, INC. 800-346-7224

METRO PHILLY & METRO NYC

Nassau Tower Holdings has tower space available in NJ Sussex, Warren, Monmouth, Ocean and Mercer Counties. Downtown Princeton NOW AVAILABLE! Call Tony Gervasi at 609-924-1515, ext. 213



CHECK THE FACTS THEN **CALL THE BEST!**

CHICAGO TOWER LEASING CORP.


Environmentally controlled equipment enclosures, back-up power. RF engineered sites. Secure

Premiere sites in Metro Chicago Area-choice of Federal State, Govt. & all Class A Systems

105 MURPHY LAKE ROAD PARK RIDGE, IL 60068

(847) 823-7713

Better RUN to get your ad in next month's MRT!



Call Dawn Rhoden at 800-347-9375 today!

MINIATURE TOWER MODELS www.creativesculptures.com



Pewter Castings, Specialty Awards & Gifts for the Wireless Communications Industry.



6205 E. Tecumseh St., Tulsa, OK 74115 Ph: 918-832-9930 Fax: 918-834-9159

Toll-Free: 888-229-5325 e-mail: marksmith@ creativesculptures.com

tower services



- Engineering
- Installation
- Service
- Maintenance

Swager is your worldwide turnkey tower company.

Phone 1-800-968-5601 or Fax 1-800-882-3414



SWAGER

P.O. Box 656 3560 East Swager Drive Fremont, IN 46737 USA Phone I-800-968-5601 • 219-495-2515

Fax 1-800-882-3414 • 219-495-4205 E-mail: sales@swager.com

Internet: www.swager.com

Circle (105) on Fast Fact Card

Do You *comply*

All sites must be in compliance with the new Federal RF Exposure Guidelines



You need the recognized leader in radio frequency and electromagnetic

exposure evaluations

Providing complete training and regulatory assistance in the area of environmental and safety compliance

Argent Consulting Services, Inc.

Please note our new address 11999 Katy Freeway, Suite 590 Houston, Texas 77079

1-800-634-3947 • Fax 1-800-311-1278 See our website for the latest RF updates www.argentinc.com

Want more information on advertised products? Use the Fast Fact Card.

Professional Training and A Tan. Only at CMC'98!

Wireless equipment manufacturers, distributors and independent representatives have relied on CMA since 1973. The Communications Marketing Association sponsors CMC '98, a unique and indispensable training event, being held November 11–15, 1998 at the San Diego Princess Resort.

The annual CMC is precisely designed for the needs of wireless communications manufacturers, distributors and independent representatives to gather for product training, networking and educational seminars. No trade show distractions and lower costs than in-plant training.

Come to CMC for new lines to rep or new ways to distribute and market your products.

Call today to get on the training schedule or get more information about CMC '98. Your contact is Bernie Brownson, CMA Executive Secretary, at (303) 576-9475 or FAX (303) 371-8153. Check out our web site, too: www.commktga.com/cma.htm or e-mail us at

CMC '98
November 11-15

bernieb@commktga.com.



Circle (55) on Fast Fact Card

ad index

	Jan 1981		CONTRACTOR OF THE PARTY OF THE				
	Page	Fast Fact	Advertiser		Page	Fast Fact	Advertiser
Company	Number	Number	Hotline	Company	Number	Number	Hotline
AEA, a div. of Tempo Research	59	60	760-598-8900	Klein Electronics	71	87	760-631-2811
Andrew Corp.			708-349-3300	Marketronics Corp.		34	800-845-1230
Andrew Corp.			703-349-3300	Maxrad, Inc.			. 630-372-6800
Anritsu Company			408-778-2000	McManus Communications			870-763-6250
Anritsu Company			408-778-2000	Mechem Electronics			. 540-891-0569
Antenex			800-323-3757	Micropath Corp			303-526-5454
AF Comm Supply			800-255-6222	Microwave Filter Company Inc			. 315-437-3953
The Antenna Specialists Co			440-349-8400	Modular Communication Systems			818-764-1333
Astron Corp			714-458-7277	NARDA/L3 Communications			. 516-231-1700
Astron Corporation			703-450-5517	New Hampshire Communications			603-668-3004
			800-423-3858	Norcomm Corp.			. 916-477-8400
Barnett Electronics Inc.							
BatteryPRO Systems			800-661-9401	Optoelectronics Inc.			. 800-327-5912
BEE Electronics Inc.			800-336-3115	PageCorp Industries			. 800-957-8700
Berkeley Varitronics			908-548-3737	Paging & Wireless Service Center			. 561-683-0022
Bird Electronic Corp			440-248-1200	Pirod, Inc.	61		. 219-936-4221
Brown and Schwaninger			202-223-8837	Polaris Industries			. 404-872-0722
Cablewave Systems			203-630-3311	Polyphaser Corp			. 800-325-7170
Canadian Marconi	58	59	613-592-6500	Premiere	66		. 800-666-2654
CELWAVE	21	6	800-321-4700	Procomm		88	. 805-497-2397
Citel America, Inc	55	40	305-621-0022	Radio Engineering Services		97+3	9-011-8194575
CMA	80	55	800-288-8606	Radio Express, Inc	68	80	. 800-545-7748
Communications Specialists		3	800-854-0547	Radio Soft	56	65	. 904-426-2521
Communications Data Services	77		800-441-0034	RCC Consultants	75		732-404-2400
Computer Resources Inc			205-987-1523	RCW Distributing			. 800-726-9015
Control Signal Corp.			800-521-2203	RSI			. 316-825-4600
CPI Communications Inc.			972-437-5320	Samlex America Inc	53		. 604-525-3836
Crystronics		94	954-776-0031	Selectone			. 510-781-5432
Dapa Communications, Inc			716-373-7228	Sharp Communication			. 800-548-2484
Decibel Products, Inc.			214-631-0310	Shinwa Communications of America .			. 800-627-4722
Doppler Systems, Inc.			602-488-9755	Sinclair Technologies Inc.			. 800-263-3275
			520-204-2597	SoftWright			. 303-344-5486
EAGLE							
Eagle Wireless International			713-280-0488	Southwest Windpower			. 520-779-9463
EDX Engineering, Inc.			541-345-0019	Survey Technologies Inc	26		. 503-591-5986
El Paso Communication Systems			915-533-5119	Swager Communications			. 800-968-5601
EMR Corp.			602-581-2875	Telepath			. 510-656-5600
General Communications			800-356-3200	Thunder Eagle			. 703-242-0122
The Genesis Group			903-561-6673	TPL Communications Inc.	45		. 213-256-3000
Glentech			847-891-2584	Transcrypt International Ltd			. 800-894-2609
Grayson Wireless			804-386-5300	Trilogy Communications Inc			. 601-932-4461
Harger Lightning Protection			847-548-8700	Tripp Lite			. 312-755-8741
Helper Instruments Co			407-777-1440	TX RX Systems Inc			. 716-549-4700
Highpoint Tower Technology			813-854-1518	Vega, A Mark IV Company			. 626-442-0782
Richard Hirschmann of America			973-835-5002	VERTEX/YAESUUSA			. 310-404-2700
Huber & Suhner Inc			802-878-0555	Vocom Products Co. LLC			800-USA-MADE
Inspec, Inc			732-321-5575	Wacom Products Inc			. 254-848-4435
International Crystal Mfg	55	41	405-236-3741	WETEC Electronics		90	. 901-286-6275
J.E.I		61	916-677-3210	W & W Associates	27		. 800-221-0732
Kantronics	74	92	785-842-7745	Zetron Inc	33	29	. 425-820-6363
1000 000 000 000 000 000 000 000 000 00				Zetron Inc.	57	56	. 425-820-6363
							A ROBERT STORY OF THE STORY OF

Vertex--For Business, Industry, and Public Safety.

Vertex Radio Communications, the land mobile division of Yaesu, has been at the forefront of high-tech engineering and quality manufacturing for over 40 years. Always keeping customer satisfaction as their goal, the Vertex line meets the ever-growing demands of private sector, public safety, and governmental organizations.

The Vertex full line of wireless radio equipment is compatible with commercial specifications worldwide, and includes a wide variety of portable, compact/mobile base stations. HF/SSB transceivers.

repeaters, and trunking systems.

Incorporating constant customer feedback with break-through design in synthesized radio communication technology has resulted in innovative products like the FTH-2070 32 Channel 5W Dual Band VHF/UHF Portable radio introduced in 1988. This unequaled radio gained immediate acceptance for its ability to link public safety organizations in time of crisis, and remains unique to Vertex today.

Now, with its expanded lineincluding the ultra-compact VX-10, 40 and 102 Channel VHF/UHF Portables -- Vertex Radio Communications provides solutions to communication needs for business, industry, and public safety.

For more information about the complete line of Vertex Radio Communications products, see your authorized Vertex dealer, or call:


562-404-2700





United States & Canada: Yaesu U.S.A., (562)404-2700. Mexico, Central & So. America, (305)593-2500 ©1998 Yaesu USA. Specifications subject to change without notice.

Circle (2) on Fast Fact Card



SS-64 \$28.95 Microminiature DIP Switch Programmable CTCSS Encoder. Includes 64 tones from 33.0 to 254.1 Hz. .66" x 1.08" x .21"



\$54.95 TS-64 Sub-miniature Programmable CTCSS Encoder-Decoder. Includes 64 Iones from 33.0 to 254.1 Hz. .78" x 1.70" x .25"



TS-64DS DIP Switch Programmable CTCSS Encoder-Decoder. Includes 64 tones from 33.0 to 254.1 Hz. 1.25" x 2.0" x .30"



ANI-1/\$39.95 ANI-2/\$299.95 Automatic Number Identification System ANI-1 Encoder - 1.13" x .66" x .22" ANI-2 Station Decoder - 5.4" x 5.8" x 1.4"




ID-8 Automatic Morse Station Identifier, Meets all FCC ID Requirements. Fully field programmable with included keypad. 1.85" x 1.12" x .35"



Full Featured Shared Repeater Tone Panel with ALL 157 CTCSS/DCS codes. In Desktop or Back Mount versions.



\$224.95 Desktop Paging Encoder, Two-Tone Sequential, other formats available, 7.5" x 7.8" x 2.7"



\$59.95 Two-Tone Sequential Decoder, Programmable unit provides switched outputs from Two-Tone paging calls. 1.25" x 2.0" x .4"



\$54.95 Two-Tone Sequential Encoder. Sub-assembly mounts inside radio or other enclosure. Multiple call capability. 1.25" x 2.0" x .4"



\$59.95 Digital Coded Squeich Encoder-Decoder. Programmable to all 106 DCS codes. 1.36" x 1.18" x .25"



TF-640 \$129 90 Multi-Purpose CTCSS/Burst Tone Encoder w/LED Display. Great for the Benchtop. 5.25" x 3.3" x 1.7"



FILTERS Call us for the lowest cost, 12.5kHz channel spacing, exact replacement, crystal and ceramic IF filters for Part 90 Refarming.

See our complete catalog and product descriptions on our web site at

Circle (3) on Fast Fact Card

- Same reliable and cost effective products you have known and trusted for 30 years!
- Full FIVE YEAR WARRANTY on all products
- "INFO FAX" with 24 hour information
- Same day shipping on most orders
- Toll free 800 numbers for both voice and FAX



COMMUNICATIONS SPECIALISTS, INC.

426 WEST TAFT AVENUE • ORANGE, CA 92865-4296 (714) 998-3021 • FAX (714) 974-3420

ENTIRE U.S.A. (800) 854-0547 •FAX (800) 850-0547

